



## 2015 Q5/SQ5 Q5 Hybrid



Engine	Part	Part Number	Quantity
	Oil Filter	06J115403Q	1
2.0L TFSI: CPMB	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	8K0133843M	1

Engine	Part	Part Number	Quantity
	Oil Filter	06J115403Q	1
2.0L TFSI Hybrid: CHJA	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
J.,,,,	Drain Plug Gasket	N 0138157	1
	Air Filter	8R0133843K	1

Engine	Part	Part Number	Quantity
	Oil Filter >> 25.11.2014	06E115562A	1
	Oil Filter 25.11.2014 >>	06E115562C	1
3.0L V6: CTUC	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use O-ring:	8K0133843 N 90964301	1

Engine	Part	Part Number	Quantity
	Oil Filter >> 25.11.2014	06E115562A	1
3.0L V6: CTUD	Oil Filter 25.11.2014 >>	06E115562C	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use O-ring:	8K0133843 N 90964301	1

6-15-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.





### **Audi**

# 2015 Q5/SQ5 Q5 Hybrid

Engine	Part	Part Number	Quantity
	Oil Filter	059198405	1
3.0L TDI: CPNB	VW 507 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.4L (6.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use O-ring:	8K0133843D N 909643901	1

Miscellaneous	Part	Quantity	
	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left)	8R1955425B	1
Miscellaneous	Passenger's Wiper Blade (Right)	8R1955426B	1
Miscellaneous	Battery	000915105CCDSP	1
	Battery	000915105CDDSP	1
	Battery	000915105CEDSP	1
	Battery	000915105CFDSP	1

#### Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle.

You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the CAR function button > Service interval display > Reset oil change interval or CAR function button > Car systems\* control button > Servicing & checks > Service intervals > Reset oil change interval.

6-15-2015

## **Executive Service**



## 2015 Q5/SQ5 Q5 Hybrid





#### Note

- Only reset the oil change display when you have completed an oil change.
- If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear.
   Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Do not exceed the time interval for the next service, even if the vehicle mileage is low.



#### Tips

The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

6-15-2015

Audi Truth in Engineering

### Q5 - 2015 FLUID CAPACITY CHART Final July 31, 2014

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q5 SUV quattro (8RB52A)	2.0 TFSI 220 hp (CPMB)  4.6 L (4.9 qt)  Audi Oil Spec** VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBK/OBL)  New Fill: 8.6 L approx. (9.0 qt.)  Refill 3.6-4.0 L (3.8-4.2 qt.)  Oil PN G 060 162 A2*  Transfer Case 1.0 L (1.1 qt.) Oil PN	Front F/Drive New Fill: 1.0L (1.1qt)  Oil PN G 052 145 S2*  Rear F/Drive (0BD)  1.0L (1.1qt)  Oil PN G 052 145 S2*	10.0 L (10.5qt)***	Electromechanical	1.0 L (1.1qt) (approximately)  VW Brake Fluid Specification:  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703  Fluid PN B 000 750*	Refrigerant Use only R134a 630g ± 15g (22.3 ± 0.5 oz.)  Refrigerant Oil Use a PAG oil with R134a  Oil Capacity & PN For Denso  150 cc +/- 10 cc (5.1 ± 0.3 oz.)  G 052 300 A2*	4.6 L (4.9 qt.)  Fluid PN G 052 164*
Q5 Hybrid SUV quattro (8RB5GA)	2.0 TFSI 211 hp (CHJA)  4.6 L (4.9 qt)  Audi Oil Spec**  VW 502 00  Use synthetic oil  SAE 5W-40,  SAE 5W-30 or  SAE 0W-40	8-Spd Tiptronic (OBW) New Fill: 8.6 L approx. (9.0 qt.) Refill 4.0 L (4.2 qt.) Oil PN G 060 162 A2*  Transfer Case 1.0 L (1.1 qt.) Oil PN G 052 145 A2*		10.0 L (10.5qt)***			Refrigerant Use only R134a 900g ± 15g (31.7 ± 0.5 oz.)  Refrigerant Oil Use a PAG oil with R134a  Oil Capacity & PN For Denso  200cc +/- 20 cc (6.7 ± 0.3 oz.)  G 052 300 A2*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2014 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

<sup>\*</sup> Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

<sup>\*\*</sup>Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

<sup>\*\*\*</sup> Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.

### Q5 - 2015 FLUID CAPACITY CHART Final July 31,



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q5	3.0L V6 272 hp	8-Spd	Front F/Drive	12.0 L (12.7qt)***	Electromechanical	1.0 L (1.1qt)	<u>Refrigerant</u>	4.6 L (4.9 qt.)
SUV	(CTUC)	Tiptronic	New Fill:			(approximately)	Use only R134a	
quattro		(OBK/OBL)	1.0L (1.1qt)				630g ± 15g	Fluid PN
	6.8 L (7.2 qt.)						$(22.3 \pm 0.5 \text{ oz.})$	G 052 164*
(8RB57A)		New Fill:	Oil PN			VW Brake Fluid		
		8.6 L approx.	G 052 145 S2*			Specification:	Refrigerant Oil	
	Audi Oil Spec**:	(9.0 qt.)					Use a PAG oil	
	VW 502 00					Use new fluid only.	with R134a	
	Use synthetic oil	<u>Refill</u>	Rear F/Drive			51.0.00 440 DOT		
	SAE 5W-40,	3.6-4.0 L	(0BD)			FMVSS 116 DOT	011 0 11 0 011	
	SAE 5W-30 or	(3.8-4.2 qt.)	4.01. (4.4 = 1)			4	Oil Capacity & PN	
	SAE 0W-40	O:I DN	1.0L (1.1qt)			or SAE J 1703	For Denso	
		<u>Oil PN</u> G 060 162 A2*	Oil PN				150 cc +/- 10 cc	
		G 000 102 AZ	G 052 145 S2*				$(5.1 \pm 0.3 \text{ oz.})$	
		Transfer Case	G 052 145 52			Fluid PN	(5.1 ± 0.3 02.)	
		1.0 L (1.1 qt.)				B 000 750*	G 052 300 A2*	
Q5	3.0L TDI V6	Oil PN		12.0 L (12.7qt)***	AdBlue® Tank		Refrigerant	
SUV	240 hp (CPNB)	G 055 145 A2*		12.0 L (12.791)	AdDideo Tank		Use only R134a	
quattro	210 115 (01 112)	0 000 1 10 7 12			23.0L		630g ± 15g	
4	6.4 L (6.8 qt.)				(6.0 gal)****		$(22.2 \pm 0.5 \text{ oz.})$	
(8RB5VA)	(				(3.3.33.7)		(	
( /					ISO Standard		Oil Capacity & PN	
	Audi Oil Spec**:				22241-1		For Denso	
	VW 507 00							
	Use synthetic oil				Only fill with filling		150 cc +/- 10 cc	
	SAE 5W-40,				device VAS6542 &		$(5.1 \pm 0.3 \text{ oz.})$	
	SAE 5W-30 or				holding device			
	SAE 0W-40				SET740.		G 052 300 A2*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2014 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

<sup>\*</sup> Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

<sup>\*\*</sup>Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

<sup>\*\*\*</sup> Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.

<sup>\*\*\*\*</sup> Part Numbers for AdBlue® Reducing Agent: 0.5 gal (1.89 L) G 052 910 A2 for warranty repairs, 2.5 gal (10.0L) GUS 052 910 A3 for maintenance services.

### SQ5 - 2015 FLUID CAPACITY CHART Final July 31, 2014



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
SQ5	3.0L V6 354 hp	8-Spd	Front F/Drive	12.0 L (12.7qt)***	Electromechanical	1.0 L (1.1qt)	Refrigerant	4.6 L (4.9 qt)
quattro	(CTUD)	Tiptronic	New Fill:			(approximately)	Use only R134a	
(0DD50A)	0.01 (7.0 -1)	(OBK/OBL)	1.0L (1.1qt)				630g ± 15g	Fluid PN
(8RB5CA)	6.8 L (7.2 qt.)						$(22.3 \pm 0.5 \text{ oz.})$	G 052 164*
		New Fill:	<u>Refill</u>			VW Brake Fluid		
	Audi Oil Spec**:	8.6 L approx.	0.9 L (0.9 qt.)			Specification:	Refrigerant Oil	
	VW 502 00	(9.0 qt.)					Use a PAG oil	
	Use synthetic oil		<u>Oil PN</u>			Use new fluid	with R134a	
	SAE 5W-40,	<u>Refill</u>	G 052 145 S2*			only.		
	SAE 5W-30 or	3.6-4.0 L						
	SAE 0W-40	(3.8-4.2 qt.)				FMVSS 116	Oil Capacity & PN	
			Rear F/Drive			DOT 4	For Denso	
		<u>Oil PN</u>	(0BC)			or SAE J 1703		
		G 060 162 A2*					150 cc +/- 10 cc	
			0.9L (0.9qt)				(5.1 ± 0.3 oz.)	
		Transfer Case					_	
		1.0 L (1.1 qt.)	Oil PN			Fluid PN	G 052 300 A2*	
		Oil PN	G 052 145 S2*			B 000 750*		
		G 055 145 A2*						

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2014 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

<sup>\*</sup> Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

<sup>\*\*</sup>Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

<sup>\*\*\*</sup> Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.