



Engine	Part	Part Number	Quantity
<b>3.0L V6: CTWA</b>	Oil Filter >> 25.11.2014	06E115562A	1
	Oil Filter 25.11.2014 >>	06E115562C	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter PR-1L0	7L0129620	1
	Air Filter PR-1L2	7L0129620A	1

Engine	Part	Part Number	Quantity
<b>3.0L V6: CTWB</b>	Oil Filter >> 25.11.2014	06E115562A	1
	Oil Filter 25.11.2014 >>	06E115562C	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter PR-1L0	7L0129620	1
	Air Filter PR-1L2	7L0129620A	1

Engine	Part	Part Number	Quantity
<b>3.0L V6 TDI: CNRB</b>	Oil Filter	TBD	1
	VW 507 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	7.7L (8.1qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter PR-1L0	7L0129620	1
	Air Filter PR-1L2	7L0129620A	1

6-15-2015

Miscellaneous	Part	Part Number	Quantity
<i>Miscellaneous</i>	Pollen Filter (20K Only)	7H0819631A	1
	Driver's Wiper Blade (Left)	4L1955425B	1
	Passenger's Wiper Blade (Right)	4L1955426A	1
	Rear Wiper Blade	4L0955425	1
	Battery	000915105CEDSP	1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1
	Battery	000915105DLDSP	1

## Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle.

You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the **CAR** function button > **Systems\*** control button > **Service interval display** > **Reset oil change interval** or **CAR** function button > **Car systems\*** control button > **Servicing & checks** > **Service intervals** > **Reset oil change interval**.



### Note

- Only reset the oil change display when you have completed an oil change.
- If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Do not exceed the time interval for the next service, even if the vehicle mileage is low.



### Tips

The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

# Q7 - 2015 FLUID CAPACITY CHART

Final July 31, 2014



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	8 Speed Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
<b>Q7</b> SUV quattro  (4LB5KA)	<b>3.0L V6 280 hp (CTWB)</b>  6.8L (7.2 qt.)  <u><b>Audi Oil Spec**:</b></u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	<b>8-Spd Tiptronic (0C8)</b>  New Fill: 10.6L (11.2 qt)  <u><b>Oil PN</b></u> G 055 540 A2*	<b>Front F/Drive</b>  New Fill: 0.6-0.8 L (0.6-0.8 qt.)  <u><b>Oil PN</b></u> G 052 145 S2*  <b>Transfer Case</b>  New Fill: 0.65L (0.7 qt.)  <u><b>Oil PN</b></u> G 052 536 A2  <b>Rear F/Drive (0AB)</b>  New Fill: 0.9-1.1 L (0.9-1.1 qt.)  <u><b>Oil PN</b></u> G 052 145 S2*	15.0L (15.8 qt)***	1.0 L (1.1qt) (approximately)  <u><b>Fluid PN</b></u> G 002 000* or G 004 000*	1.0 L (1.1qt) (approximately)  <u><b>VW Brake Fluid Specification:</b></u>  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703  <u><b>Fluid PN</b></u> B 000 750*	<u><b>Refrigerant</b></u> Use only R134a  <u>1-Evaporator</u> 700g ± 50g (24.7 oz. ± 1.8 oz.)  <u>2-Evaporators</u> 1050g ± 50g (37 oz. ± 1.8 oz.)  <u><b>Refrigerant Oil</b></u> Use a PAG oil with R134a  <u><b>Oil Capacity</b></u>  <u>1-Evaporator</u> 145cc ± 15cc (4.9 oz. ± 0.5 oz.)  <u>2-Evaporators</u> 245cc ± 15cc (8.3 oz. ± 0.5 oz.)  <u><b>Oil PN</b></u>  G 052 300 A2*	4.5 L (4.8 qt)  <u><b>Fluid PN</b></u> G 052 164*
<b>Q7</b> SUV quattro  (4LB5XA)	<b>3.0L V6 333 hp (CTWA)</b>  6.8L (7.2 qt.)  <u><b>Audi Oil Spec**:</b></u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40							

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.

