



**2015 Beetle/Beetle Convertible** Das Auto.

Engine	Part	Part Number	Quantity
<b>1.8L Turbo: CPKA, CPRA</b>	Oil Filter	06K115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30	N/A	5.5L (5.7qt)
	Drain Plug Gasket	N-0138157	1
	Air Filter	5C0129620	1

Engine	Part	Part Number	Quantity
<b>2.0L Turbo Diesel: CVCA</b>	Oil Filter	03N115562	1
	VW 507 00 Use synthetic oil SAE-5W-30	N/A	5.5L (5.8qt)
	Drain Plug Gasket	N-90813202	1
	Air Filter	1K0129620D w/PR-0Y2	1
	Air Filter	1K0129620L w/PR-0Y3	1
	Fuel Filter (20K Only)	5Q0127177	1

Engine	Part	Part Number	Quantity
<b>2.0L Turbo: CPLA, CPPA</b>	Oil Filter	06K115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30	N/A	5.5L (5.8qt)
	Drain Plug Gasket	N-0138157	1
	Air Filter	5C0129620	1

Miscellaneous	Part	Part Number	Quantity
<b>Miscellaneous</b>	Pollen Filter	1K0819644B w/PR-9AB	1
	Pollen Filter	1K1819653B w/PR-9AK	1
	Wiper Blades (Left or Right)	5C1955425	1
	Battery	000915105DEDSP (61AH/330A)	1
	Battery	000915105CCDSP (68AH/380A)	1
	Battery	000915105DGDSP (72AH/380A)	1

## Resetting the oil change service reminder

If the service was not performed by an authorized Volkswagen dealer or an authorized Volkswagen Service Facility, the oil change service reminder can be reset as follows:

---

### Vehicles with Premium display:

---

---


1. Switch off the ignition.
  2. Press and hold the **0.0/SET** button in the instrument cluster.
  3. Switch on the ignition.
  4. Release the **0.0/SET** button.
  5. A confirmation message appears in the display. Confirm request with the **OK/RESET** in the windshield wiper lever or the **OK** button on the multi-function steering wheel.
- 

---

### Vehicles with Basic display:

---

---

1. Switch off the ignition.
  2. Push the **0.0/SET** button in the instrument cluster and hold down.
  3. Switch on the ignition.
  4. Release the **0.0/SET** button and push the  button in the instrument cluster within about 20 seconds.
- 

## Resetting the inspection service reminder

If the service was not performed by an authorized Volkswagen dealer or an authorized Volkswagen Service Facility, the inspection service reminder can be reset as follows:

---

### Vehicles with Premium display:

---

---

1. Switch off the ignition.
  2. Switch on the emergency flashers.
  3. Press and hold the **0.0/SET** button in the instrument cluster.
- 
-

---

**Vehicles with Premium display:**

---

---


4. Switch on the ignition.
  5. Release the **0.0/SET** button.
  6. A confirmation message appears in the display. Confirm request with the **OK/RESET** in the windshield wiper lever or the **OK** button on the multi-function steering wheel.
  7. Switch off the emergency flashers.
- 


---


**Vehicles with Basic display:**

---

---

1. Switch off the ignition.
  2. Switch on the emergency flashers.
  3. Push the **0.0/SET** button in the instrument cluster and hold down.
  4. Switch on the ignition.
  5. Release the **0.0/SET** button and push the  button in the instrument cluster within about 20 seconds.
  6. Switch off the emergency flashers.
- 

 Do **not** reset the service reminder between service intervals; otherwise incorrect information will be displayed.

 The service reminder disappears after a few seconds or after the **OK/RESET** button on the windshield wiper lever or the **OK** button on the multi-function steering wheel has been pushed.



Das Auto.



Das Auto.

**Beetle - 2015 FLUID CAPACITY CHART**

8/21/14

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>New Beetle</b> FWD Manual  (5C11R1) (5C12R1) (5C13R1) (5C11Q1) (5C12Q1) (5C13Q1)	<b>1.8L 170 hp (CPKA/CPRA)</b>  5.5 L (5.7 qt.)  <b>VW Oil Spec:</b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>5-Spd (0A4)</b> 1.9 L (2.0 qt.)  <b>Oil PN</b> G 052 527 A2*	<b>N/A</b>	<b>N/A</b>	8.0 L (8.5 qt.)***	0.7 – 0.9 L (0.7 – 1.0 qt) (approximately)  <b>Fluid PN</b> G 002 000*	1.0 L (1.1qt.) (approximately)  <b>VW Brake Fluid Specification:</b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <b>Fluid PN</b> B 000 750*	<b>Refrigerant</b> Use only R134a  <b>Refrig. Capacity</b> 525 ± 25 grams (18.5 + 0.8 oz)  <b>Refrigerant Oil</b> Use a PAG oil with R134a  <b>Oil PN &amp; Capacity</b> <b>Sanden Cmpr:</b> G 052 154 A2* 110 ± 10 cc (3.7 ± 0.3 fl.oz)  <b>Denso Cmpr:</b> G 052 300 A2* 90 ± 10 cc (3.0 ± 0.3 fl.oz)	3.6 – 4.5 L (3.8 – 4.7 qt.)  <b>Fluid PN</b> G 052 164*
<b>New Beetle</b> FWD Auto  (5C11R3) (5C12R3) (5C13R3) (5C11Q3) (5C12Q3) (5C1333)		<b>N/A</b>	<b>6-Spd (09G)</b>  <b>New Fill:</b> 7.0 L (7.4 qt.)  <b>Change:</b> 3.0 L (3.2 qt.)  <b>Oil PN</b> G 055 540 A2*	Capacity included with transmission					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\* Refer to technical bulletin 2012855 for engine oils that meet standard VW 502 00.

\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) **G 13** (TL-VW 774 J). **Dilute with Distilled Water.**

© 2014 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.



Das Auto.



Das Auto.

# Beetle - 2015 FLUID CAPACITY CHART

8/21/14

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>New Beetle</b> FWD Manual  (5C14N2) (5C15M2) (5C15N2) (5C15M2) (5C16N2) (5C16M2)	<b>2.0T 210hp (CPLA/CPPA)</b>  5.5 L (5.8 qt)  <b>VW Oil Spec:</b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>6-Spd (02Q)</b>  2.3 L (2.4 qt.)  <b>Oil PN</b> G 052 527 A2*	<b>N/A</b>	<b>N/A</b>	8.0 L (8.5 qt.)***	0.7 – 0.9 L (0.7 – 1.0 qt) (approximately)  <b>Fluid PN</b> G 002 000*	1.0 L (1.1qt.) (approximately)  <b>VW Brake Fluid Specification:</b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <b>Fluid PN</b> B 000 750*	<b>Refrigerant</b> Use only R134a  <b>Refrig. Capacity</b> 525 ± 25 grams (18.5 + 0.8 oz)  <b>Refrigerant Oil</b> Use a PAG oil with R134a  <b>Oil PN &amp; Capacity</b> <b>Sanden Cmpr:</b>  G 052 154 A2* 110 ± 10 cc (3.7 ± 0.3 fl.oz)  <b>Denso Cmpr:</b>  G 052 300 A2* 90 ± 10 cc (3.0 ± 0.3 fl.oz)	3.6 – 4.5 L (3.8 – 4.7 qt.)  <b>Fluid PN</b> G 052 164*
<b>New Beetle</b> FWD Auto  (5C14N3) (5C15M3) (5C15N3) (5C15M3) (5C16N3) (5C16M3)		<b>N/A</b>	<b>6-Spd DSG® (02E)</b>  <b>New Fill:</b> 6.9 - 7.2 L (7.3 – 7.6 qt.)  <b>Change:</b> 5.2L (5.5 qt.)  <b>Change Mechatronic:</b> 3.0-4.0 L (3.1-4.2 qt.) <b>Oil PN</b> G 052 182 A2*	Capacity included with transmission					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\* Refer to technical bulletin 2012855 for engine oils that meet standard VW 502 00.

\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.

© 2014 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.



Das Auto.



Das Auto.

**Beetle - 2015 FLUID CAPACITY CHART** 8/21/14

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>New Beetle</b> FWD Manual  (5C119L) (5C139L)	<b>2.0 TDI 150hp (CVCA)</b>  5.5L (5.8 qt.)  <u>VW Oil Spec:</u> VW 507 00** Use synthetic oil SAE 5W-30	<b>6-Spd (02Q)</b>  <b>2.3 L (2.4 qt.)</b>  <u>Oil PN</u> G 052 527 A2*	<b>N/A</b>	<b>N/A</b>	8.0 L (8.45 qt.)	0.7 – 0.9 L (0.7 – 1.0 qt) (approximately)  <u>Fluid PN</u> G 002 000*	1.0 L (1.1qt.) (approximately)  <u>VW Brake Fluid Specification:</u>	<u>Refrigerant</u> Use only R134a  <u>Refrig. Capacity</u> 525 ± 25 grams (18.5 + 0.8 oz)  <u>Refrigerant Oil</u> Use a PAG oil with R134a  <u>Oil PN &amp; Capacity</u> <u>Sanden Cmpr:</u>  G 052 154 A2* 110± 10 cc (3.7±0.3 fl.oz)  <u>Denso Cmpr:</u>  G 052 300 A2* 90± 10 cc (3.0±0.3 fl.oz)	3.6 – 4.5 L (3.8 – 4.7 qt.)  <u>Fluid PN</u> G 052 164*
<b>New Beetle</b> FWD Auto  (5C119M) (5C139M)		<b>N/A</b>	<b>6-Spd DSG® (02E)</b>  <u>New Fill:</u> 6.9 - 7.2 L (7.3 – 7.6 qt.)  <u>Change:</u> 5.2L (5.5 qt.)  <u>Change Mechatronic:</u> 3.0-4.0 L (3.1-4.2 qt.)  <u>Oil PN</u> G 052 182 A2*	Capacity included with transmission	<b>AdBlue® Tank</b>  14.7 L - (3.8 gal.)****  <u>ISO Standard</u> 22241-1		Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <u>Fluid PN</u> B 000 750*		

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\* Refer to *technical bulletin 2012855 for engine oils that meet standard VW 507 00.*\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) **G 13** (TL-VW 774 J). **Dilute with Distilled Water.**

\*\*\*\* Part Numbers for AdBlue® Reducing Agent: 0.5 gal (1.89 L) G 052 910 A2 for warranty repairs, 2.5 gal (10.0L) GUS 052 910 A3 for Carefree maintenance services.



## Beetle Convertible - 2015 FLUID CAPACITY CHART 8/21/14

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
FWD Auto  (5C71R3) (5C72R3) (5C73R3) (5C71Q3) (5C72Q3) (5C73Q3)	<b>1.8L 170 hp (CPKA/CPRA)</b>  5.5 L (5.7 qt.)  <u><b>VW Oil Spec:</b></u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>N/A</b>	<b>6-Spd (09G)</b>  <u><b>New Fill:</b></u> 7.0 L (7.4 qt.)  <u><b>Change:</b></u> 3.0 L (3.2 qt.)  <u><b>Oil PN</b></u> G 055 540 A2*	Capacity included with transmission	8.0 L (8.4 qt.)***	0.7 – 0.9 L (0.7 – 1.0 qt.) (approximately)  <u><b>Fluid PN</b></u> G 002 000*	1.0 L (1.1qt) (approximately)  <u><b>VW Brake Fluid Specification:</b></u>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <u><b>Fluid PN</b></u> B 000 750*	<u><b>Refrigerant</b></u> Use only R134a  <u><b>Refrig. Capacity</b></u> 525 ± 25 grams (18.5 + 0.8 oz)  <u><b>Refrigerant Oil</b></u> Use a PAG oil with R134a  <u><b>Oil PN &amp; Capacity</b></u> <u><b>Sanden Cmpr:</b></u>  G 052 154 A2* 110 ± 10 cc (3.7 ± 0.3 fl.oz)  <u><b>Denso Cmpr:</b></u>  G 052 300 A2* 90 ± 10 cc (3.0 ± 0.3 fl.oz)	3.6 – 4.5 L (3.8 – 4.7 qt.)  <u><b>Fluid PN</b></u> G 052 164*

**For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.**

**\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.**

**\*\* Refer to *technical bulletin 2012855* for engine oils that meet standard VW 502 00.**

**\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) **G 13** (TL-VW 774 J). Dilute with Distilled Water.**



Das Auto.



Das Auto.

**Beetle Convertible - 2015 FLUID CAPACITY CHART**

8/21/14

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
FWD Manual  (5C74N2) (5C74M2) (5C75N2) (5C75M2) (5C76N2) (5C76M2)	<b>2.0T 210 hp (CPLA/CPPA)</b>  5.5 L (5.8 qt)  <u>VW Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>6-Spd (02Q)</b>  2.3 L (2.4 qt.)  <u>Oil PN</u> G 052 527 A2*	<b>N/A</b>	<b>N/A</b>	8.0 L (8.4 qt.)***	0.7 – 0.9 L (0.7 – 1.0 qt) (approximately)  <u>Fluid PN</u> G 002 000*	1.0 L (1.1qt.) (approximately)  <u>VW Brake Fluid Specification:</u>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a  <u>Refrig. Capacity</u> 525 ± 25 grams (18.5 + 0.8 oz)  <u>Refrigerant Oil</u> Use a PAG oil with R134a	3.6 – 4.5 L (3.8 – 4.7 qt.)  <u>Fluid PN</u> G 052 164*
FWD Auto  (5C75N3) (5C75M3) (5C76N3) (5C76M3)		<b>N/A</b>	<b>6-Spd DSG® (02E)</b>  <u>New Fill:</u> 6.9 - 7.2 L (7.3 – 7.6 qt.) <u>Change:</u> 5.2L (5.5 qt.)  <u>Change Mechatronic:</u> 3.0-4.0 L (3.1-4.2 qt.) <u>Oil PN</u> G 052 182 A2*	Capacity included with transmission				<u>Oil PN &amp; Capacity</u> <u>Sanden Cmpr:</u>  G 052 154 A2* 110 ± 10 cc (3.7 ± 0.3 fl.oz)  <u>Denso Cmpr:</u>  G 052 300 A2* 90 ± 10 cc (3.0 ± 0.3 fl.oz)	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\* Refer to *technical bulletin 2012855* for engine oils that meet standard VW 502 00.

\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) **G 13** (TL-VW 774 J). **Dilute with Distilled Water.**

© 2014 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.





Das Auto.



Das Auto.

**Beetle Convertible - 2015 FLUID CAPACITY CHART** 8/21/14

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
FWD Manual  (5C719L) (5C739L)	<b>2.0 TDI 150 hp (CVCA)</b>  5.5 L (5.8 qt)  <b><u>VW Oil Spec:</u></b> VW 507 00** Use synthetic oil SAE 5W-30	<b>6-Spd (02Q)</b>  2.3 L (2.4 qt.)  <b><u>Oil PN</u></b> G 052 527 A2*	<b>N/A</b>	<b>N/A</b>	8.0 L (8.45 qt.)	0.7 – 0.9 L (0.7 – 1.0 qt) (approximately)  <b><u>Fluid PN</u></b> G 002 000*	1.0 L (1.1qt.) (approximately)  <b><u>VW Brake Fluid Specification:</u></b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4	<b>Refrigerant</b> Use only R134a  <b>Refrig. Capacity</b> 525 ± 25 grams (18.5 + 0.8 oz)  <b>Refrigerant Oil</b> Use a PAG oil with R134a	3.6 – 4.5 L (3.8 – 4.7 qt.)  <b><u>Fluid PN</u></b> G 052 164*
FWD Auto  (5C719M) (5C739M)		<b>N/A</b>	<b>6-Spd DSG® (02E)</b>  <b><u>New Fill:</u></b> 6.9 - 7.2 L (7.3 – 7.6 qt.) <b><u>Change:</u></b> 5.2L (5.5 qt.) <b><u>Change Mechatronic:</u></b> 3.0-4.0 L (3.1-4.2 qt.) <b><u>Oil PN</u></b> G 052 182 A2*	Capacity included with transmission	<b>AdBlue® Tank</b>  14.7 L - (3.8 gal.)****  <b><u>ISO Standard</u></b> 22241-1		<b><u>Fluid PN</u></b> B 000 750*	<b><u>Oil PN &amp; Capacity</u></b> Sanden Cmpr: G 052 154 A2* 110± 10 cc (3.7±0.3 fl.oz) Denso Cmpr: G 052 300 A2* 90± 10 cc (3.0±0.3 fl.oz)	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\* Refer to technical bulletin 2012855 for engine oils that meet standard VW 507 00.

\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.

\*\*\*\* Part Numbers for AdBlue® Reducing Agent: 0.5 gal (1.89 L) G 052 910 A2 for warranty repairs, 2.5 gal (10.0L) GUS 052 910 A3 for Carefree maintenance services.

© 2014 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.