

A5, A5 Cabriolet, S5 2016 FLUID CAPACITY CHART Update 17 Nov 2015

10, 710	<u>oabiioiot</u> , t	<u> </u>	<u> </u>	/ (OII OII	Titi Opaate 1	7 140 V 2013		9999
Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
A5	2.0L TFSI 220 hp	6-Spd	N/A	Front F/Drive	10.0 L (10.5 qt)***	1.0 L (1.1qt)	Refrigerant	4.5L (4.8 qt)
Coupe	(CAED)	(0B2)	-	New Fill:	(- 17	(approximately)	Use only R134a	17
quattro	4.5L (4.8 qt)	, ,		1.1L (1.2 qt)			550 g ± 15 g	Fluid PN
		4.5L (4.7qt)				Audi Brake Fluid	(19.5 oz. ± 0.5 oz.)	G 052 164*
(8T35G9)	Audi Oil Spec**			Oil PN		Specification:		
Manual	VW 502 00**	Oil PN		G 055 190 A2*			Refrigerant Oil	
	Use synthetic oil	G 055 532 A2*		Rear F/Drive		Use new fluid only.	Use a PAG oil	
	SAE 5W-40, SAE 5W-30 or			(0BC)			with R134a	
	SAE 0W-40			New Fill:		FMVSS 116 DOT 4		
				0.9L (1.0 qt)		or SAE J 1703	011.0	
				OH DN			Oil Capacity	
				<u>Oil PN</u> G 052 145 S2*			Denso 150 cc +/- 10 cc	
				G 052 145 52		Fluid PN	$(5.0 \pm 0.3 \text{ fl. oz.})$	
						B 000 750 *	(3.0 ± 0.3 11. 02.)	
A5	2.0L TFSI 220 hp	N/A	8-Spd	Front F/Drive		D 000 130	Fluid PN	
quattro	(CPMB)		Tiptronic	New Fill:			G 052 300 A2*	
	4.5L (4.8 qt)		(OBK/OBL)	1.0L (1.1qt)				
(057504)	A		New Fill:	Transfer Case				
(8F752A) Cabrio	Audi Oil Spec** VW 502 00**		8.6 L (9.0 qt)	New Fill: 1.1L (1.1qt)				
	Use synthetic oil		Change:	Change:				
	SAE 5W-40,		3.6 - 4.0L	0.8L (0.84 qt.)				
	SAE 5W-30 or		(3.8 - 4.2 qt.)	0.02 (0.0 : 4)				
	SAE 0W-40		(0.0 4)	Oil PN				
A5			Oil PN	G 055 145 A2				
Coupe			G 060 162 A2					
quattro				Rear F/Drive (0BD)				
(8T352A)				New Fill:				
(01332A)				1.0L (1.1 qt)				
				Oil PN				
				G 052 145 S2*				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.

^{© 2015} Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

A5, A5 Cabriolet, S5 2016 FLUID CAPACITY CHART Update 17 Nov 2015



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
S 5	3.0L V6 333 hp	6-Spd	N/A	Front F/Drive	12.0 L (12.6 qt)***	1.0 L (1.1qt)	Refrigerant	4.5L (4.8 qt)
Coupe	(CTUB)	(0B4)		New Fill:		approximately	Use only R134a	
quattro	6.8L (7.2 qt)			1.0L (1.1qt)			550 g ± 15 g	Fluid PN
		3.8L (4.0 qt)				Audi Brake Fluid	(19.5 oz. ± 0.5	G 052 164*
(8T3549)				Oil PN		Specification:	oz.)	
Manual	Audi Oil Spec**	Oil PN		G 052 145 S2*				
	VW 502 00**	G 052 911 A2*				Use new fluid		
S5	Use synthetic oil SAE 5W-40,		7-Spd DSG	Transfer Case		only.		
Coupe	SAE 5W-30 or	N/A	(0B5)	New Fill:			Refrigerant Oil	
quattro	SAE 0W-40		New Fill:	4.35L (4.5 qt)		FMVSS 116 DOT	Use a PAG oil	
			7.0 - 7.5L			4	with R134a	
(8T354Y)			(7.3 - 7.9 qt)	Oil PN		or SAE J 1703		
				G 055 532 A2*				
Cabriolet			Change:				Oil Capacity	
quattro			6.7L (7.0 qt)	Rear F/Drive			Denso	
(8F754Y)			approx.	(0BC / 0BF)		Fluid PN	150 cc +/- 10 cc	
				New Fill:		B 000 750 *	$(5.0 \pm 0.3 \text{ fl. oz.})$	
			<u>Oil PN</u>	0.9L (1.0 qt)			EL : 1 DN	
			G 052 529 A2*				Fluid PN	
				<u>Oil PN</u>			G 052 300 A2*	
				G 052 145 S2*				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.