Vehicle (Sales Code)	<b>Engine Oil</b> approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
A4 FWD <u>Sedan</u> (8K25GH)	2.0L TFSI 220 hp (CAED) 4.5 L (4.8 qt) <u>Audi Oil Spec**</u> VW 502 00** Use synthetic oil SAE 5W-40,	N/A	CVT (0AW) <u>New Fill:</u> 8.0 L (8.5 qt) <u>Change:</u> 5.5 – 7.0 L (5.8 – 7.4 qt) <u>Oil PN</u> G 052 516 A2*	Front F/Drive <u>New Fill:</u> 1.1 L (1.2qt) <u>Oil PN</u> G 055 190 A2*	10.0 L (10.5 qt)***	1.0 L (1.1qt) approximately <u>VW Brake Fluid</u> <u>Specification:</u> Use new fluid only.	Refrigerant Use only R134a 550g ± 15g (19.5 ± 0.5 oz.) Refrigerant Oil Use a PAG oil with R134a	4.5 L (4.8 qt) <u>Fluid PN</u> G 052 164*
<b>A4</b> quattro <u>Sedan-Manual</u> (8K25G9)	SAE 5W-30 or SAE 0W-40	6-Spd (0B2) 4.5 L (4.7 qt) <u>Oil PN</u> G 055 532 A2*	N/A	Rear F/Drive (0BC)   New Fill:   0.9 L (1.0qt)   Oil PN   G 052 145 S2*		FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	Oil Capacity & PN For Denso 150 cc +/- 10 cc G 052 300 A2*	
A4 quattro <u>Sedan-Auto</u> (8K252A) <u>allroad</u> (8KH52A)	2.0L TFSI 220 hp (CPMB) 4.5 L (4.8 qt) <u>Audi Oil Spec**</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	N/A	8-Spd Tiptronic (OBK) <u>New Fill:</u> 8.6 L (9.0qt) <u>Change</u> 3.6 - 4.0 L (3.8 - 4.2 qt) <u>Oil PN</u> G 060 162 A2	G New Fill:   1.0 L (1.1qt) Oil PN   G 052 145 S2*   Transfer Case 0.8 L (0.84 qt.)   Change: 0.8L (0.84 qt.)   Oil PN G 055 145 A2   Rear F/Drive (0BD)   New Fill: 1.0 L (1.1qt)   Oil PN G 052 145 S2*				

\*\*Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

44, S4, a	llroad 2	016 FLUID	<b>CAPACIT</b>	Y CHART	pdate 17 Nov 2015	Truth in Eng	ineering	<u>LLL</u>
Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headligh Fluid
<b>S4</b> quattro	3.0L V6 333 hp (CTUB)	6-Spd (0B4)	N/A	Rear F/Drive (0BD)	12.0 L (12.6qt)***	1.0 L (1.1qt) approximately	Refrigerant Use only R134a	4.5 L (4.8 q
(8K2549) Manual	6.8 L (7.2 qt)	3.8 L (4.0qt) <u>Oil PN</u>		<u>New Fill:</u> 1.0 L (1.1qt)		VW Brake Fluid	550g ± 15g (19.5 ± 0.5 oz.)	<u>Fluid PN</u> G 052 164
Manuai	Audi Oil Spec** VW 502 00**	G 052 911 A2*		Oil PN		Specification:	<u>Refrigerant Oil</u> Use a PAG oil	
	Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40			G 052 145 S2*		Use new fluid only.	with R134a	
S4		N/A	7-Spd DSG	Front F/Drive	-	FMVSS 116 DOT 4	Oil Capacity & PN	
quattro			(0B5)	New Fill:		or SAE J 1703	For Denso	
(8K254Y)			New Fill:	1.0 L (1.1 qt) <u>Oil PN</u>			150 cc +/- 10 cc	
(UK2041) Auto			7.0 - 7.5 L	G 052 145 A2*			G 052 300 A2*	
			(7.3 - 7.9qt)			Fluid PN		
				Transfer Case		B 000 750*		
			Change:	4.35 L (4.5 qt.)				
			6.7 L (7.0qt) approx.	<u>Oil PN</u> G 055 532 A2				
			<u>Oil PN</u>	Rear F/Drive				
			G 052 529 A2*	(0BC / 0BF)				
				<u>New Fill:</u> 0.9 L (1.0qt)				
				<u>Oil PN</u>				
				G 052 145 S2*				

Audi

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\* Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with distilled water.

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.