

A5, A5 Cabriolet S5,RS5 2015 FLUID CAPACITY CHART

Update 17 Nov 2015



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
A5 Coupe quattro (8T35G9) Manual	2.0L TFSI 220 hp (CAED) 4.6L (4.9 qt) Audi Oil Spec** VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd (0B2) 4.5L (4.7qt) Oil PN G 055 532 A2*	N/A	Rear F/Drive (0BC) New Fill: 0.9L (1.0 qt) Oil PN G 052 145 S2*	10.0 L (10.5 qt)***	1.0 L (1.1qt) (approximately) Audi Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750 *	Refrigerant Use only R134a 550 g ± 15 g (19.5 oz. ± 0.5 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity Denso 150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.) Fluid PN G 052 300 A2*	4.5L (4.8 qt) Fluid PN G 052 164*
A5 Cabriolet FWD (8F75GH) Auto			CVT (0AW) New Fill: 8.0 L (8.5 qt) Change: 5.5 – 6.0 L (5.8 – 6.3 qt) Oil PN G 052 516 A2*	Front F/Drive New Fill: 1.1L (1.2 qt) Oil PN G 055 190 A2*				
A5 quattro (8F752A) Cabrio			8-Spd Tiptronic (0BK/OBL) New Fill: 8.6 L (9.0 qt) Change: 3.6 - 4.0L (3.8 - 4.2 qt.) Oil PN G 060 162 A2	Front F/Drive New Fill: 1.0L (1.1 qt) Transfer Case New Fill: 1.1L (1.1qt) Change: 0.8L (0.84 qt.) Oil PN G 055 145 A2				
A5 Coupe quattro (8T352A)				Rear F/Drive (0BD) New Fill: 1.0L (1.1 qt) Oil PN G 052 145 S2*				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.

A5, A5 Cabriolet S5,RS5 2015 FLUID CAPACITY CHART Update 17 Nov 2015

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
S5 Coupe quattro (8T3549) Manual	3.0L V6 333 hp (CTUB) 6.8L (7.2 qt) <u>Audi Oil Spec**</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd (0B4) 3.8L (4.0 qt) <u>Oil PN</u> G 052 911 A2*	N/A	Front F/Drive New Fill: 1.0L (1.1 qt) <u>Oil PN</u> G 052 145 S2*	12.0 L (12.6 qt)***	1.0 L (1.1qt) approximately <u>Audi Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750 *	<u>Refrigerant</u> Use only R134a 550 g ± 15 g (19.5 oz. ± 0.5 oz.) <u>Refrigerant-RS5</u> Use only R134a 570 g ± 20 g (20.1 oz. ± 0.7 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a	4.5L (4.8 qt) <u>Fluid PN</u> G 052 164*
A5/S5 Coupe quattro (8T354Y) Cabriolet quattro (8F754Y)	(Same as above)	N/A	7-Spd DSG (0B5) New Fill: 7.0 - 7.5L (7.3 - 7.9 qt) Change: 6.7L (7.0 qt) approx. <u>Oil PN</u> G 052 529 A2*	Transfer Case New Fill: 4.35L (4.5 qt) <u>Oil PN</u> G 055 532 A2* Rear F/Drive (0BC / 0BF) New Fill: 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2*		15.0 L (15.8qt)***	(Same as above)	(Same as above)
RS5 Coupe quattro (8T35XY) RS5 Cabriolet quattro (8F75XY)	4.2L V8 450 hp (CFSA) 9.7L (10.2 qt) <u>Audi Oil Spec**</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	N/A	(Same as above)	(Same as above)	(Same as above)	(Same as above)	<u>Oil Capacity</u> Denso 150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.) <u>Fluid PN</u> G 052 300 A2*	(Same as above)

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.