



## 2013 – 2014 Jetta



Das Auto.

Engine	Part	Part Number	Quantity
<b>1.4L Hybrid: CNLA</b>	Oil Filter	04E115561H	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30	N/A	4.0L (4.2qt)
	<b>Drain Plug + Gasket</b>	<b>N 90288901 N 0138157</b>	1 1
	Air Filter	04E129620	1
	Fuel Filter (Every 20K miles)	1K0201051K	1

Engine	Part	Part Number	Quantity
<b>1.8L Turbo: CPKA, CPRA</b>	Oil Filter	06K115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30	N/A	5.5L (5.7qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	5C0129620	1

Engine	Part	Part Number	Quantity
<b>2.0L MPI: CBPA</b>	Oil Filter	06A115561B	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30	N/A	3.7L (3.9qt)
	Drain Plug + Gasket	N 91086801	1
	Air Filter	1F0129620	1

Engine	Part	Part Number	Quantity
<b>2.0L Turbo: CCTA, CBFA</b>	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30	N/A	4.6L (4.9qt)
	Drain Plug Gasket	See Tech Tip 17-12-02 Elsa Doc #2030603	1
	Air Filter	1K0129620D	1



## 2013 – 2014 Jetta



Das Auto.

Engine	Part	Part Number	Quantity
<b>2.0L Turbo Diesel: CJAA</b>	Oil Filter	071115562C	1
	VW 507 00 Use synthetic oil SAE 5W-30	N/A	4.3L (4.5qt)
	Drain Plug Gasket	N 90813202	1
	Air Filter	1K0129620E	1
	Fuel Filter (20K Only)	1K0127434B	1

Engine	Part	Part Number	Quantity
<b>2.0L CPLA, CPPA</b>	Oil Filter	06K115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30	N/A	5.5L (5.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	5C0129620	1

Engine	Part	Part Number	Quantity
<b>2.5L CBTA, CBUA</b>	Oil Filter	06D115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30	N/A	6.0L (6.3qt)
	Drain Plug + Gasket	N 90813202	1
	Air Filter	07K129620	1

Miscellaneous	Part	Part Number	Quantity
<b>Miscellaneous</b>	Pollen Filter (20K Only) PR-9AB	1K0819644B	1
	Pollen Filter (20K Only) PR-9AK	1K1819653B	1
	Driver's Wiper Blade (Left)	5C7955425B	1
	Passenger's Wiper Blade (Right)	5C7955426B	1
	Battery	000915105DEDSP	1
	Battery	000915105DGDSP	1
	Battery		1



2013 – 2014 Jetta



### 2013 Jetta Service Reminder Reset

#### Resetting the service reminder display

If the service was not performed by an authorized Volkswagen dealer or an authorized Volkswagen Service Facility, the service reminder can be reset as follows:

---

Switch off the ignition.

---

Push the **0.0 / SET** button in the instrument cluster and hold down.

---

Switch on the ignition.

---

Release the **0.0 / SET** button and push the **OK / RESET** button in the instrument cluster within about 20 seconds.

---

**i** Do **not** reset the service reminder between service intervals; otherwise, incorrect information will be displayed.

**i** The service reminder disappears after a few seconds when the engine is running or after the **OK/RESET** button on the windshield wiper lever has been pushed.

### 2013 Jetta GLI Service Reminder Reset

#### Resetting the service reminder display

If the service was not performed by an authorized Volkswagen dealer or an authorized Volkswagen Service Facility, the service reminder can be reset as follows:

---

Select the **Settings** menu.

---

In the **Service** submenu, select the **Reset** menu item.

---

Confirm request by pressing the **OK** button on the multi-function steering wheel.

---

**i** Do **not** reset the service reminder between service intervals; otherwise, incorrect information will be displayed.

**i** The service reminder disappears after a few seconds when the engine is running or after the **OK** button on the multi-function steering wheel has been pushed.



2013 – 2014 Jetta



## 2014 Jetta Service Reminder Reset

### Resetting the service reminder

If the service was not performed by an authorized Volkswagen dealer or an authorized Volkswagen Service Facility, the oil change service reminder can be reset as follows:

---

Switch off the ignition.


---

Press and hold the **0.0/SET** button in the instrument cluster.

---

Switch on the ignition.

---

Push the  button in the instrument cluster within about 20 seconds.

---

### OR:

---

Switch off the ignition.

---

Switch on the emergency flashers.


---

Press and hold the **0.0/SET** button in the instrument cluster.

---

Switch on the ignition.


---

Push the  button in the instrument cluster within about 20 seconds.

---

Switch off the emergency flashers.

---

 Do **not** reset the service reminder between service intervals; otherwise, incorrect information will be displayed.

 The service reminder disappears after a few seconds.



2013 – 2014 Jetta



## 2014 Jetta GLI and Jetta Hybrid Service Reminder Reset

### Resetting the oil change service reminder

If the service was not performed by an authorized Volkswagen dealer or an authorized Volkswagen Service Facility, the oil change service reminder can be reset as follows:

---

Switch off the ignition.

---

Press and hold the **O.O/SET** button in the instrument cluster.

---

Switch on the ignition.

---

Release the **O.O/SET** button.

---

A confirmation message appears in the display. Confirm request with the **OK** button on the multi-function steering wheel.

---



# Jetta (A6) - 2013 FLUID CAPACITY CHART 2 Nov 2012



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>Jetta</b> FWD-Manual  (1623S1) (1624S1) (1625S1) (1626S1)	<b>2.5L 170 hp (CBTA/CBUA)</b>  6.0 L (6.3 qt)  <b>VW Oil Spec:</b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>5-Spd (0A4)</b> 1.9 L (2.0 qt)  <b>Oil PN</b> G 052 512 A2*	N/A	N/A	<b>9.0 L (9.5 qt)**</b>	1.0L (1.1 qt.)  <b>Fluid P/N</b> G 002 000* Or G 004 000*	1.2 L (1.3qt) (approximately)  <b>VW Brake Fluid Specification:</b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <b>Fluid PN</b> B 000 750*	<b>Refrigerant</b> Use only R134a  <b>Refrig. Capacity</b> 525 ± 25 grams (18.5 ± 0.9 oz.)  <b>Refrigerant Oil</b> Use a PAG oil with R134a  <b>Oil PN &amp; Capacity</b> <b>Sanden Cmpr:</b>  G 052 200 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.)	3.0-4.0 L (3.1-4.2qt)  <b>Fluid PN</b> G 052 164*
<b>Jetta</b> FWD – Auto  (1623S3) (1624S3) (1625S3) (1626S3)		N/A	<b>6-Spd (09G)</b>  <b>Gen. 1</b> <b>New Fill:</b> 7.0 L (7.4 qt)  <b>Oil PN</b> G 055 025 A2*  <b>Gen. 2</b> <b>New Fill:</b> 6.1L (6.4 qt)  <b>Oil PN</b> G 055 540 A2*	Capacity included with transmission.					
<p><b>For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.</b></p> <p>* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.</p> <p>** Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.</p> <p>*** VW Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus (TL-VW 774 G) PN- G 012 A8G or G 12 plus (TL-VW 774 F) PN- G 012 A8F.</p>									

© 2012 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.



## Jetta (A6) - 2013 FLUID CAPACITY CHART 2 Nov 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>Jetta</b> FWD-Manual  (1621J1) (1622J1) (162SJ1)	<b>2.0L MPI 115 hp (CBPA)</b>  3.7 L (3.9 qt.)  <b>VW Oil Spec:</b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>5-Spd (0AF)</b>  2.0L (2.1 qt.)  <b>Oil PN</b> G 070 726 A2*	<b>N/A</b>	<b>N/A</b>	<b>5.0L (5.3 qt)***</b>	1.0L (1.1 qt.)  <b>Fluid P/N</b> G 002 000* Or G 004 000*	1.2 L (1.3qt) (approximately)  <b>VW Brake Fluid Specification:</b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <b>Fluid PN</b> B 000 750*	<b>Refrigerant</b> Use only R134a  <b>Refrig. Capacity</b> 525 ± 25 grams  <b>Refrigerant Oil</b> Use a PAG oil with R134a  <b>Oil PN &amp; Capacity</b> <b>Sanden Cmpr:</b>  G 052 200 A2* 110 cc ± 10 cc	3.0-4.0 L (3.1-4.2qt)  <b>Fluid PN</b> G 052 164*
<b>Jetta</b> FWD – Auto  (1621J3) (1622J3) (162SJ3)		<b>N/A</b>	<b>6-Spd (09G)</b>  <b>Gen. 1 New Fill:</b> 7.0L (7.4 qt)  <b>Oil PN</b> G 055 025 A2*  <b>Gen. 2 New Fill:</b> 6.1L (6.4 qt)  <b>Oil PN</b> G 055 540 A2*	Capacity included with transmission.					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\* Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.

\*\*\* VW Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus (TL-VW 774 G) PN- G 012 A8G or G 12 plus (TL-VW 774 F) PN- G 012 A8F.

© 2012 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.



# Jetta (A6) - 2013 FLUID CAPACITY CHART 2 Nov 2012



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>Jetta TDI</b>  (16259L) (16269L) (16279L)	<b>2.0T 140 hp Diesel (CJAA)</b>  4.3L (4.5 qt)  <b>VW Oil Spec:</b> VW 507 00** Use synthetic oil SAE 5W-30	<b>6-Spd (02Q)</b>  2.3L (2.4 qt)  <b>Oil PN</b> G 052 171 A2*	N/A	N/A	8.0L (8.5 qt)***	Electro-Mechanical	1.2 L (1.3qt) (approximately)  <b>VW Brake Fluid Specification:</b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <b>Fluid PN</b> B 000 750*	<b>Refrigerant</b> Use only R134a  <b>Refrig. Capacity</b> 600 ± 25 grams (19.2 ± 0.8 oz.)  <b>Oil PN &amp; Capacity</b> <b>Sanden Cmpr:</b>  G 052 200 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.)	3.0-4.0 L (3.1-4.2qt)  <b>Fluid PN</b> G 052 164*
<b>Jetta TDI</b>  (16269L) (16269M) (16279M)		N/A	<b>6-Spd DSG (02E)</b>  <u>New Fill:</u> 7.2L (7.6 qt)  <u>Change:</u> 5.2L (5.5 qt)	Capacity included with transmission.  <b>Oil PN</b> G 052 182 A2*					
<p>For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.</p> <p>* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.</p> <p>** Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.</p> <p>*** VW Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus (TL-VW 774 G) PN- G 012 A8G or G 12 plus (TL-VW 774 F) PN- G 012 A8F.</p>									

© 2012 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.





# Jetta (A6) GLI - 2013 FLUID CAPACITY CHART 2 Nov 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>GLI</b> FWD - Manual (1629W2) (162AW2) (162NW2)  <b>PZEV</b> (1629Y2) (162AY2) (162NY2)	<b>2.0 T 200 hp (CCTA/CBFA)</b>  4.6L (4.9 qt)  <b>VW Oil Spec:</b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>6-Spd (02Q)</b>  2.3 L (2.4 qt)  <b>Oil PN</b> G 052 171 A2*	<b>N/A</b>	<b>N/A</b>	8.0L (8.5 qt)***	1.0L (1.1 qt.)  <b>Fluid P/N</b> G002 000* or G004 000*	1.2 L (1.3qt) (approximately)  <b>VW Brake Fluid Specification:</b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <b>Fluid PN</b> B 000 750 *	<b>Refrigerant</b> Use only R134a  <b>Refrig. Capacity</b> 525 ± 25 grams (18.5 ± 0.9 oz.)  <b>Refrigerant Oil</b> Use a PAG oil with R134a  <b>Oil PN &amp; Capacity</b> For Sanden use:  G 052 200 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.)	3.0-4.0L (3.1-4.2 qt)  <b>Fluid PN</b> G 052 164*
<b>GLI</b> FWD - Auto (1629W3) (162AW3) (162NW3)  <b>PZEV</b> (1629Y3) (162AY3) (162NY3)	(Same as above)	<b>N/A</b>	<b>6-Spd DSG (02E)</b>  <b>New Fill:</b> 6.9 - 7.2 L (7.3 - 7.6 qt)  <b>Change:</b> 5.2L (5.5 qt)  <b>Oil PN</b> G 052 182 A2*	Capacity included with transmission.	(Same as above)	(Same as above)	(Same as above)	(Same as above)	(Same as above)

**For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.**

**\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.**

**\*\*Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.**

**\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J)**



# Jetta (A6) GLI - 2013 FLUID CAPACITY CHART Update 31 May 2013

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>GLI</b> FWD - Manual (1629N2) (162AN2) (162NN2)  <b>PZEV</b> (1629M2) (162AM2) (162NM2)	<b>2.0 T 210 hp</b> <b>(CPLA/CPPA)</b>  5.5L (5.8 qt)  <b>VW Oil Spec:</b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>6-Spd</b> <b>(02Q)</b>  2.3 L (2.4 qt)  <b>Oil PN</b> G 052 171 A2*	<b>N/A</b>	<b>N/A</b>	8.0L (8.5 qt)***	1.0L (1.1 qt.)  <b>Fluid P/N</b> G002 000* or G004 000*	1.2 L (1.3qt) (approximately)  <b>VW Brake Fluid</b> <b>Specification:</b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <b>Fluid PN</b> B 000 750 *	<b>Refrigerant</b> Use only R134a  <b>Refrig. Capacity</b> 525 ± 25 grams (18.5 ± 0.9 oz.)  <b>Refrigerant Oil</b> Use a PAG oil with R134a  <b>Oil PN &amp; Capacity</b> For Sanden use:  G 052 200 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.)	3.0-4.0L (3.1-4.2 qt)  <b>Fluid PN</b> G 052 164*
<b>GLI</b> FWD - Auto (1629N3) (162AN3) (162NN3)  <b>PZEV</b> (1629M3) (162AM3) (162NM3)	(Same as above)	<b>N/A</b>	<b>6-Spd DSG</b> <b>(02E)</b>  <b>New Fill:</b> 6.9 - 7.2 L (7.3 - 7.6 qt)  <b>Change:</b> 5.2L (5.5 qt)  <b>Oil PN</b> G 052 182 A2*	Capacity included with transmission.	(Same as above)	(Same as above)	(Same as above)	(Same as above)	(Same as above)

**For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.**

**\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.**

**\*\*Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.**

**\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J) G 013A8J**



# Jetta Hybrid - 2013 FLUID CAPACITY CHART update 12Jun2014

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>Jetta Hybrid</b> FWD – Auto  (1620H5) (1621H5) (1622H5) (1623H5)	<b>1.4 L 150 HP (CNLA)</b>  4.0L (4.2 qt)  <u><b>VW Oil Spec:</b></u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>N/A</b>	<b>7-Spd DSG (0CG)</b>  <u><b>New Fill:</b></u> 1.7 L (1.8 qt)  <u><b>Hydraulic for mechatronic J743</b></u> 1.0 L (1.0 qt)  <u><b>Oil PN</b></u> <span style="color: red;">G 052 512 A2*</span>	<u><b>Bevel Box</b></u>  <u><b>New Fill:</b></u> 0.9L (1.0 qt.)  <u><b>Oil PN</b></u> G 052 145 S2	8.0 L (8.5 qt)***	Electro- Mechanical	1.2 L (1.3qt) (approximately)  <u><b>VW Brake Fluid Specification:</b></u>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <u><b>Fluid PN</b></u> B 000 750 *	<u><b>Refrigerant</b></u> Use only R134a  <u><b>Refrig. Capacity</b></u> 525 ± 25 grams (18.5 ± 0.9 oz.)  <u><b>Refrigerant Oil</b></u> Use a PAG oil with R134a  <u><b>Oil PN &amp; Capacity</b></u> For Delphi use:  G 052 300 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.) from 10.2008	3.0 L - 4.0 L (3.1 - 4.2 qt)  <u><b>Fluid PN</b></u> G 052 164*

**For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.**

**\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.**

**\*\*Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.**

**\*\*\* VW Coolant Additive Specification and Part Number:** (color is purple) G 12 plus-plus (TL-VW 774 G) PN- G 012 A8G.



## Jetta (A6) - 2014 FLUID CAPACITY CHART Update 4/4/14

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>Jetta</b> FWD-Manual	<b>1.8L 170 hp (CPKA/CPRA)</b>  <b>5.5 L (5.7 qt.)</b>  <b><u>VW Oil Spec:</u></b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>5-Spd (0A4)</b> 1.9 L (2.0 qt.)  <b><u>Oil PN</u></b> G 052 512 A2*	<b>N/A</b>	<b>N/A</b>	<b>8.0L (8.5 qt)***</b>	<b>1.0L (1.1 qt.)</b>  <b><u>Fluid P/N</u></b> G 002 000* Or G 004 000*	<b>1.2 L (1.3qt)</b> (approximately)  <b><u>VW Brake Fluid</u></b> <b><u>Specification:</u></b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <b><u>Fluid PN</u></b> B 000 750*	<b><u>Refrigerant</u></b> Use only R134a  <b><u>Refrig. Capacity</u></b> 525 ± 25 grams (18.5 ± 0.9 oz.)  <b><u>Refrigerant Oil</u></b> Use a PAG oil with R134a  <b><u>Oil PN &amp; Capacity</u></b> <u>Sanden Cmpr:</u>  G 052 200 A2* 110 cc ± 10 cc	3.0-4.0 L (3.1-4.2qt)  <b><u>Fluid PN</u></b> G 052 164*
<b>Jetta</b> FWD – Auto		<b>N/A</b>	<b>6-Spd (09G)</b>  <b>Gen. 1</b> <b><u>New Fill:</u></b> 7.0 L (7.4 qt) <b><u>Change:</u></b> 3.0L (3.1 qt.)  <b><u>Oil PN</u></b> G 055 025 A2*  <b>Gen. 2</b> <b><u>New Fill:</u></b> 6.1L (6.4 qt)  <b><u>Oil PN</u></b> G 055 540 A2*	Capacity included with transmission.					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.

\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) **G 13** (TL-VW 774 J) G 013A8J. **Dilute with Distilled Water.**

© 2014 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.



# Jetta (A6) - 2014 FLUID CAPACITY CHART

Update 4/4/14

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>Jetta</b> FWD-Manual	<b>2.0L MPI 115 hp (CBPA)</b>  3.7 L (3.9 qt.)  <b>VW Oil Spec:</b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>5-Spd (0AF)</b>  2.0L (2.1 qt.)  <b>Oil PN</b> G 070 726 A2*	<b>N/A</b>	<b>N/A</b>	<b>5.0L (5.3 qt)***</b>	1.0L (1.1 qt.)  <b>Fluid P/N</b> G 002 000* Or G 004 000*	1.2 L (1.3qt) (approximately)  <b>VW Brake Fluid Specification:</b>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <b>Fluid PN</b> B 000 750*	<b>Refrigerant</b> Use only R134a  <b>Refrig. Capacity</b> 525 ± 25 grams (18.5 ± 0.9 oz.)  <b>Refrigerant Oil</b> Use a PAG oil with R134a  <b>Oil PN &amp; Capacity</b> Sanden Cmpr:  G 052 200 A2* 110 cc ± 10 cc	3.0-4.0 L (3.1-4.2qt)  <b>Fluid PN</b> G 052 164*
<b>Jetta</b> FWD – Auto		<b>N/A</b>	<b>6-Spd (09G)</b>  <b>Gen. 1</b> <b>New Fill:</b> 7.0L (7.4 qt)  <b>Change:</b> 3.0L (3.1 qt.)  <b>Oil PN</b> G 055 025 A2*  <b>Gen. 2</b> <b>New Fill:</b> 6.1L (6.4 qt)  <b>Oil PN</b> G 055 540 A2*	Capacity included with transmission.					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.

\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) **G 13** (TL-VW 774 J) G 013A8J. **Dilute with Distilled Water.**



## Jetta (A6) - 2014 FLUID CAPACITY CHART Update 4/4/14

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>Jetta TDI</b>	<b>2.0T 140 hp Diesel (CJAA)</b>  4.3L (4.5 qt)  <u><b>VW Oil Spec:</b></u> VW 507 00** Use synthetic oil SAE 5W-30	<b>6-Spd (02Q)</b>  2.3L (2.4 qt.)  <u><b>Oil PN</b></u> G 052 171 A2*	<b>N/A</b>	<b>N/A</b>	<b>8.0L (8.5 qt)**</b>	<b>Electro- Mechanical</b>	1.2 L (1.3qt) (approximately)  <u><b>VW Brake Fluid Specification:</b></u>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <u><b>Fluid PN</b></u> B 000 750*	<u><b>Refrigerant</b></u> Use only R134a  <u><b>Refrig. Capacity</b></u> 600 ± 25 grams (19.2 ± 0.9 oz.)  <u><b>Oil PN &amp; Capacity Sanden Cmpr:</b></u>  G 052 200 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.)	3.0-4.0 L (3.1-4.2qt)  <u><b>Fluid PN</b></u> G 052 164*
<b>Jetta TDI</b>		<b>N/A</b>	<b>6-Spd DSG (02E)</b>  <u>New Fill:</u> 7.2L (7.6 qt)  <u>Change:</u> 5.2L (5.5 qt)  <u>Mechatronic Only</u> 3-4L (3.1-4.2 qt.)	Capacity included with transmission.  <u><b>Oil PN</b></u> G 052 182 A2*					

**For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.**

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\* Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.

\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J) G 013A8J. **Dilute with Distilled Water.**



# Jetta (A6) GLI - 2014 FLUID CAPACITY CHART 01 Aug 2013

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>GLI</b> FWD - Manual (162DN2) (162EN2) (162FN2)  <b>PZEV</b> (162DM2) (162EM2) (162FM2)	<b>2.0 T 210 hp (CPLA/CPPA)</b>  5.5L (5.8 qt)  <u>VW Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>6-Spd (02Q)</b>  2.3 L (2.4 qt)  <u>Oil PN</u> G 052 171 A2*	<b>N/A</b>	<b>N/A</b>	8.0L (8.5 qt)***	1.0L (1.1 qt.)  <u>Fluid P/N</u> G002 000* or G004 000*	1.2 L (1.3qt) (approximately)  <u>VW Brake Fluid Specification:</u>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <u>Fluid PN</u> B 000 750 *	<u>Refrigerant</u> Use only R134a  <u>Refrig. Capacity</u> 525 ± 25 grams (18.5 ± 0.9 oz.)  <u>Refrigerant Oil</u> Use a PAG oil with R134a  <u>Oil PN &amp; Capacity</u> For Sanden use:  G 052 200 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.)	3.0-4.0L (3.1-4.2 qt)  <u>Fluid PN</u> G 052 164*
<b>GLI</b> FWD - Auto (162DN3) (162EN3) (162FN3)  <b>PZEV</b> (162DM3) (162EM3) (162FM3)	(Same as above)	<b>N/A</b>	<b>6-Spd DSG (02E)</b>  <u>New Fill:</u> 6.9 - 7.2 L (7.3 – 7.6 qt)  <u>Change:</u> 5.2L (5.5 qt)  <u>Oil PN</u> G 052 182 A2*	Capacity included with transmission.	(Same as above)	(Same as above)	(Same as above)	(Same as above)	(Same as above)

**For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.**

**\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.**

**\*\*Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.**

**\*\*\* VW Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J) G 013A8J. Dilute with Distilled Water.**



# Jetta Hybrid - 2014 FLUID CAPACITY CHART update12Jun2014

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>Jetta Hybrid</b> FWD – Auto  (1624H5) (1625H5) (1626H5) (1627H5)	<b>1.4 L 150 HP (CNLA)</b>  4.0L (4.2 qt)  <u><b>VW Oil Spec:</b></u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>N/A</b>	<b>7-Spd DSG (0CG)</b>  <u><b>New Fill:</b></u> 2.1 L (2.2 qt)  <u><b>Hydraulic for mechatronic J743</b></u> 1.0 L (1.0 qt)  <u><b>Oil PN</b></u> <span style="color: red;">G 052 512 A2*</span>	<u><b>Bevel Box</b></u>  <u><b>New Fill:</b></u> 0.9L (1.0 qt.)  <u><b>Oil PN</b></u> G 052 145 S2	8.0 L (8.5 qt)***	Electro- Mechanical	1.2 L (1.3qt) (approximately)  <u><b>VW Brake Fluid Specification:</b></u>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <u><b>Fluid PN</b></u> B 000 750 *	<u><b>Refrigerant</b></u> Use only R134a  <u><b>Refrig. Capacity</b></u> 525 ± 25 grams (18.5 ± 0.9 oz.)  <u><b>Refrigerant Oil</b></u> Use a PAG oil with R134a  <u><b>Oil PN &amp; Capacity</b></u> For Delphi use:  G 052 300 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.) from 10.2008	3.0 L - 4.0 L (3.1 - 4.2 qt)  <u><b>Fluid PN</b></u> G 052 164*

**For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.**

**\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.**

**\*\*Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.**

**\*\*\* VW Coolant Additive Specification and Part Number:** (color is purple) G 12 plus-plus (TL-VW 774 G) PN- G 012 A8G.



# Tech Tips

TT 17-12-02

Date: July 27, 2012

2012-2014 Beetle, CC, Eos, GTI, Jetta GLI, and Tiguan  
Equipped with CCTA or CBFA Engines – Oil Leak From Oil  
Drain Plug Area After Oil Change and/or Drain Plug  
Replacement

**July 26, 2013: Update to Information.**

An oil leak from around the oil drain plug noted after oil change, and/or drain plug replacement, may be caused by installation of incorrect drain plug. Correct part number drain plug is based on the oil pan design as shown below. Original drain plug is 18mm hex for both style oil pans.



If the oil pan has a boss use part number:  
**N 908 132 02 Drain plug w/seal**



If the oil pan is flat, use drain plug and washer:  
**N 911 679 01 Plug**  
**N 013 81 57 Seal**

