



Das Auto.

2016 Beetle Perfect Delivery Inspection (PDI) - Technician and Detailer Inspections

Stock No.: _____ Dealer Number: _____ R.O. No.: _____
VIN: _____

Technician Inspection

Initial Inspection (A workshop maintainer/charger must be used):

- ☐ Check hood latch and safety catch
- ☐ Ensure proper installation of permanent wiper blades (WINDSHIELD MUST BE CLEAN BEFORE INSTALLING)
- ☐ Test and auto charge battery with INC-940 using the "48 Hour Check" test or the VAS5903.
Record and document test code
- ☐ Install front license plate bracket if required
- ☐ Check engine coolant level (engine off/cold). Do not exceed max fill line
- ☐ Check brake and power steering fluid levels. Do not exceed max fill line
- ☐ Top-off windshield washer solvent
- ☐ Check engine oil level
- ☐ Adjust tire pressure to specification on vehicle sticker at "B" Pillar. (Do not set until day before delivery)
- ☐ Torque wheels to specification. (Refer to Elsa)
- ☐ Retrieve radio code from Elsa and check for any open Campaigns and Updates. Perform if applicable

Make sure hands and clothing are clean before entering the vehicle

- ☐ Disable vehicle transport mode.
- ☐ Check all instrument cluster warning lights by cycling the ignition from off to on
- ☐ Check that all keys and remotes lock, unlock, and start vehicle
- ☐ Check operation of all exterior lights and AFS using a mirror or another technician
- ☐ Check front windshield wiper/washer functions
- ☐ Check function of tilt and telescopic features of steering wheel
- ☐ Set clock, date, and year (if applicable)
- ☐ Reset inspection/oil service interval
- ☐ Verify language and units of measurement (F°) in multi-function display and Navigation system (if applicable)
- ☐ Verify HD Radio is turned "off" in Radio/Settings Menu (Premium 8)
- ☐ Verify radio operates in AM, FM, CD, MP3 and Satellite Radio modes using applicable radio buttons and steering wheel controls
- ☐ Set memory preset stations to AM and FM stations with good reception quality by using the scan feature
- ☐ Check function of all power windows (including sunroof if equipped), program One-Touch feature, and check function of pinch protection feature
- ☐ Check convertible top operation (if applicable)
- ☐ Check seat belts, seat adjusters, heated seats (if applicable)

- ☐ Check function of Rear Seat Easy Entry System
- ☐ Install Warranty and Maintenance Booklet
- ☐ Install California Emissions Warranty Booklet
- ☐ Install Applicable Tire Warranty Brochure
- ☐ Check proper fuel door operation
- ☐ Check proper hatch operation using the remote and the exterior button
- ☐ Place tow hook and wheel lock adapter in tool kit. Discard 2nd tow hook (if applicable)
- ☐ Install rear tow hook cover (if applicable)
- ☐ Raise vehicle and perform a visual inspection for leaks and/or under body damage
- ☐ Remove suspension blocks located in the suspensions coil springs (If applicable)

Road Test:

- ☐ Odometer reading before road test: _____ after: _____
- ☐ Check engine performance and acceleration
- ☐ Store current tire pressure values for TPMS by pressing the SET button in the glove box for a minimum of 2 seconds or setting in MFI if applicable
- ☐ Check automatic transmission operation, including automatic shift lock and Tiptronic®
- ☐ Check brake system function (including ABS)/Parking brake operation – engage and disengage
- ☐ Check steering for pulling, vibration and steering wheel alignment
- ☐ Check climate control for mode functions (Defrost/Vent/Floor), air conditioning operation and heater operation
- ☐ Car-Net (if equipped): Vehicle must be in coverage area, have clear sight to the sky for 5 minutes, and have 5 miles registered on the odometer. Then, verify light in 3 button switch assembly located in overhead console is illuminated green. This confirms over the air vehicle registration has taken place.

After Road Test:

- ☐ Verify no warning lights are illuminated
- ☐ Retrieve fault memory, correct any DTC's, set readiness code (if necessary). Save and attach printout to Repair Order

I certify that all operations have been completed and that this vehicle has been prepared in accordance with Volkswagen procedures and quality standards.

☐ All product updates have been checked ☐ Dealer 30-day maintenance process has been initiated

Dealership Authorized Signature: _____ Date: _____

Detailer Process

Exterior:

- ☐ Remove RAPGARD protective covering (best removed 60°-80F°)
- ☐ Wash/dry vehicle exterior (convertibles: do not use high pressure washer above door sills or above rear window seals)
- ☐ Check for water leaks
- ☐ Clean alloy wheels/tires, remove any adhesive on wheels
- ☐ Inspect paint surfaces, moldings and glass. Remove any adhesive, tar, or residue. If any defects (scratches/dings/dents/body damage) are found, contact Service Manager to schedule immediate repair.
- ☐ Wax vehicle using 3M Perfect-It™ Paste Wax or equivalent
- ☐ Clean all glass and mirrors using 3M Gloss enhancer, cleaner clay or equivalent
- ☐ Wipe door jambs

Under Hood:

- ☐ Wipe down engine compartment (no high pressure wash).

Interior:

- ☐ Clean all glass, mirrors, and sunroof (if applicable)
- ☐ Remove all trim protection, coverings, stickers, and decals - Do not remove airbag warning triangle/warning labels
- ☐ Check upholstery and clean as required
- ☐ Check for excessive grease on seat tracks and clean as required
- ☐ Check all interior surfaces and compartments (including sun visors and headliner) and clean as required
- ☐ Vacuum carpet
- ☐ Check luggage compartment and vacuum
- ☐ Install front/rear floor mats (including locking clip / tabs), check color match. If monster mats are installed, please put factory mats in trunk.

I certify that all operations have been completed and that this vehicle has been prepared in accordance with Volkswagen procedures and quality standards.

☐ All product updates have been checked

☐ Dealer 30-day maintenance process has been initiated

Dealership Authorized Signature: _____

Date: _____

Original – Retain with Repair Order in Service File

VW.BEETLE.PDITECHCHECK.06.08.2015