TT-TTS - 2016 FLUID CAPACITY CHART July 30, 2015



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
TT - quattro	2.0L TFSI 220 hp	N/A	6-Spd DSG (02E)	Rear F/Drive	10.0 L (10.5 qt)***	1.0 L (1.1 qt)	Refrigerant	4.1L (4.3 qt)
	(CNTC)			(0BR)		(approximately)	Use only R134a	
(FV355L)	5.7L (6.0 qt)		New Fill:	0.95 L (1.0 qt)			500 ± 15 g	Fluid PN
Coupe			6.9 L (7.3 qt)			VW Brake Fluid	(17.5 ± 0.5 oz.)	G 052 164*
				Oil PN		Specification:		
(FV955L)	Audi Oil Spec: VW 502 00**		Change:	G 052 145 S2*			Refrigerant Oil	
Roadster	Use synthetic oil		5.5 L (5.8 qt)	Halden Obstali		Use new fluid only.	Use a PAG oil	
	SAE 5W-40,		approx.	Haldex Clutch		ENN/00 440 DOT 4	with R134a	
	SAE 5W-30 or		Oil PN	(4)		FMVSS 116 DOT 4 or SAE J 1703	Danca Camprassar	
	SAE 0W-40		G 052 182 A2*	<u>New Fill:</u> 0.85 L (0.9 qt)		01 SAE J 1703	Denso Compressor	
			G 052 162 AZ	0.65 L (0.9 qt)		Fluid PN	110 cc ± 10 cc	
TTS - quattro	2.0L TFSI 292 hp		Bevel Box	Replacement:		B 000 750*	(3.7 oz. ± 0.3 oz.)	
(-) ((1)	(CYFB)		New Fill:	0.7 L (0.8 qt)		B 000 700	(0.7 02. ± 0.0 02.)	
(FV351L)	5.7L (6.0 qt)		0.9 L (1.0 qt)	0.1 L (0.0 qt)			Part Number	
Coupe	VIM Oil Speed		0.0 = (4.)	Oil PN			G 052 154 A2*	
	<u>VW Oil Spec:</u> VW 502 00**		Oil PN	G 055 175 A2*				
	Use synthetic oil		G 052 145 S2*					
	SAE 5W-40,			(0AV)				
	SAE 5W-30 or			0.95 L (1.0 qt)				
	SAE 0W-40							
				Haldex Clutch				
				(2)				
				New Fill:				
				0.85 L (0.9 qt)				
				Replacement: 0.65 L (0.68 qt)				
				<u>Oil PN</u> G 055 175 A2*				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{**}Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.