



NUMBER: 08-049-15

GROUP: Electrical

DATE: May 05, 2015

This bulletin is supplied as technical information only and is not an authorization for repair. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without written permission of FCA US LLC.

THE wiTECH SOFTWARE LEVEL MUST BE AT 15.04 OR HIGHER TO PERFORM THIS PROCEDURE.

SUBJECT:

Inoperative Blue And Me Steering Wheel Button

OVERVIEW:

This bulletin involves performing a BCM Proxi Configuration.

MODELS:

2015 (FF) Fiat 500

NOTE: This bulletin applies to vehicles built on or before April 22, 2015 (MDH 0422XX) equipped with Instrument Cluster (Sales Codes JAV).

SYMPTOM/CONDITION:

The customer may notice that the buttons on the steering wheel for Blue and Me may stop working. Also for customers in Canada and Mexico, they may notice that the Tire Pressure Monitor System (TPMS) "Winter Mode" feature is missing.

DIAGNOSIS:

Using a Scan Tool (wiTECH) with the appropriate Diagnostic Procedures available in TechCONNECT, verify if Diagnostic Trouble Codes (DTCs) are set. If DTCs are present, record them on the repair order and repair as necessary before proceeding further with this bulletin.

If the customer describes the symptom/condition listed above, perform the Repair Procedure.

REPAIR PROCEDURE:

1. Using wiTECH, perform a Restore BCM Proxi Configuration. This routine is available under the 'Vehicle Preparations' tab found on the home page of wiTECH.
2. Clear any DTCs which may have been set during the reconfiguration.

POLICY:

Reimbursable within the provisions of the warranty.

TIME ALLOWANCE:

Labor Operation No:	Description	Skill Category	Amount
18-19-02-AL	Module, Body Control, Proxi Procedure (0 - Introduction)	6 - Electrical and Body Systems	0.2 Hrs.

FAILURE CODE:

The dealer must choose which failure code to use. If the customer came in with an issue and the dealer found updated software to correct that issue, use failure code CC, for all other use failure code RF.

- If the customer's concern matches the SYMPTOM/CONDITION identified in the Service Bulletin, than failure code CC is to be used.
- If an available flash is completed while addressing a different customer concern, failure code RF is to be used.

CC	Customer Concern
RF	Routine Flash