



# SERVICE BULLETIN

Classification: HA15-002a	Reference: NTB15-042a	Date: October 12, 2015
------------------------------	--------------------------	---------------------------

## 2014-2015 TAXI; A/C COMPRESSOR SERVICE INFORMATION

This bulletin has been amended. The Title, Applied Vehicles, and Service Information section have been revised. Please discard previous versions of this bulletin.

**APPLIED VEHICLES:** 2014-2015 Taxi

### SERVICE INFORMATION

If the A/C compressor on an Applied Vehicle is being replaced for any reason, perform the following:

1. Evacuate the system's refrigerant.
2. Record the amount evacuated (this will determine if step 4 applies).  
**NOTE:** Make sure your Robinair/Tech-Mate Air-Conditioning Machine # 48710 is calibrated.
3. Replace the compressor with the one listed in FAST or your electronic parts catalog.
  - Refer to the applicable Electronic Service Manual (ESM), section **HAC-Heater & Air Conditioning System**, for compressor removal and installation procedure.
4. If the amount initially evacuated was less than 600 grams (1.32 pounds), check for leaks and repair as needed.
5. Evacuate and charge the A/C system.
  - Ideal refrigerant charge amount: 700 grams (1.54 pounds)
  - Acceptable charge amount: 700 grams +/- 50 grams (1.54 pounds +/- 0.11 pounds)

**NOTE:** Do not use the charge capacity value listed in NV200 Taxi ESMs.

Nissan Bulletins are intended for use by qualified technicians, not 'do-it-yourselfers'. Qualified technicians are properly trained individuals who have the equipment, tools, safety instruction, and know-how to do a job properly and safely. **NOTE:** If you believe that a described condition may apply to a particular vehicle, DO NOT assume that it does. See your Nissan dealer to determine if this applies to your vehicle.