

# Tire Positioning before New Vehicle Delivery

Service  
Category General

Section Pre-Delivery Service

Market USA

Lexus Supports  
ASE Certification 

## Applicability

| YEAR(S) | MODEL(S)  | ADDITIONAL INFORMATION |
|---------|---|------------------------|
| 2016    | CT200H, ES300H, ES350,<br>GS F, GS200T, GS350,<br>GS450H, GX460, IS200T,<br>IS300, IS350, LS460,<br>LS600H, LX570, NX200T,<br>NX300H, RC F, RC200T,<br>RC300, RC350, RX350,<br>RX450H |                        |

### REVISION NOTICE

February 23, 2016 Rev1:

- Applicability has been updated to include 2016 model year GS F, GS 200t, GX 460, IS 300/200t, and RC 200t/300 vehicles.

Any previous printed versions of this bulletin should be discarded.

## Introduction

During the manufacturing process, tires are mounted on the vehicle as matched sets to help reduce conditions such as pulling or drifting. If the wheels are replaced or refinished before vehicle delivery, it is important that the tires remain on the vehicle in the same location and in the same direction of rotation.

Please refer to the following procedure to ensure that the original tires stay in the same location on the vehicle.

## Warranty Information

| OP CODE | DESCRIPTION                | TIME | OFP | T1 | T2 |
|---------|----------------------------|------|-----|----|----|
| N/A     | Not Applicable to Warranty | –    | –   | –  | –  |

## Tire Positioning before New Vehicle Delivery

---

### Installation Procedure

1. Mark the tire installation position on the inward facing tire sidewall.  
Example: Front Right = FR, Front Left = FL, Rear Right = RR, Rear Left = RL
2. Install the original tires on the new or refinished wheels with the marked side facing inwards.
3. Balance tire/wheel assemblies on the vehicle in the marked positions.
4. Place the tire/wheel assemblies on the vehicle in the marked positions.

**NOTE**

**Torque the wheel nuts to the proper torque value in sequence.**