SB-10058888-5704

PORSCHE'

Technical Information

86/15 ENU WF57

Service

-₅₇ 2

WF57 - Replacing Tailpipe on Exhaust System (Workshop Campaign)

Vehicle Type:	Cayman GT4 (981)
Model Year:	2016
Concerns:	Tailpipe on exhaust system
Information:	This is to inform you of a voluntary Workshop Campaign on the above-mentioned vehicles. Tailpipe covers, whose durability cannot be guaranteed over the service life of the vehicle, were installed on the affected vehicles.
	The tailpipe covers can crack on vehicles with high mileage due to vibrations in the engine, particularly at high engine speeds. This can cause noises.
Action Required:	Replace tailpipe on exhaust system.
Affected Vehicles:	The VIN(s) can be checked by using PIWIS Vehicle Information link to verify if the campaign affects the vehicle. This campaign is scope specific to the VIN! Failure to verify in PIWIS may result in an improper repair. This campaign affects 23 vehicles in North America.

Parts Info: NOTE: PARTS WILL NOT BE AUTOMATICALLY ALLOCATED TO YOUR DEALERSHIP. ALL PARTS MUST BE ORDERED VIA A PTEC/PAV.

Part No.	Designation – Use	Qty.
000.043.210.29	\Rightarrow Tailpipe	1 ea.
981.111.113.00	\Rightarrow Seal – Rear silencer to catalytic converter	1 ea.
900.910.003.03	\Rightarrow Hexagon nut, M8 – Rear silencer to catalytic converter	2 ea.
981.111.281.02	\Rightarrow Clamp – Rear silencer connection, left/right	1 ea.
999.512.707.00	\Rightarrow Hose clamp, 9.6 – 11.3 mm – Vacuum line to control box	1 ea.

Materials: **Required materials** (usually already available in the Porsche dealership):

2015[©] Porsche Cars North America, Inc.

AfterSales

	Part No. 000.043.207.07		Designation – Use	Oty. 75g tube (approx. 10 grams required per vehicle)				
			Optimol MF grease – Tailpipe to rear muffler					
Tools:	•	Torque wrench, 6 – 50 Nm (4.5 – 37 ftlb.), e.g. V.A.G 1331 - Torque wrench, 6-50 Nm (4.5-37 ftlb.) ftlb.) Torque wrench, 20 – 100 Nm (15 – 74 ftlb.), e.g. VAS 5820 - Torque wrench, 20-100 Nm (15-74 ftlb.)						
Claim Submission:	See	See Attachment "A".						
Replacing tai	lpip	e on exhaust system						
Work Procedure	: 1	1 Raise the vehicle on a lifting platform \Rightarrow Workshop Manual '4X00IN Lifting the vehicle'.						
	2	Remove rear left wheel	\Rightarrow Workshop Manual '440519 Removing and installing wheel'.					
	3	Remove rear muffler for cylinder bank 4–6 \Rightarrow Workshop Manual '263319 Removing and installing rear silencer'.						
	4	Remove tailpipe on exha	iust system \Rightarrow Workshop Manual '263519 Removing and installing tailpipe					
	5	Push new, stronger tailpipe onto the rear muffler for cylinder bank $1-3$, but do not tighten it initially.						
	6	Install rear muffler for cylinder bank 4–6 \Rightarrow Workshop Manual '263319 Removing and installing rear silencer'.						
	7	Adjust and secure tailpipe on exhaust system \Rightarrow Workshop Manual '263519 Removing and installing tailpipe cover'. To do this, set the gap between the tailpipe and rear apron to the same values as for the Cayman S (981).						
	8	Install rear left wheel \Rightarrow Workshop Manual '440519 Removing and installing wheel'.						
	9	Lower the vehicle and remove it from the lifting platform.						
	10	Enter the workshop can	npaign in the Warranty and Maintenance booklet.					
Attachment "A":	: Claim Submission - Workshop Campaign WF57 Warranty claims should be submitted via WWS/PQIS.							

Technical Information	Service	\mathbf{O}
	86/15 ENU WF57	2

Open campaigns may be checked by using either the PIWIS Vehicle Information system or through PQIS Job Creation.

Labor, parts, and sublet will be automatically inserted when Technician is selected in WWS/PQIS. If necessary, the required part numbers will need to be manually entered into warranty system by the dealer administrator.

i Information

The working time specified below was determined specifically for carrying out this campaign and may differ from the working times published in the Labor Operation List in PIWIS.

Working time:								
Replacing tailpipe on exhaust system Labor time: 69 1 Includes: Raising and lowering the vehicle Removing and installing rear left wheel Removing and installing rear muffler for cylinder bank 4-6 Adjusting tailpipe Adjusting tailpipe								
Parts requi	red:							
000.043.21	0.29	Tailpipe	1 ea.					
981.111.11	3.00	Seal	1 ea.					
900.910.003.03		Hexagon nut, M8	2 ea.					
981.111.281.02		Clamp	1 ea.					
999.512.707.00		Hose clamp	1 ea.					
Required m	Required materials:							
000.043.207.07		Optimol MF grease (75g tube)	0.15 ea. (= approx. 10 g)					
\Rightarrow Damage code WF57 066 000 2								

References:

s: \Rightarrow Workshop Manual '263319 Removing and installing rear silencer'

 \Rightarrow Workshop Manual '263519 Removing and installing tailpipe cover'

 \Rightarrow Workshop Manual '4X00IN Lifting the vehicle'

 \Rightarrow Workshop Manual '440519 Removing and installing wheel'

Important Notice: Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. If a particular condition is described, do not assume that the bulletin applies to your vehicle, or that your vehicle will have that condition. See your authorized Porsche Dealer for the latest information about whether a particular technical bulletin applies to your vehicle. Part numbers listed in these bulletins are for reference only. Always check with your authorized Porsche dealer to verify the current and correct part numbers. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

Dealership	Service Manager	 Shop Foreman	 Service Technician	 	
Distribution Routing	Asst. Manager	 Warranty Admin.	 Service Technician	 	

Dr. Ing. h.c. F. Porsche AG is the owner of numerous trademarks, both registered and unregistered, including without limitation the Porsche Crest®, Porsche®, Boxster®, Carrera®, Cayenne®, Cayman®, Macan®, Panamera®, Speedster®, Spyder®, 918 Spyder®, Tiptronic®, VarioCam®, PCM®, PDK®, 911®, RS®, 4S®, FOUR, UNCOMPROMISED®, and the model numbers and the distinctive shapes of the Porsche automobiles such as, the federally registered 911 and Boxster automobiles. The third party trademarks contained herein are the properties of their respective owners. Porsche Cars North America, Inc. believes the specifications to be correct at the time of printing. Specifications, performance standards, standard equipment, options, and other elements shown are subject to change without notice. Some options may be unavailable when a car is built. Some vehicles may be shown with non-U.S. equipment. The information contained herein is for internal authorized Porsche dealer use only and cannot be copied or distributed. Porsche recommends seat belt usage and observance of traffic laws at all times.