



NEW FLYER®

SB-10058937-7186

SERVICE MANUAL BULLETIN

This Service Manual Bulletin is prepared by the Publications Department of New Flyer Industries Canada ULC. Refer to details below.

SMB-145

ISSUE DATE: Jul 29 2015

APPLICABILITY					
VEHICLE LENGTH	<input type="checkbox"/> 30ft.	<input type="checkbox"/> 35ft.	<input type="checkbox"/> 40ft.	<input type="checkbox"/> 60ft.	<input checked="" type="checkbox"/> ALL
VEHICLE TYPE	<input type="checkbox"/> High Floor	<input type="checkbox"/> Low Floor	<input type="checkbox"/> Invero®	<input checked="" type="checkbox"/> Xcelsior®	<input type="checkbox"/> ALL
FUEL TYPE	<input checked="" type="checkbox"/> Diesel	<input checked="" type="checkbox"/> Electric	<input checked="" type="checkbox"/> CNG	<input type="checkbox"/> LNG	<input type="checkbox"/> ALL
	<input checked="" type="checkbox"/> Diesel/Electric	<input type="checkbox"/> Gas/Electric	<input type="checkbox"/> Fuel Cell		
SUBJECT	Wheel Flange Installation & Radius Rod Installation				
SECTION TITLE	1 - FRONT AXLE & SUSPENSION				
DETAILS	<p>This bulletin provides revised OEM information on the wheel flange and lower radius rod to axle installation.</p> <p>When installing the wheel flange, check condition of bolts. Replace any mounting bolts that show signs of damage or deformity.</p> <p>Use NEVER-SEEZ when installing the bolts for the lower radius rod to axle.</p> <p>This information supersedes any prior information on this subject already provided in your New Flyer Service Manuals. Make this Service Bulletin available to service personnel to inform them of changed information.</p>				