

TECHNICAL BULLETIN

LTB00829NAS1

29 SEP 2015



© Jaguar Land Rover North America, LLC

NOTE: The information in Technical Bulletins is intended for use by trained, professional Technicians with the knowledge, tools, and equipment required to do the job properly and safely. It informs these Technicians of conditions that may occur on some vehicles, or provides information that could assist in proper vehicle service. The procedures should not be performed by 'do-it-yourselfers'. If you are not a Retailer, do not assume that a condition described affects your vehicle. Contact an authorized Land Rover service facility to determine whether this bulletin applies to a specific vehicle.

SECTION: 414-00

Battery And/Or Charging System Concerns

AFFECTED VEHICLE RANGE:

Discovery Sport (LC)

Model Year: 2015 Onwards
VIN: 500429 Onwards
Manufacturing Plant: Halewood

LR4 (LA)

Model Year: 2010 Onwards
VIN: 510178 Onwards
Manufacturing Plant: Solihull

Range Rover Evoque (LV)

Model Year: 2012 Onwards
VIN: 000447 Onwards
Manufacturing Plant: Halewood

Range Rover Sport (LW)

Model Year: 2014 Onwards
VIN: 001154 Onwards
Manufacturing Plant: Solihull

Range Rover (LG)

Model Year: 2013 Onwards
VIN: 001204 Onwards
Manufacturing Plant: Solihull

LR2 (LF)

Model Year: 2010-2015
VIN: 148520-439912
Manufacturing Plant: Halewood

Range Rover Sport (LS)

Model Year: 2010-2013
VIN: 212145-814822
Manufacturing Plant: Solihull

MARKETS:

All

CONDITION SUMMARY:

Situation: The vehicle battery may be flat or one of the following messages/warning lights may be displayed on the Instrument Cluster:

- Faulty generator
- Faulty Battery Monitoring System (BMS)
- The charge warning indicator is illuminated when the engine is running.

Cause: The power supply is a fully integrated system that requires SDD to diagnose overall functionality robustly to make sure customer satisfaction is met via right first time diagnosis.

Action: Should a customer express this concern, follow the Diagnostic Procedure below.

PARTS:

No Parts Required

TOOLS:



NOTE: this is an 'Active Bulletin' that will display a functional programming shortcut if accessed within a diagnostic session using SDD.

SDD with latest DVD and Calibration File

Jaguar Land Rover-approved Midtronics battery power supply

WARRANTY:



NOTE: Repair procedures are under constant review, and therefore times are subject to change; those quoted here must be taken as guidance only. Always refer to TOPIx to obtain the latest repair time.



NOTE: DDW requires the use of causal part numbers. Labor only claims must show the causal part number with a quantity of zero.

DESCRIPTION	SRO	TIME (HOURS)	CONDITION CODE	CAUSAL PART
Battery - power supply service mode diagnostic	86.90.11	0.3	42	Refer to the Service Information section



NOTE: Normal Warranty procedures apply.

SERVICE INFORMATION:

1The causal part number will vary depending on the findings of the Diagnostic Procedure. Make sure the relevant causal part number is claimed based on the results.

DIAGNOSTIC PROCEDURE:



CAUTION: a Jaguar Land Rover-approved Midtronics battery power supply must be connected to the vehicle battery during SDD diagnosis / module programming.



CAUTION: ensure all ignition 'ON' / ignition 'OFF' requests are carried out; failure to perform these steps may cause damage to control modules in the vehicle.



NOTE: SDD must be loaded with DVD142.06 v.215 or later.

1Connect the Jaguar Land Rover-approved Midtronics battery power supply to the vehicle battery.

2Turn ignition 'ON' (engine not running).

3Connect the Symptom Driven Diagnostics (SDD) system to the vehicle and begin a new session.

4Follow the on-screen prompts, allowing SDD to read the VIN and identify the vehicle and initiating the data collect sequence.

5Select 'Diagnosis' from the Session Type screen.

6Select the 'Selected Symptoms' tab, and then select:

- Electrical > Battery > Charging system > Battery monitoring system **or**
- Electrical > Instruments > Warning lamps > Battery and alternator lamp **or**
- Powertrain > Engine system > Starting system > Start-stop system

7Select 'continue'.

8Select the 'Recommendations' tab, and then select '**Run**' to perform the 'Battery - Power supply service mode diagnostic' option.

9Follow all of the on screen instructions to complete the application.

10After the application has finished follow the on screen instructions for the next steps.

11When all of the tasks are complete, exit the current session.

12Disconnect the SDD and the battery power supply from the vehicle.