



Technical Service Bulletin

SUBJECT:		No: TSB-16-00-007	
TECHNICAL SPECIFICATIONS – 2017 MIRAGE G4		DATE: May, 2016	
		MODEL: 2017 Mirage G4	
CIRCULATE TO:	<input type="checkbox"/> GENERAL MANAGER	<input checked="" type="checkbox"/> PARTS MANAGER	<input checked="" type="checkbox"/> TECHNICIAN
<input checked="" type="checkbox"/> SERVICE ADVISOR	<input checked="" type="checkbox"/> SERVICE MANAGER	<input checked="" type="checkbox"/> WARRANTY PROCESSOR	<input checked="" type="checkbox"/> SALES MANAGER

2017 MIRAGE G4

ENGINE		ES / SE		TRANSMISSION RATIOS											
Type	1.2L DOHC, 12-valve Inline 3 cyl.														
Engine Code	3A92														
Engine Block/Cylinder Head	Aluminum / Aluminum														
Displacement (cu. in. / cc)	72.8 / 1193														
Bore x Stroke (in. / mm)	2.95 x 3.54 / (75.0 x 90.0)														
Compression Ratio	10.5:1														
Valve Train	DOHC Mitsubishi Innovative Valve-timing Electronic Control														
Horsepower @ RPM (BHP)	78 @ 6,000														
Torque @ RPM (lb-ft)	74 @ 4,000														
Redline	6,500 RPM														
Fuel System	Electronically Controlled Multi-point Fuel Injection														
Engine Oil Capacity (w/o filter)	2.96 Qts / 2.8 L														
Engine Oil Type	0W-20 (API Service Standard SN / ILSAC certification oil)														
SUSPENSION				RACK & PINION POWER ASSIST STEERING											
Front	Independent MacPherson strut suspension with coil springs and stabilizer bar			Electric Power Steering											
Rear	Torsion beam suspension with coil springs, shock absorbers			Turning Cir Wall - Wall 33.5 ft / 10.2 m											
				Turning Cir Curb - Curb 31.5 ft / 9.6 m											
BRAKES (in. / mm)				ELECTRICAL SYSTEM											
Front Disc Diameter (Vented)	9.9 / 251			Battery Group 55D23L / 356 (CCA)											
Rear Drum Inside Diameter	8.0 / 203			Alternator 85 A											
Anti-Lock Brake System	4-wheel, 4-channel ASC with EBD														
EXTERIOR DIMENSIONS (in. / mm)				WEIGHTS (5MT / CVT)											
Wheelbase	100.4 / 2550			GVWR - 3053 / 3108 lbs (1385 / 1410 kg)											
Length	169.5 / 4305			CURB WEIGHT (lbs / kg)											
Width	65.7 / 1670														
Height	59.2 / 1505														
Front Tread Width	56.9 / 1445														
Rear Tread Width	56.3 / 1430														
Min. Ground Clearance	6.3 / 160														
INTERIOR DIMENSIONS (cu. ft)															
SAE Interior Volume	101.8														
Passenger Volume	89.5														
Cargo Area	12.3														
PASSENGER SPACE (in. / mm)		Front		Rear											
Passenger Seating Capacity	5														
Head Room	39.1 / 994		36.9 / 936												
Shoulder Room	51.7 / 1314		51.2 / 1300												
Hip Room	48.8 / 1240		48.2 / 1225												
Leg Room	41.7 / 1058		37.2 / 944												
* WARRANTIES		Basic		Powertrain		Anti-corrosion		Emissions		Roadside					
Years	5		10		7		See Warranty Statement		5						
Miles	60,000		100,000		100,000		Unlimited								
* U.S. coverage shown. Coverage may vary according to terms in effect at the time of purchase.															
				WHEELS & TIRES											
				ES		SE									
				Type Steel		Alloy									
				Size 14 in.		15 in.									
				Tires 165/65R14		175/55R15									
				Spare T115/70D14 88M											
				FUEL TANK CAPACITY (gal / L)											
				9.2 / 35											
				EPA FUEL ECONOMY (MPG)											
				City		Hwy		Comb.							
				CVT 35		42		37							
				5 M/T 33		40		35							

Copyright 2016, Mitsubishi Motors North America, Inc.

The information contained in this bulletin is subject to change. For the latest version of this document, go to the Mitsubishi Dealer Link, MEDIC, or the Mitsubishi Service Information website (www.mitsubishitechinfo.com) (4405)