



Technical Service Bulletin

SUBJECT:		No: TSB-16-00-013	
TECHNICAL SPECIFICATIONS – 2017 OUTLANDER SPORT		DATE: September, 2016	
		MODEL: 2017 Outlander Sport	
CIRCULATE TO:	<input type="checkbox"/> GENERAL MANAGER	<input checked="" type="checkbox"/> PARTS MANAGER	<input checked="" type="checkbox"/> TECHNICIAN
<input checked="" type="checkbox"/> SERVICE ADVISOR	<input checked="" type="checkbox"/> SERVICE MANAGER	<input type="checkbox"/> WARRANTY PROCESSOR	<input checked="" type="checkbox"/> SALES MANAGER

2017 OUTLANDER SPORT

ENGINE	ES	SE / SEL / GT	TRANSMISSION RATIOS			
Type	2.0L MIVEC inline-4	2.4L MIVEC inline-4	M/T	CVT (2.0)	CVT (2.4)	
Engine Code	4B11	4B12	CVT Mode	N/A	2.631-0.378 2.349-0.394	
Engine Block/Cylinder Head	Aluminum/Aluminum		1 st	3.833	2.631 2.349	
Displacement (cu. in./cc)	122 / 1998	144 / 2360	2 nd	1.913	1.440 1.517	
Bore x Stroke (in./mm)	3.4 x 3.4 / 86.0 x 86.0	3.5 x 3.8 / 88 x 97	3 rd	1.333	1.165 1.105	
Compression Ratio	10:1	10.5:1	4 th	1.028	0.906 0.857	
Horsepower @ RPM	148 bhp @ 6000	168 bhp @ 6000	5 th	0.820	0.680 0.621	
Torque @ RPM (lb-ft)	145 lb/ft @ 4200	167 lb/ft @ 4100	6 th	N/A	0.499 0.446	
Valve Train	DOHC 16V		Rev	3.583	1.960 1.750	
Redline	6500 RPM		Final Drive	4.235	6.026 6.466	
Fuel System	Electronically Controlled Multi-Point Fuel Injection		RACK & PINION POWER ASSIST STEERING			
Engine Oil Capacity (w/o filter)	CVT: 4.5 qt. / 4.2 L	4.5 qt. / 4.3 L	Type:	Electric power assisted rack & pinion		
Engine Oil Type	0W-20 Minimum: API Service Standard SN (ILSAC certification)		Ratio	43.69 mm/rev		
SUSPENSION			Turns Lock - Lock	3.3		
Front	Independent MacPherson strut, coil springs, stabilizer bar		Turn. Cir C-C (ft/m)	34.8 / 10.6		
Rear	Multi-link, coil springs, stabilizer bar		ELECTRICAL SYSTEM			
BRAKES			Battery	75D23L		
Frt. Ventilated Disc Diameter	11.6" / 294 mm		Alternator	520 CCA		
Rear Solid Disc Diameter	11.9" / 302 mm		130 amp			
Total swept area (sq. in.)	424		WEIGHTS (lbs / kg)			
Anti-Lock Brake System	4-sensor, 4-channel with EBD		GVWR (All)	4343 / 1970		
EXTERIOR DIMENSIONS (in. / mm)			Curb wt.	2WD	AWC	
Wheelbase	105.1 / 2670		ES (CVT)	3109 / 1410	3252 / 1475	
Length	171.5 / 4356		ES (M/T)	3032 / 1375	N/A	
Width	71.3 / 1811		SE	3109 / 1410	3252 / 1475	
Height	64.8 / 1646		SEL	3142 / 1425	3265 / 1481	
Front Tread Width	60.6 / 1539		GT	N/A	3285 / 1490	
Rear Tread Width	60.6 / 1539		Weight Distribution			
Min. Ground Clearance	8.5 / 216		CVT (M/T)	60/40 (59/41)	59/41 (N/A)	
INTERIOR DIMENSIONS (cu. ft.)			WHEELS & TIRES			
Interior Volume	119.2 (117.3 w/panoramic roof)		Wheels	18 x 7 J Aluminum Alloy		
Passenger	97.5 (95.6 w/panoramic roof)		Tires	P225/55R 18 97H - NEXEN		
Cargo capacity behind frt. seat	49.5 (48.8 w/panoramic roof)		Spare Tire	T155/90D16		
Cargo capacity behind rear seat	21.7 (20.1 w/subwoofer)		FUEL TANK CAPACITY (gal / L)			
PASSENGER SPACE (in./mm)			16.6 / 62.8 (2WD)		15.8 / 59.8 (AWC)	
	Front	Rear	EPA FUEL ECONOMY (mpg)			
Headroom (w/ panoramic roof)	39.4 / 1000 (38.9 / 988)	37.9 / 962.7 (36.8 / 934.7)		City	Hwy	Comb.
Shoulder Room	56.2 / 1428	55.5 / 1410	ES 2WD (M/T)	24 (23)	30 (29)	27 (25)
Hip Room	52.1 / 1323	51.6 / 1310	ES AWC	23	29	26
Leg Room (MAX)	41.6 / 1056	36.3 / 921	SE 2WD	TBD		
Max. Passenger Capacity	5 passengers		SE AWC			
WARRANTIES - U.S. shown - Coverage may vary according to terms in effect at time of first sale.						
	Basic	Powertrain	Anti-corrosion	Emissions		
Yrs	5	10	7	See individual statement for CA & Fed. coverage		
Miles	60,000	100,000	100,000			
*U.S. coverage shown. Coverage may vary according to terms in effect at the time of purchase						

Copyright 2016 Mitsubishi Motors North America, Inc.

The information contained in this bulletin is subject to change. For the latest version of this document, go to the Mitsubishi Dealer Link, MEDIC, or the Mitsubishi Service Information website (www.mitsubishitechinfo.com).

(4457)