



NEW FLYER®

SERVICE MANUAL BULLETIN

This Service Manual Bulletin is prepared by the Publications Department of New Flyer Industries Canada ULC. This Service Bulletin supersedes existing information in your New Flyer Service Manual. Refer to details below.

SMB-162

ISSUE DATE: Sep 22 2016

APPLICABILITY					
VEHICLE LENGTH	<input type="checkbox"/> 30ft.	<input type="checkbox"/> 35ft.	<input type="checkbox"/> 40ft.	<input type="checkbox"/> 60ft.	<input checked="" type="checkbox"/> ALL
VEHICLE TYPE	<input type="checkbox"/> High Floor	<input checked="" type="checkbox"/> Low Floor	<input type="checkbox"/> Invero	<input checked="" type="checkbox"/> Xcelsior	<input type="checkbox"/> ALL
FUEL TYPE	<input type="checkbox"/> Diesel	<input type="checkbox"/> Electric	<input checked="" type="checkbox"/> CNG	<input type="checkbox"/> LNG	<input type="checkbox"/> ALL
	<input type="checkbox"/> Diesel/Electric	<input type="checkbox"/> Gas/Electric	<input type="checkbox"/> Fuel Cell		
SUBJECT	Pressure Relief Device (PRD) - Activation				
SECTION TITLE	7 - CNG FUEL SYSTEM				
DETAILS	<p>This bulletin identifies the activation temperature for Pressure Relief Devices (PRD) manufactured by OMB, P/N 554507 on your New Flyer Vehicle.</p> <p>This PRD will activate when the temperature rises above the eutectic ring melting temperature of 230 °F (110 °C).</p> <p>This information supersedes any prior information on this subject already provided in your New Flyer Manuals. Make this Service Bulletin available to service personnel to inform them of changed information and procedures.</p>				