TOYOTA Sienna 2017 PRE-DELIVERY SERVICE CHECK SHEET

BEFORE INSPECTION Image: State and Cycle ignition "IG-ON"; place gear selector in reverse; turn UNDER VEHICLE (ON 1 Install short pin (see page 2) 1 1 Remove disc brake anti-rus wheel film* (remove just prior) 2 Initialize power back door* (see page 2) 1 1 Remove disc brake anti-rus wheel film* (remove just prior) 3 Initialize power back door* (see page 2) 1 1 1 1 4 Initialize Parking Assist Monitor System* 1 1 1 1 1 FUNCTIONAL OPERATION 1	t covers/a
 2 Initialize power sliding door* (see page 2) 3 Initialize power back door* (see page 2) 4 Initialize Parking Assist Monitor System* 5 FUNCTIONAL OPERATION Apply parking brake and cycle ignition "IG-ON"; place gear selector in reverse; turn 	
 2 Initialize power sliding door* (see page 2)	r to custom
 3 Initialize power back door* (see page 2) 4 Initialize Parking Assist Monitor System* FUNCTIONAL OPERATION Apply parking brake and cycle ignition "IG-ON"; place gear selector in reverse; turn 2 Inspect tires for defects/dama 3 Initialize Tire Pressure Warning 4 Install wheel covers/caps/space 4 Install wheel covers/caps/space 	
FUNCTIONAL OPERATION (see page 2)4 Apply parking brake and cycle ignition "IG-ON"; place gear selector in reverse; turn 4 Install wheel covers/caps/spa	ıge (includir
Apply parking brake and cycle ignition "IG-ON"; place gear selector in reverse; turn 4 Install wheel covers/caps/spa	ng System
Apply parking brake and cycle ignition "IG-ON"; place gear selector in reverse; turn 4 Install wheel covers/caps/spa	
on lights and rear defogger. Unlock all doors, release fuel door. 5 Inspect for fuel, oil, coolant, a	
1 Check dome, courtesy, map, and sun visor lights*	
2 Check warning/indicator lights, gauges, and horn	
3 Check windshield wipers and washers	
4 Check field lights, instrument lights, turn signals,	
	tomor satisfa
6 Check cigarette lighter* and power outlets	
8 Check audio/navigation*/backup camera* systems and	
set clock	Reading A
9 Check Rear Seat Entertainment system operation*	¥
0 Check Automatic Door Lock (ADL) function*	
1 Install shift-lock override button cover	
2 Check Auto Access Seat*	
5. Check broke and parties had	•
WALKAROOND INSPLCTION 6 Check steering operation and	
Start at left front door. Check window and door lock operation (from master power	
switch, if equipped). Continue around vehicle in a counterclockwise direction shecking each door and window operation, child door locks, seat belts, interior 8 Inspect for squeaks and rattle	
ondition, all lights, luggage compartment contents. Finish by checking headlight 9 Check front and rear* heater a	
im and continue into UNDER HOOD checks.	•
1 Check Smart Key System*	
2 Check door and door lock operation, including each 12 Set/calibrate compass* (see	•
wireless remote control/theft deterrent system*	
3 Check window operation	
Check that engine starts with an keys	
Check that child safety door locks are in hormal	
(unlocked) position	
o Check seals and seal bell operation	
retaining clips*	
8 Check side marker, tail, backup, and license plate lights 4 Verify green light is illuminate	d on SOS
9 Check luggage compartment light* and trim appearance 0 Adjust spare tire pressure* & check jack & tool installation	
1 Check headlight aim	
UNDER HOOD 7 Inspect paint finish for scratch	
1 Check engine oil level	
2 Check brake fluid level	
3 Check engine coolant level	
4 Check windshield washer fluid level	
5 Check battery state-of-charge using Digital Battery 10 Place Owner's Manual portfol	
5 Check battery state-of-charge using Digital Battery System Analyzer (SOC Reading:%) 10 Place Owner's Manual portfol 11 Install front license plate and 10 6 Inspect for fuel, oil, coolant, and other fluid leaks 10	
5 Check battery state-of-charge using Digital Battery System Analyzer (SOC Reading:%) 10 Place Owner's Manual portfol 6 Inspect for fuel, oil, coolant, and other fluid leaks 11 Install front license plate and install front license plate	Check
5 Check battery state-of-charge using Digital Battery System Analyzer (SOC Reading:%) 10 Place Owner's Manual portfol 11 Install front license plate and (see page 2) 6 Inspect for fuel, oil, coolant, and other fluid leaks 10 Place Owner's Manual portfol	Check
5 Check battery state-of-charge using Digital Battery System Analyzer (SOC Reading:%) 10 Place Owner's Manual portfol 6 Inspect for fuel, oil, coolant, and other fluid leaks 11 Install front license plate and installicense plate and install front license plate and inst	Check ap*
5 Check battery state-of-charge using Digital Battery System Analyzer (SOC Reading:%) 10 Place Owner's Manual portfol 6 Inspect for fuel, oil, coolant, and other fluid leaks 10 Place Owner's Manual portfol Notes: 11 Install front license plate and the state of the state o	Check ap*
5 Check battery state-of-charge using Digital Battery System Analyzer (SOC Reading:%) 10 Place Owner's Manual portfol 6 Inspect for fuel, oil, coolant, and other fluid leaks 10 Place Owner's Manual portfol Notes: 11 Install front license plate and the state of the state o	Check ap* I/required.
5 Check battery state-of-charge using Digital Battery System Analyzer (SOC Reading:%) 10 Place Owner's Manual portfol 6 Inspect for fuel, oil, coolant, and other fluid leaks 11 Install front license plate and to see page 2) Notes: 12 Perform Techstream Health Constrained to see to serve to wing hitch can be added to serve to serve to serve to wing hitch can be added to serve to se	Check ap*

	- 4 0
Remove disc brake anti-rust covers/anti-corrosion	
wheel film* (remove just prior to customer delivery)	
Inspect tires for defects/damage (including spare tire*)	. – – –
Initialize Tire Pressure Warning System (TPWS)	
(see page 2)	
Install wheel covers/caps/spare tire wheel covers*	
Inspect for fuel, oil, coolant, and other fluid leaks	
Inspect under the vehicle for damage, rust, etc	╷╷└┚└┚
Visually check bolts and nuts on chassis and powertrain	
for looseness	ப ப
Install rubber body plugs (stored in glove box or center	
console)*	
ROAD TEST	
complete road test helps assure customer satisfaction. Drive vehicle ov	/er a
ariety of road surfaces and driving conditions. Check for unusual noise a	
erformance.	
nter Odometer Readings	
eading Before Test: Reading After Test:	
Check cold engine operation	
Check engine operation during warm-up	
Check engine at normal operating temperature	
Check automatic transmission operation	
Check brake and parking brake operation	. 🗆 🗖
Check steering operation and off-center/vehicle pull/flutter	
Inspect for abnormal noise and vibration	
Inspect for squeaks and rattles	
Check front and rear* heater and A/C operation	
Check cruise control operation*	
Check front seat heater/ventilation operation*	니브브
Set/calibrate compass* (see page 2)	. 🔲 🗆
FINAL INSPECTION AND CLEANING	
Remove interior protective covers, unnecessary labels,	
tags, etc. (Remove just before delivery to customer)	
Visually inspect all interior parts for installation, damage,	1
fit, dirt, etc	
Verify floor mat application and install using	1
retaining clips*	
Varify groon light is illuminated on SOS (Safety	· · · ·
Verify green light is illuminated on SOS (Safety	
Connect) button*	·┌─╯└┛
Remove Rapgard [™] and clear protective bumper film*	·닐빌
Wash and clean vehicle	ם כון .
Inspect paint finish for scratches, chips, rust, dents,	
damage, etc	
Inspect exterior body parts for proper installation, damage,	,
rust, etc	
Place oil change sticker on inside of windshield, top	
left corner	
Place Owner's Manual portfolio* in glove box	
Install front license plate and mounting bracket*	
(see page 2)	
Perform Techstream Health Check	
	·╠╹
Install receiver towing hitch cap*	·· I
nspect or install when equipped/required.	

August 2016

OK / (epair

We hereby certify that all items on this form have been checked and corrected for

					proper operation as required.
NAME (PLEASE PRIN	Т)	NAME (PLEASE F	PRINT)		
Date	Dealer Name		Dealer Code	Vehicle Identificat	ion Number (Sticker)

SHORT PIN INSTALLATION

To minimize battery discharge the short pin has been removed and is stored in the engine compartment relay block. Install the short pin and confirm all related DTCs are cleared.

DTC Clearing Procedure

- 1. Connect Techstream to DLC3.
- 2. Cycle the ignition switch to the "IG-ON" position.
- 3. Using Techstream, check any other codes being output.
- 4. Erase DTCs (B1650 and B1794) and Freeze Frame Data.

NOTE

If any DTCs besides B1650 and B1794 remain, repair the applicable system according to the Repair Manual.


POWER SLIDING AND POWER BACK DOOR INITIALIZATION

As a result of the removal of the Short Pin, the "automatic open and close" and "jam protection" functions of the power sliding and power back door will be inoperative due to loss of the power back door position. Initialize the power back door after installing the Short Pin in its original location during Pre-Delivery Service (PDS).

Power Sliding Door

Refer to the Repair Manual for the Initialization procedure.

Power Back Door Refer to the Repair Manual for the Initialization procedure.



ההההההההה

600600

2 Installation Location

0000

1 Storage Location

الالالالي وحواوها

ΠΠ

3 Front

TIRE PRESSURE WARNING SYSTEM (TPWS) INITIALIZATION

Refer to the Repair Manual for the Initialization procedure.

NOTE

To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using Techstream and select the "Compensation Tire Pressure" checkbox. Compensation pressures will be displayed on the Health Check results screen. Adjust the tire pressure when the tires are cold.

COMPASS CALIBRATION

Refer to the Repair Manual for the Calibration procedure for vehicles equipped with a compass in the rear view mirror.

NOTE

- Do NOT perform calibration of the compass in a place where the Earth's magnetic field is subject to interference by artificial magnetic fields (underground parking, under a steel tower, between buildings, roof parking, near a railroad crossing, etc.).
- During calibration, do NOT operate electric systems (moon roof, power windows, etc.) as they may interfere with the calibration.

FRONT LICENSE PLATE & MOUNTING BRACKET INSTALLATION*

- 1. Insert the license plate into the front license plate bracket.
- 2. Align the installation holes on the front license plate mounting bracket and front license plate with the dimples on the front bumper.
- Screw in the 2 self-tapping screws directly into the dimples to install the front license plate and mounting bracket onto the bumper.

NOTICE

- Do NOT pre-drill holes into the bumper.
- Do NOT overtighten the self-tapping screws.

