



# CC - 2017 FLUID CAPACITY CHART

11/22/2016



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Brake System	A/C System	Windshield Fluid
<b>CC</b> FWD Auto  (3581FD) (3587YD) (358CFD)	<b>2.0 TFSI 200 hp (CCTA / CBFA)</b>  4.7 L (4.9 q.t.)  <u><b>VW Oil Spec:</b></u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<b>NA</b>	<b>6-Spd DSG (02E)</b>  <u><b>New Fill:</b></u> 6.9 – 7.2L (7.3 – 7.6 qt)  <u><b>Change:</b></u> 5.2L (5.5 qt)  <u><b>Mechatronic Only</b></u> 3.0 – 4.0 L (3.1-4.2qt.) <u><b>Oil PN</b></u> G 052 182 A2*	Capacity included with transmission.	8.0L (8.5 qt)***	1.2 L (1.3qt) (approximately)  <u><b>VW Brake Fluid Specification:</b></u>  Use new fluid only. VW 501 14 or FMVSS 116 DOT 4  <u><b>Fluid PN</b></u> B 000 750 *	<u><b>Refrigerant</b></u> Use only R134a  <u><b>Refrig. Capacity</b></u> 550 ± 5 grams (19.4 ± 0.2 oz.)  <u><b>Refrigerant Oil</b></u> Use a PAG oil with R134a  <u><b>Oil PN &amp; Capacity</b></u> 1) For Sanden use G 052 154 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.)  2) For Zexel use G 052 200 A2* 120 cc ± 15 cc (4.0 ± 0.5 fl. oz.)  3) For Denso use G 052 300 A2* 140 cc ± 10 cc (4.7 ± 0.3 fl. oz.)  4) For Delphi use G 052 154 A2* or G 052 300 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.)	3.0L (3.1qt)  <u><b>Fluid PN</b></u> G 052 164*
<p><b>For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.</b></p> <p>* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.</p> <p>**Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.</p> <p>*** VW Coolant Additive Specification and Part Number: (color is pink) <b>G 13</b> (TL-VW 774 J). <b>Dilute with Distilled Water.</b></p>								