



Golf - 2017 FLUID CAPACITY CHART 11/22/2016

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Brake System	A/C System	Windshield Fluid
Golf FWD-Manual (AU1WQ1)	1.8L 170hp (CXBA/CXBB)	5-Spd (0A4)	N/A	N/A	8.0 L (8.45 qt.)***	1.2 L (1.3qt) (approximately)	<u>Refrigerant</u> Use only R134a	3.0 L- 5.0 L (3.1 - 5.2 qt.
(AU12Q1)	5.5 L (5.7 qt.) <u>VW Oil Spec:</u>	1.9 L (2.0 qt.) <u>Change:</u> 1.7L (1.8 qt.)				<u>VW Brake Fluid</u> Specification:	Refrig. Capacity 500 ± 15 grams (17.6 ± 0.5 oz.)	Fluid PN G 052 164*
	VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30	<u>Oil PN</u> G 052 512 A2*				Use new fluid only. VW 501 14 or FMVSS 116 DOT 4	<u>Refrigerant Oil</u> Use a PAG oil with R134a	
	SAE 5W-30					<u>Fluid PN</u> B 000 750 *	Oil PN & Capacity	
Golf FWD-Auto (AU1WQ3) (AU12Q3)	-	N/A	6-Spd (09G)				Use: G 052 300 A2* 110 cc ± 10 cc (3.7 ± 0.3 fl. oz.)	
			<u>New Fill:</u> 7.0 L (7.4 qt.)				For Sanden Use <u>:</u> G 052 154 A2* 75 cc ± 10 cc	
			<u>Change:</u> 3.0 L (3.1 qt.)				$(2.5 \pm 0.3 \text{ fl. oz.})$	
			<u>Oil PN</u> G 055 540 A2*					

© 2016 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.