Audi Service



2015 MY Scheduled Maintenance Intervals

The first scheduled service is due at 5,000 miles (8,000km) or 1 year after delivery, whichever occurs first. Thereafter, all remaining scheduled services are due every 10,000 miles or 1 year after previous service, whichever occurs first.

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95/135	35/75/115
Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145/205	55/115/175
Engine Oil/Oil Filter – change oil and replace filter	•	•	•
AdBlue Fluid – fill completely with fresh fluid (maximum capacity: 24 liters)	 A3 2.0L TDI, Q5 3.0L TDI, A6 3.0L TDI and A7 3.0L TDI, Q7 3.0L TDI and A8 3.0L TDI only 	 A3 2.0L TDI, Q5 3.0L TDI, A6 3.0L TDI and A7 3.0L TDI, Q7 3.0L TDI and A8 3.0L TDI only 	A3 2.0L TDI, Q5 3.0L TDI, A6 3.0L T and A7 3.0L TDI, Q7 3.0L TDI and A8 3.0L TDI only
Cooling System – check level, add if necessary		•	•
Engine Compartment – check for leaks		•	•
Onboard Diagnosis - check	Flex Fuel vehicles only	Flex Fuel vehicles only	Flex Fuel vehicles only
Visual Check – check the chassis for possible paint damage and corrosion, from the inside and outside, with the doors as well as hood and trunk lids open			•
Battery – check for clean terminals (no corrosion), properly mounted housing, and no damage; replace if necessary. Also, check the acid level of battery only if the level can be seen through the housing and fill if necessary		except Q5 hybrid	except Q5 hybrid
Small (12-volt) Side Battery – located in the trunk compartment on left side – check for clean terminals (no corrosion), properly mounted housing and no damage; replace if necessary		Q5 hybrid only	Q5 hybrid only
Dust and Pollen Filter - replace		•	•
Spark Plugs – replace at 35,000 miles (55,000 km) or 6 years, whichever occurs first. Thereafter, every 40,000 miles (60,000 km) or 6 years, whichever occurs first*			 all vehicles with the 4.0L VB TFSI, AB W12, all vehicles with 2.0L TFSI (except Q3 and Flex Fuel engines)
 replace at 55,000 miles (85,000 km) or 6 years, whichever occurs first. Thereafter, every 60,000 miles (90,000 km) or 6 years, whichever occurs first 		 55K only: vehicles with the 1.8L (A3), 2.0L TFSI (Q3), 3.0L V6 TFSI, 4.2L V8 FSI and 5.2L V10 FSI engines 	
 replace at 35,000 miles (55,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first 			 35K only: 2.0L TFSI Flex Fuel engines only
Power Steering Fluid - check, add if necessary			A8, Q7 only
Air Cleaner – clean housing, replace filter element		 55K only: except RS 5, S6, S7, RS 7, A8 3.0L V6 TFSI, A8 3.0L V6 TDI, A8 4.0L V8 TFSI and TTS 	 RS 5, S6, S7, A8 3.0L V6 TDI, A8 3 V6 TFSI, A8 4.0L V8 TFSI, TTS and RS 7 only
- clean housing, replace filter element		RS 5 only	N3 / Only
Ribbed V Belt and Tensioner – check condition and replace if necessary		R8 Coupe, R8 Spyder only	R8 Coupe, R8 Spyder only
Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary			75K only
 replace only the belt for the compressor drive (front belt) 		 55K only: all vehicles with the 3.0L V6 TFSI 	 115K only: all vehicles with the 3.0L V6 TFSI
Snow Screen for Air Cleaner – clean		 A4, S4, allroad, A5, A5 Cabriolet, S5, S5 Cabriolet, Q5, SQ5 and Q5 hybrid only 	 A4, S4, allroad, A5, A5 Cabriolet, S5, S5 Cabriolet, Q5, SQ5 and Q5 hybrid only
Fuel Filter – replace		 A3 2.0L TDI, A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, Q5 3.0L TDI and Q7 3.0L TDI only 	 A6 3.0L TDI, A7 3.0L TDI, A8 3.0L Q5 3.0L TDI and Q7 3.0L TDI only
Diesel Particulate Filter (DPF) – perform after the first 115K miles (USA)/175,000 km (Canada) or 110K miles (USA)/165,000 km (Canada) after a Diesel Particulate Filter (DPF) replacement; check ash loading according to manufacturer's work procedure, replace** if necessary	USA: 115K only: A3 2.0. TDI, A6 3.0. TDI, A7 3.0. TDI, A8 3.0. TDI, Q5 3.0. TDI and Q7 3.0. TDI Q5 3.0. TDI and Q7 3.0. TDI Canada: 175 km only: A3 2.0. TDI, A6 3.0. TDI, A7 3.0. TDI, A8 3.0. TDI, Q7 3.0. TDI and Q7 3.0. TDI		
Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary		•	•
Tires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS)	•		
 check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) 		•	•
Tires – rotate, reset TPMS	5K only		
Wiper Blades – check condition and replace if necessary (USA only)	•	•	•
Wiper Blades – check condition (Canada only)		•	•
Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	•	•	•
Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			
Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights		•	•
Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights		•	•
Service Reminder Display – reset	•	•	•
Horn – check function Door Hinges and Straps – lubricate		Q7, TT, TTS, R8 Coupe and R8 Spyder only	•
		no opywer only	
Doors – lubricate door hinges, straps, locks and hood latch			continued





2015 MY Scheduled Maintenance Intervals (continued)

The first scheduled service is due at 5,000 miles (8,000km) or 1 year after delivery, whichever occurs first. Thereafter, all remaining scheduled services are due every 10,000 miles or 1 year after previous service, whichever occurs first.

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95/135	35/75/115
Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145/205	55/115/175
Hood Lid Hinges – lubricate		R8 Coupe, R8 Spyder, TT and TTS only	R8 Coupe, R8 Spyder, TT and TTS only
All Sunroof Systems – clean guide rails and lubricate with grease		•	•
Front Latch for Cabriolet Roof - lubricate		 A3 Cabriolet, A5 Cabriolet and S5 Cabriolet only 	 A3 Cabriolet, A5 Cabriolet and S5 Cabriolet only
Brake System - check for damage, leaks, pad thickness, fluid level	•	•	•
Brake Discs – check thickness			•
Exhaust System – check for damage, leaks		•	•
Front and Rear Axle – check for excessive play, check dust seals on ball joints and tie rod ends		•	•
Drive Shaft Boots - check		•	•
Automatic Transmission and Final Drive - check for leaks		•	•
Manual Transmission and Final Drive - check for leaks		•	•
Continuously Variable Transmission (multitronic) – change ATF			•
DSG/S Tronic® – change MTF oil for gear box		RS 5 only	RS 5 only
DSG/S Tronic – change ATF oil and replace transmission filter element for clutch hydraulics			A3, S4, S5, S5 Cabriolet, S6, S7, RS 5, TT, TTS, R8 Coupe and R8 Spyder
Tiptronic Gear Box – change ATF			Q5 hybrid only
Rear Sport Differential – change ATF for clutch hydraulics and differential oil			RS 5 and RS 7 only
Underbody – check for damage and leaks		•	•
Road Test – check engine performance, clutch, manual/automatic transmission, braking (including hand and foot brake), steering, wheels, wheel bearings, drive shaft, horn and hybrid vehicles (electric drive for operational readiness)		•	•
Timber Balt, and as at 110K wiles (175,000 km) or TTC Charles a dition of timber bulk to a incident			

Timing Belt - replace at 110K miles (175,000 km) on TTS. Check condition of timing belt tensioning system, dampening pulleys and idler pulleys, and replace if necessary

Brake Fluid – replace every 2 years regardless of mileage

Cloth Top – check function and rollover protection every 2 years regardless of mileage (A5/S5 Cabriolet and R8 Spyder only)

AdBlue Fluid - replace every 4 years regardless of miles/kilometers only if AdBlue has not been filled within the last 4 years (Q7 3.0L TDI, A8 3.0L TDI, A7 3.0L TDI, A7 3.0L TDI and Q5 3.0L TDI only)

Crash Active Headrest – check function every 2 years regardless of miles/kilometers (A8 only)

BorgWarner Clutch – change oil every 3 years regardless of mileage/kilometers (A3, Q3, TT and TTS only)

*Does not include 2.0L TFSI Flex Fuel engines.

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.

^{**}If DPF replacement is not necessary, perform check every 20,000 miles (30,000 km) thereafter until replacement becomes necessary. Subsequent DPF replacement interval is a minimum of 120,000 miles (195,000 km) thereafter.