

HINO GENUINE COOLANT

The New Standard for Super High Performance



COOLANT

PART NUMBER	DESCRIPTION
HP-LLC-01	1 gallon bottle (6 bottles per case)
HP-LLC-55	55 gallon plastic drum (4 drums per skid)



HINO GENUINE COOLANT

- Protects water pump seals.
- Will not clog radiators from silicone "gelling".
- Will not corrode aluminum surfaces with borate.
- Active ingredients: Water, Ethylene Glycol, Diethylene Glycol, Sebacic Acid, Potassium Hydroxide.

FORMULATION APPROACH

HINO LLC-EX SUPER Antifreeze/Coolant is a new generation ethylene glycol-based premium engine coolant offering excellent corrosion protection and formulated specifically for HINO engines.

- Ready to use in a 50/50 prediluted formulation
- Meets ASTM specifications: ASTM-D-3306
- Can extend your fill intervals up to three years/ 360,000 miles*
- Freeze point approximately: -42° C (-34° F)
- Boiling point approximately: 37° C (265° F)
- Meets all Hino warranty requirements
- Highly recommended by Hino Motor Trucks

In fact, all 2005 and later Hino truck models are filled with Hino LLC-EX SUPER Antifreeze/Coolant at the factory.

APPLICATIONS

- All Hino and other OEM truck applications with cooling systems requiring Super Long Life Antifreeze/Coolant.

* See your Hino Truck Manual for complete details.



B U S I N E S S I N M O T I O N