

PUREHINO



**DRAIN INTERVALS UP TO TWICE
AS LONG AS GENERIC BRANDS
HINO GENUINE ENGINE OIL**

PUREHINO



A Toyota Group Company



6 REASONS TO USE HINO GENUINE OIL

IMPROVED PERFORMANCE:

Specifically developed for Hino J series engines with common rail fuel injection

EXTENDED OIL LIFE:

Enjoy the benefits of up to 20,000 miles between oil drain intervals for 2005 and later Hino trucks (See your owners manual for complete maintenance details for your specific make and model)

REDUCED MAINTENANCE COSTS:

Longer drain intervals can significantly reduce preventative maintenance costs

INCREASED UPTIME:

Less time in the shop means more time to make money

CLEANER RUNNING:

Designed to reduce soot, minimize piston deposits and neutralize acid levels

REDUCED OIL CONSUMPTION:

Superior shear stability minimizes oil consumption and increases oil film strength for greater engine protection

TYPICAL ANALYSIS

Exceeds API Service Categories:

- SAE 15W-40 (CJ-4, CI-4 Plus, CI-4, CH-4, CG-4, CF-4, CF, SM)
- SAE Grade: 15W-40
- Viscosity @ 100° C, cSt: 15.0
- Viscosity @ 40° C, cSt: 110
- Viscosity Index: 140
- Viscosity CCS, cP @ -20° C: 6020
- Flash Point: 224°C (435°F)
- Pour Point: -42°C
- Gravity, °API: 30.38
- Pounds per Gallon: 7.278
- Ash Content, % Wt.: 1.0
- Total Base Number ASTM D-2896: 11

ENGINEERED FOR YOUR HINO TRUCK

HINO GENUINE OIL sets the standard for super high performance diesel engine oils. Delivering up to twice the drain interval of generic oils, Its advanced low ash, soothandling technology breaks the mold for conventional heavy duty engine oils.

Developed in partnership with BP Lubricants USA Inc., and combining high performance synthetics with Hino's proprietary (high TBN and low ash) additive chemistry, Hino Genuine Oil greatly extends conventional service intervals and extends time-to-engine-rebuild and equipment life.

The Bottom Line: Hino Genuine Oil provides extended drain intervals (up to 20,000 miles), superior performance and protection for your engine, enhanced component and equipment life, lower maintenance costs and increased profitability. **Period.**

PART NUMBER	DESCRIPTION:
15000-0005	1 gallon jug 3 gallons per case 60 cases per skid 180 total gallons per skid
15000-0001	55 gallon drum – 4 drums per skid

HINO GENUINE MOTOR OIL MEETS THE FOLLOWING SPECIFICATIONS

- Caterpillar ECF-3
- Cummins CES 20081
- Detroit Diesel Power Guard 93K218
- Deutz
- Navistar International
- Mack EO-O Premium Plus
- Volvo VDS-4
- Hino Trucks (Extended Drain Interval)



HINO.COM