



Technical Service Bulletin

SUBJECT:		No: TSB-16-00-002	
TECHNICAL SPECIFICATIONS – 2017 MIRAGE		DATE: March, 2016	
		MODEL: 2017 Mirage	
CIRCULATE TO:	<input type="checkbox"/> GENERAL MANAGER	<input checked="" type="checkbox"/> PARTS MANAGER	<input checked="" type="checkbox"/> TECHNICIAN
<input checked="" type="checkbox"/> SERVICE ADVISOR	<input checked="" type="checkbox"/> SERVICE MANAGER	<input checked="" type="checkbox"/> WARRANTY PROCESSOR	<input checked="" type="checkbox"/> SALES MANAGER

2017 MIRAGE

ENGINE		ES / SE / GT		TRANSMISSION RATIOS			
Type	1.2L DOHC, 12-valve Inline 3 cyl.				MT	CVT	
Engine Code	3A92			Gear		4.007 ~ 0.550	
Engine Block/Cylinder Head	Aluminum / Aluminum			1 st	3.545	N/A	
Displacement (cu. in. / cc)	72.8 / 1193			2 nd	1.913	N/A	
Bore x Stroke (in. / mm)	2.95 x 3.54 / (75.0 x 90.0)			3 rd	1.310	N/A	
Compression Ratio	10.5:1			4 th	0.973	N/A	
Valve Train	DOHC Mitsubishi Innovative Valve-timing Electronic Control			5 th	0.804	N/A	
Horsepower @ RPM (BHP)	78 @ 6,000			Reverse	3.214	3.771	
Torque @ RPM (lb-ft)	74 @ 4,000			Final Drive	4.055	3.757	
Redline	6,500 RPM						
Fuel System	Electronically Controlled Multi-point Fuel Injection			RACK & PINION POWER ASSIST STEERING			
Engine Oil Capacity (w/o filter)	2.96 Qts / 2.8 L			Electric Power Steering			
Engine Oil Type	0W-20 (API Service Standard SN / ILSAC certification oil)			Turning Cir Wall - Wall	32.1 ft / 9.8 m		
SUSPENSION				Turning Cir Curb - Curb	30.2 ft / 9.2 m		
Front	Independent MacPherson strut suspension with coil springs and stabilizer bar			ELECTRICAL SYSTEM			
Rear	Torsion beam suspension with coil springs, shock absorbers			Battery	Group 55D23L / 356 (CCA)		
BRAKES (in. / mm)				Alternator	85 A		
Front Disc Diameter (Vented)	9.9 / 251			WEIGHTS (5MT / CVT)			
Rear Drum Inside Diameter	8.0 / 203			GVWR - 2910 / 3020 lbs (1320 / 1370 kg)			
Anti-Lock Brake System	4-wheel, 4-channel ASC with EBD			CURB WEIGHT (lbs / kg)			
EXTERIOR DIMENSIONS (in. / mm)					ES	SE	GT
Wheelbase	96.5 / 2450			5M/T	2018 / 915	2040 / 925	N/A
Length	149.4 / 3795			CVT	2073 / 940	2095 / 950	2117 / 960
Width	65.6 / 1665			WHEELS & TIRES			
Height	59.4 / 1510			Type	Steel	Alloy	
Front Tread Width	56.3 / 1430			Size	14 in.		15 in.
Rear Tread Width	55.7 / 1415			Tires	165/65R14		175/55R15
Min. Ground Clearance	6.3 / 160			Spare	T115/70D14 88M		
INTERIOR DIMENSIONS (cu. ft)				FUEL TANK CAPACITY (gal / L)			
SAE Interior Volume	103.3			9.2 / 35			
Passenger Volume	86.1			EPA FUEL ECONOMY (MPG)			
Cargo Area (Rear Seats Up / Down)	17.2 / 47.0				City	Hwy	Comb.
PASSENGER SPACE (in. / mm)		Front	Rear	CVT	37	43	39
Passenger Seating Capacity	5			5 M/T	33	41	36
Head Room	39.1 / 992	37.3 / 946					
Shoulder Room	51.7 / 1314	51.0 / 1296					
Hip Room	48.9 / 1240	46.4 / 1179					
Leg Room	41.7 / 1058	34.0 / 864					
* WARRANTIES		Basic	Powertrain	Anti-corrosion	Emissions	Roadside	
Years	5	10	7	See Warranty Statement	5		
Miles	60,000	100,000	100,000		Unlimited		
* U.S. coverage shown. Coverage may vary according to terms in effect at the time of purchase.							