



GROUP SST	MODEL 2017MY Sportage (QL)
NUMBER 044 (Rev 1 Revised 7/25/16)	DATE July 2016

TECHNICAL SERVICE BULLETIN

SUBJECT: R1234YF OIL AND DYE INJECTORS

* NOTICE

This bulletin has been revised to include additional information. New/revised sections of this bulletin are indicated by a black bar in the margin area.

Using fluorescent leak detection dye in vehicle's A/C system could aid in locating refrigerant leaks. R1234yf A/C systems Oil and Dye Injector Kits are available through Snap-On Business Solutions.

Tips for Use

- Follow instructions included with the Oil/Dye Injector Kit
- Ensure that the oil and dye is compatible with the R1234yf system being serviced
- Avoid overfilling the Injector chamber and remove all air from the injector hose
- Attach the injector coupler to the vehicle's low side port
- UV Leak Detection Lamp is required in conjunction with the LD-2 Arctic Pro Leak Detector
- The vehicle's A/C system must be running to circulate dye throughout the system
- Dye needs time to penetrate all the A/C systems lines and components
- Avoid checking the A/C system immediately after adding dye

Where to Order	Phone	Website
Snap-On Business Solutions	(888) 542-1011	www.KiaSpecialTools.com


File Under: <SST>

Circulate To: General Manager Service Manager Parts Manager
 Service Advisors Technicians Body Shop Manager Fleet Repair

SUBJECT:

R1234YF OIL AND DYE INJECTORS

Note: Although there are 2 parts listed below, only 1 is to be used.

Part Number	Description	Image
AIR90023	Large Oil Injector for R1234yf with 5 inch hose and quick connector	
ACT53135	R1234yf Refill Dye/Oil Injector	