



Countries:
Availability:
Major System: ELECTRICAL SYSTEM
Current Language: English
Other Languages: NONE
Viewed: 60

Document ID: IK0800525
Revision: 0
Created: 7/5/2016
Last Modified: 7/5/2016
Author: Andrew Boyd

[Less Info](#)

Hide Details

Coding Information

Copy Link 	Copy Relative Link 	Bookmark View My Bookmarks	Add to Favorites 	Print 	Edit Document 	Provide Feedback 	Helpful 0	Not Helpful 0
----------------------	-------------------------------	--	-----------------------------	------------------	--------------------------	-----------------------------	-------------------------	-----------------------------

Title: Cube fuse installation after maintenance

Applies To: Prostar with 0008WSP

CHANGE LOG

Please refer to the change log text box below for recent changes to this article:

07/05/2016 - Initial Article Release

DESCRIPTION

This document will guide the user through correct positioning the Cube Fuse Holder after regular maintenance.

SYMPTOM(s)

Not Applicable

SPECIAL TOOL(s) / SOFTWARE

Not Applicable

Tool Description	Tool Number	Comments	Instructions

[Tools Resource Center](#)

SERVICE PARTS INFORMATION

Not Applicable

Kit Description	Part Number	Quantity Required	Notes
Match Description to Parts Catalog			

DIAGNOSTIC STEP(s)

When performing maintenance on Prostars with 0008WSP you will notice the Cube Fuse Holder orientation to be incorrect as shown below.



This must be corrected when reinstalling the Cube Fuse Holder to the following: **Cab feed cable must be at a 90 degree angle to the Cube Fuse Holder, while the Cube Fuse Holder must be parallel to the front wall of the battery box.**

Nut for cube fuse holder and other cables on battery post: **16-20 N-M**

Nut for feed cable & cube fuse on cube fuse holder: **12NM +/- 1NM**

WARRANTY INFORMATION

Not Applicable

Group:	xxxxx - Description
Noun:	xxx - Description

Description	Chassis	Engine	SRT
CALIBRATE (MAF) SENSOR, PERFORM	All	MaxxForce 7 (2010-2013 Emissions)	A12-6171X
ACCESSORY DRIVE BELT (SERPENTINE), REPLACE	BE/CE	MaxxForce 7 (2010-2013 Emissions)	G12-3001J
ACCESSORY DRIVE BELT (SERPENTINE), REPLACE	4100	MaxxForce 7 (2010-2013 Emissions)	J12-3001J
ACCESSORY DRIVE BELT (SERPENTINE), REPLACE	4300 M7	MaxxForce 7 (2010-2013 Emissions)	K12-3001J
ACCESSORY DRIVE BELT (SERPENTINE), REPLACE	A/E Bus	MaxxForce 7 (2010-2013 Emissions)	TG12-3945X
ACCESSORY DRIVE BELT (SERPENTINE), REPLACE	TerraStar	MaxxForce 7 (2010-2013 Emissions)	TS12-3945X
With Air Compressor	All	MaxxForce 7 (2010-2013 Emissions)	A12-600-1
ON-BOARD FILTER CLEANLINESS TEST, PERFORM	All	MaxxForce 7 (2010-2013 Emissions)	A12-2235A

SRT Table:

Step	Repair	Model	Engine	SRT

Not Applicable

OTHER RESOURCES

[Master Service Information Site](#)

Hide Details

Feedback Information

Viewed: 59
 Helpful: 0
 Not Helpful: 0

No Feedback Found