Vehicle (Sales Code)	<b>Engine Oil</b> approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
<b>A6</b> FWD (4GC58G)	2.0L TFSI 252 hp (CYNB) 4.7L (5.0 qt)	7-Spd S-tronic (0CK) <u>Automatic</u>	Front F/Drive New Fill: 1.1L (1.2qt)	NA	10.0L (10.5 qt)***	1.0 L (1.1qt) (approximately) <u>VW Brake Fluid</u>	Refrigerant   Use only R134a   570 ± 20g   (20.1 ± 0.7 oz.)	w/o headlight wash 3.5L (3.7 qt.)
	Audi Oil Spec** VW 502 00** Use synthetic oil SAE 5W-40,	3.5L (3.6 qt) <u>Oil PN</u> G 055 529 A2	<u>Oil PN</u> G 055 190 A2*			Specification: Use new fluid only.	<u>Refrigerant Oil</u> Use a PAG oil with R134a	with headligh wash 4.9L (5.2 qt.)
	SAE 5W-30 or SAE 0W-40	<u>Manual:</u> 3.8L (4.0 qt) <u>Oil PN</u> G 052 549 A2				FMVSS 116 DOT 4 or SAE J 1703	Oil PN & Capacity For Denso use:	<u>Fluid PN</u> G 052 164*
A6 quattro (4GC58A)		8-Spd Tiptronic (OBK)	Front F/Drive <u>New Fill:</u> 1.0L (1.0 qt.)	Transfer Case <u>New Fill:</u> 1.0L (1.0 qt.)	10.0L (10.5 qt)***	<u>Fluid PN</u> B 000 750*	$120 \text{ cc} \pm 10 \text{ cc}$ (4.0 ± 0.3 fl. oz.) G 052 300 A2*	
		<u>New Fill:</u> 8.6L (9.0 qt)	<u>Refill:</u> 0.9L (1.0 qt.)	<u>Refill:</u> 0.85L (0.9 qt.)			0.002 300 A2	
		<u>Refill:</u> 3.6-4.0L (3.8-4.2 qt.)	<u>Oil PN</u> G 052 145 A2*	<u>Oil PN</u> G 055 145 A2				
		<u>Oil PN</u> G 060 162A2*		Rear F/Drive (0BC/OBD) 0.9L (1.0 qt)				
				<u>Oil PN</u> G 052 145 S2*				

0000

\*\*Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.

© 2016 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

## A6 - 2017 FLUID CAPACITY CHART 22 July 2016

Truth in Engineering



<b>Vehicle</b> (Sales Code)	<b>Engine Oil</b> approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
A6 quattro (4GC52A)	3.0L TFSI 333 hp (CREC) 340 hp (CREH)	8-Spd Tiptronic (OBK)	Front F/Drive <u>New Fill:</u> 1.0L (1.0 qt.)	Transfer Case <u>New Fill:</u> 1.0L (1.0 qt.)	12.0L (12.7 qt)***	1.0 L (1.1qt) (approximately)	<u>Refrigerant</u> Use only R134a 570 ± 20g (20.1 ± 0.7 oz.)	w/o headlight wash 3.5L (3.7 qt.)
Sedan (4GC53A) Competition	6.8L (7.2 qt.) <u>Audi Oil Spec**:</u> VW 502 00**	<u>New Fill:</u> 8.6L (9.0 qt) <u>Refill:</u>	<u>Refill:</u> 0.9L (1.0 qt.) <u>Oil PN</u>	<u>Refill:</u> 0.85L (0.9 qt.) <u>Oil PN</u>		VW Brake Fluid Specification: Use new fluid only.		with headlight wash 4.9L (5.2 qt.)
	Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	3.6-4.0L (3.8-4.2 qt.) <u>Oil PN</u> G 060 162 A2*	G 052 145 A2*	G 055 145 A2 Rear F/Drive (0BC/OBF)		FMVSS 116 DOT 4 or SAE J 1703	<u>Refrigerant Oil</u> Use a PAG oil with R134a	Fluid PN G 052 164*
		G 060 162 A2		0.9L (1.0 qt) <u>Oil PN: Gear Oil</u> G 052 145 S2*		<u>Fluid PN</u> B 000 750*	Oil PN & Capacity For Denso use: 120 cc ± 10 cc	
				0.85L (0.9 qt.) <u>Oil PN: ATF</u> G 055 515 A2*			(4.0 ± 0.3 fl. oz.) G 052 300 A2*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.

© 2016 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

## S6 - 2017 FLUID CAPACITY CHART 22 July 2016

Truth in Engineering

Audi

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
<b>S6</b> quattro (4GC5FY)	4.0L TFSI 450 hp (CTGE) 8.7L (9.2 qt.)	7-Spd S-tronic (0B5) Automatic	Front F/Drive <u>New Fill:</u> 1.0L (1.0 qt.)	Transfer Case <u>New Fill:</u> 4.35L (4.5 qt.)	15.0L (15.8 qt)***	1.0 L (1.1qt) (approximately)	Refrigerant Use only R134a 570 ± 20g (20.1 ± 0.7 oz.)	w/o headlight wash 3.5L (3.7 qt.)
Sedan	Audi Oil Spec: VW 502 00** Use synthetic oil	<u>Initial</u> 7.0 – 7.5 L (7.3 – 7.9 qt.)	<u>Refill:</u> 0.9L (1.0 qt.) Oil PN	<u>Oil PN</u> G 055 532 A2 <b>Rear F/Drive</b>		<u>VW Brake Fluid</u> <u>Specification:</u> Use new fluid only.		with headlight wash 4.9L (5.2 qt.)
	SAE 5W-40, SAE 5W-30 or SAE 0W-40	<u>Change:</u> 5.5 - 6.0 L (5.8 - 6.3 qt.) <u>Oil PN</u>	G 052 145 A2*	(0BC/OBF) 0.9L (1.0 qt.) <u>Oil PN: Gear Oil</u>		FMVSS 116 DOT 4 or SAE J 1703	<u>Refrigerant Oil</u> Use a PAG oil with R134a	<u>Fluid PN</u> G 052 164*
		G 052 529 A2 <u>Manual</u> 4.3L (4.5 qt.) <u>Oil PN</u> G 055 532 A2		G 052 145 S2* 0.85L (0.9 qt.) <u>Oil PN: ATF</u> G 055 515 A2*		<u>Fluid PN</u> B 000 750*	<u>Oil PN &amp; Capacity</u> For Denso use: 120 cc ± 10 cc (4.0 ± 0.3 fl. oz.)	
							G 052 300 A2*	

\*\*\* Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.

© 2016 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.