



HYUNDAI | NEW THINKING.
NEW POSSIBILITIES.

Technical Service Bulletin

GROUP CAMPAIGN	NUMBER 17-01-014
DATE FEBRUARY 2017	MODEL(S) Sonata Hybrid (YF HEV)

SUBJECT: SONATA HYBRID (YF HEV) UNDERBODY CORROSION PREVENTATIVE SERVICE
(SERVICE CAMPAIGN 943)

This bulletin supersedes TSB 15-01-047 to specify cavity wax application directions and duration.

* IMPORTANT

*** Retail Vehicles Only ***

Dealers must perform this Service Campaign on all affected vehicles whenever an affected vehicle is in the shop for any maintenance or repair.

When a vehicle arrives at the Service Department, access Hyundai Motor America's "Warranty Vehicle Information" screen via WEBDCS to identify open Campaigns.

Description: In some areas, a vehicle's underbody may exhibit corrosion due to road salt usage. As a precautionary measure, cavity wax coating is applied to the internal surfaces of underbody components, and an undercoating spray is applied to the bottom exterior surfaces of specified underbody components. This bulletin describes the procedure to perform this preventative service on certain Sonata Hybrid (YF HEV) vehicles.



Applicable Vehicles:

VERIFY THAT THE VEHICLE IS IDENTIFIED AS AFFECTED BY THE SERVICE CAMPAIGN VIA WEBDCS.

- Models:** 2011-2015MY Sonata Hybrid (YF HEV)
- Production Date Range:** From SOP to September 4, 2014.
- Areas:** Connecticut, Delaware, Illinois, Indiana, Iowa, Maine, Maryland, Massachusetts, Michigan, Minnesota, Missouri, New Hampshire, New Jersey, New York, Ohio, Pennsylvania, Rhode Island, Vermont, West Virginia, Wisconsin, and the District of Columbia

Circulate To: General Manager, Service Manager, Parts Manager, Warranty Manager, Service Advisors, Technicians, Body Shop Manager, Fleet Repair

★ IMPORTANT




There are circumstances under which vehicles that are not currently registered or have never been registered in a “salt belt” state may be eligible for this Campaign. These circumstances include:




Vehicles that have relocated into a “salt belt” area and/or vehicles registered in a “non-salt belt” state and driven in a “salt belt” area. If it is determined that an owner of a vehicle within the affected VIN production date range relocates or has operated their vehicle in a “salt belt” area, the dealer should perform the campaign procedure. The dealer should perform this procedure at no cost to the customer, and the Hyundai Warranty PA Center must be contacted prior to repair and submission of Warranty Claim.

★ NOTE




If the owner of a vehicle within the affected VIN production date range requests an undercarriage inspection of their vehicle, the inspection should be performed at no charge to the customer.

Parts Information:

Part Name	Image / Part Number	Remark
Cavity Wax		Use about half a can per vehicle.
	00232-19034	
Undercoat Spray		Use about 1 can per vehicle.
	00232-19035	
Wax Spray Gun		Regulate air pressure to <u>70 psi</u> . <i>If wax output is slow</i> , prime the gun by blocking the nozzle with a rag, and spraying the gun until the flow of wax increases.
	00232-19036	

<p>“Inside” Nozzle</p>	 <p>50mm</p>	<p>This is a newly developed nozzle that has an improved wax application spray pattern.</p>  <p>The pink tubing is to signal the user to stop spraying when pulling the nozzle out.</p> <p><u>This nozzle must be used for this service procedure.</u></p>
	<p>09624-2H101-QQH</p>	<p>This nozzle is supplied with the wax gun.</p>
<p>“Outside” Nozzle</p>		<p>This nozzle is supplied with the wax gun.</p>

Tools & Equipment Required:

Tool Name	Image	Remark
<p>Air Nozzle</p>		
<p>Goggles</p>		<p>NOTICE</p> <p>Wear protective goggles and respiratory protection when performing the procedures in this bulletin.</p> <p>This procedure should be performed in a well-ventilated area.</p>
<p>Mask</p>		

Mallet		
Wire Brush		
Plastic bags		Trash bags large enough to cover wheel/tire assemblies.

Warranty Information:

Model	Op. Code	Operation	Op. Time	Causal Part	Nature	Cause
YF HEV	50C069R0	APPLYING CAVITY WAX & BLACK UNDER COAT TO THE UNDERBODY	0.7 M/H	55405-3V100	A12	ZZ2

NOTE 1: Submit Claim on Campaign Claim Entry Screen.

NOTE 2: Each labor operation will reimburse applicable undercoating and cavity wax in sublet.

NOTE 3: If a part is found in need of replacement while performing this TSB and the affected part is still under warranty, please submit a separate claim using the same Repair Order.

If the affected part is out of warranty, submit a Prior Approval Request for goodwill consideration prior to performing the work.



Wear protective goggles and respiratory protection when performing the procedures in this bulletin. The vehicle should be in a well-ventilated area.

Service Procedure Notes:

1. When applying the cavity wax, the floor might be contaminated due to the cavity wax. It is recommended to put a plastic vinyl sheet on the floor before applying wax.



Wax gun preparation:

- 2a. Remove the compression fitting from the nozzle assembly that originally comes with the wax gun by unscrewing the nut, then removing the fitting from the tube.



2b. Attach the compression fitting to the tubing on the new nozzle assembly.



2c. Fill wax gun reservoir with cavity wax.

Prime the wax gun by spraying into a trash bag (or similar) until a light mist is visibly coming out of the nozzle.

NOTICE

Air supply pressure must be set to 70 psi.



NOTICE

If volume of wax coming out of the nozzle slows significantly (so that a light mist is no longer visible), prime the gun again.

It may speed the priming process to block the nozzle with a rag while spraying the gun until the flow of wax increases.



Service Procedure #1: Hammering and Air Blowing to Remove Debris


CAUTION

Wear protective goggles and respiratory protection when performing the procedures in this bulletin. The vehicle should be in a well-ventilated area.

1. Lift the vehicle on a hoist.



2. There are two types of front cross members, A-type and B-type. The area for hammering , debris removal, applying the cavity wax and black undercoat is different for each type.




2. Lightly tap the vehicle underbody with a 16 oz. hammer to loosen debris and the PVC coating in the following locations:

Cross member (A-type)




3. Cross member (B-type)




4. Front lower control arms

NOTICE

If the vehicle has front lower control arms made of aluminum, no service procedure is required on the front lower control arms.




5. Rear cross member and lower control arms





- 6. Remove the remaining debris by inserting an air nozzle into the locations shown, then blowing air in multiple directions.

Front cross member and lower control arms (A-type)



- 7. Front cross member and lower control arms (B-type)




- 8. Rear cross member




9. Rear lower control arms

NOTICE


If the vehicle has rear lower control arms made of aluminum, no service procedure is required on the rear lower control arms.



10. Rear upper control arms

**Service Procedure #2: Preparation for Cavity Wax and Undercoating Spray**

1. Clean the brake banjo bolt surfaces at all 4 calipers using a wire brush.



2. Wrap the brake assemblies with plastic bags to protect them from overspray. Use tape to secure the plastic in place. Leave the banjo fitting area exposed, as shown.



3. Wrap large plastic bags around the wheel/tire/brake assemblies to protect them from overspray. Use tape to secure the plastic in place.



4. Wrap the exhaust areas adjacent to the front and rear cross members with plastic bags to protect them from overspray. Use tape to secure the plastic in place.

NOTICE

The exhaust must be sufficiently cooled before it is wrapped.



Exhaust near front cross member



Exhaust near rear cross member

Service Procedure #3: Applying the Cavity Wax

⚠ CAUTION

Wear protective goggles and respiratory protection when performing the procedures in this bulletin. The vehicle should be in a well-ventilated area.

1. Apply the cavity wax at each of the locations noted in the following steps.

Generally for coating interior surfaces, insert the “inside” nozzle as deeply as possible at each point of entry. Spray the cavity wax while simultaneously rotating the nozzle, and slowly pulling the nozzle out. Continue this rotating/pulling motion until the pink tubing is seen coming out of the opening. The pink tubing indicates there is about 50mm of tubing left until the end of the nozzle. Stop spraying when the pink tubing is seen.


Insert the nozzle through the marked location in multiple directions and for the prescribed duration indicated in each step. The duration is for the total time for each marked location.

Generally for coating exterior surfaces, use the “outside” nozzle, provided with the wax gun.


- 2a. Refer to the photos on the right for the marked locations.

Front cross member (A-type) – Interior surfaces (using “inside” nozzle)

- Four (4) locations
- 15 seconds each




- 2b. Front cross member (A-type) – Interior surfaces (using “outside” nozzle)
- Four (4) locations
 - 15 seconds each




- 2c. Front lower control arms (A-type) – Interior surfaces (using “inside” nozzle)
- One (1) location each arm
 - 7 seconds each

NOTICE

If the vehicle has front lower control arms made of aluminum, no service procedure is required on the front lower control arms.





- 3a. Front cross member (B-type) – Interior surfaces (using “inside” nozzle)
- Four (4) locations
 - 10 seconds each



- 3b. Front lower control arms (B-type) – Interior surfaces (using “inside” nozzle)
 - Two (2) locations each arm
 - 7 seconds each




- 4. Rear cross member – Interior surfaces (using “inside” nozzle)
 - Five (5) locations
 - 15 seconds each



5 Other side of rear cross member

- 5. Rear lower control arms – Interior surfaces (using “inside” nozzle)
 - Three (3) locations each arm
 - 7 seconds each




NOTICE


If the vehicle has front lower control arms made of aluminum, no service procedure is required on the front lower control arms.



6. Rear upper control arms – Interior surfaces but using the “outside” nozzle because the opening is too small for the “inside” nozzle.
- Four (4) locations each arm
 - 7 seconds each



7. Wipe off the excess wax that may have flowed out.





Service Procedure #4: Applying the Undercoating Spray

CAUTION

Wear protective goggles and respiratory protection when performing the procedures in this bulletin. The vehicle should be in a well-ventilated area.

1. Spray the black undercoating on all exterior surfaces of the front and rear cross members, lower arms, rear upper arms, front and rear brake hose mounting points, and the fuel & brake tubes. Refer to the following procedures and images.

2. Front cross member.



3. Front lower control arms.

NOTICE

If the vehicle has front lower control arms made of aluminum, no service procedure is required on the front lower control arms.



4. Rear cross member.



- 5. Rear lower control arms.

NOTICE


If the vehicle has rear lower control arms made of aluminum, no service procedure is required on the rear lower control arms.




- 6. Rear upper control arms.



- 7. Front and rear brake banjo fittings and mounting brackets.



8. Fuel and brake lines.
- Remove the underbody panel to expose brake and fuel lines, apply the undercoating spray, then re-install the underbody panel.



9. Remove all the plastic bags to complete the procedure.