



Technical Service Bulletin

SUBJECT: TECHNICAL SPECIFICATIONS – 2018 MIRAGE			No: TSB-17-00-003
			DATE: August 2017
			MODEL: 2018 Mirage
CIRCULATE TO:	<input type="checkbox"/> GENERAL MANAGER	<input checked="" type="checkbox"/> PARTS MANAGER	<input checked="" type="checkbox"/> TECHNICIAN
<input checked="" type="checkbox"/> SERVICE ADVISOR	<input checked="" type="checkbox"/> SERVICE MANAGER	<input checked="" type="checkbox"/> WARRANTY PROCESSOR	<input checked="" type="checkbox"/> SALES MANAGER

2018 MIRAGE

ENGINE		ES / SE / GT		TRANSMISSION RATIOS			
Type	1.2L DOHC, 12-valve Inline 3 cyl.			MT			
Engine Code	3A92			CVT			
Engine Block/Cylinder Head	Aluminum / Aluminum			Gear	4.007 ~ 0.550		
Displacement (cu. in. / cc)	72.8 / 1193			1 st	3.545	N/A	
Bore x Stroke (in. / mm)	2.95 x 3.54 / (75.0 x 90.0)			2 nd	1.913	N/A	
Compression Ratio	10.5:1			3 rd	1.310	N/A	
Valve Train	DOHC Mitsubishi Innovative Valve-timing Electronic Control			4 th	0.973	N/A	
Horsepower @ RPM (BHP)	78 @ 6,000			5 th	0.804	N/A	
Torque @ RPM (lb-ft)	74 @ 4,000			Reverse	3.214	3.771	
Redline	6,500 RPM			Final Drive	4.055	3.757	
Fuel System	Electronically Controlled Multi-point Fuel Injection			RACK & PINION POWER ASSIST STEERING			
Engine Oil Capacity (w/o filter)	2.96 Qts / 2.8 L			Electric Power Steering			
Engine Oil Type	0W-20 (API Service Standard SN / ILSAC certification oil)			Turning Cir Wall - Wall	32.1 ft / 9.8 m		
SUSPENSION				Turning Cir Curb - Curb	30.2 ft / 9.2 m		
Front	Independent MacPherson strut suspension with coil springs and stabilizer bar			ELECTRICAL SYSTEM			
Rear	Torsion beam suspension with coil springs, shock absorbers			Battery	Group 55D23L / 356 (CCA)		
BRAKES (in. / mm)				Alternator	85 A		
Front Disc Diameter (Vented)	9.9 / 251			WEIGHTS (5MT / CVT)			
Rear Drum Inside Diameter	8.0 / 203			GVWR - 2910 / 3020 lbs (1320 / 1370 kg)			
Anti-Lock Brake System	4-wheel, 4-channel ASC with EBD			CURB WEIGHT (lbs / kg)			
EXTERIOR DIMENSIONS (in. / mm)							
Wheelbase	96.5 / 2450						
Length	149.4 / 3795						
Width	65.6 / 1665						
Height	59.4 / 1510						
Front Tread Width	56.3 / 1430						
Rear Tread Width	55.7 / 1415						
Min. Ground Clearance	6.3 / 160						
INTERIOR DIMENSIONS (cu. ft)							
SAE Interior Volume	103.3						
Passenger Volume	86.2						
Cargo Area (Rear Seats Up / Down)	17.2 / 47.0						
PASSENGER SPACE (in. / mm)							
	Front		Rear				
Passenger Seating Capacity	5						
Head Room	39.1 / 992	37.3 / 946					
Shoulder Room	51.7 / 1314	51.0 / 1296					
Hip Room	48.8 / 1240	46.4 / 1179					
Leg Room	41.7 / 1058	34.0 / 864					
* WARRANTIES							
	Basic	Powertrain	Anti-corrosion	Emissions	Roadside		
Years	5	10	7	See Warranty Statement	5		
Miles	60,000	100,000	100,000		Unlimited		
* U.S. coverage shown. Coverage may vary according to terms in effect at the time of purchase.							
				FUEL TANK CAPACITY (gal / L)			
				9.2 / 35			
				EPA FUEL ECONOMY (MPG)			
				City	Hwy	Comb.	
				CVT	37	43	39
				5 M/T	33	41	36

Copyright 2017, Mitsubishi Motors North America, Inc.

The information contained in this bulletin is subject to change. For the latest version of this document, go to the Mitsubishi Dealer Link, MEDIC, or the Mitsubishi Service Information website (www.mitsubishitechinfo.com) (4579)