



Technical Service Bulletin

SUBJECT:		No: TSB-17-00-005	
TECHNICAL SPECIFICATIONS – 2018 MIRAGE G4		DATE: August 2017	
		MODEL: 2018 Mirage G4	
CIRCULATE TO:	<input type="checkbox"/> GENERAL MANAGER	<input checked="" type="checkbox"/> PARTS MANAGER	<input checked="" type="checkbox"/> TECHNICIAN
<input checked="" type="checkbox"/> SERVICE ADVISOR	<input checked="" type="checkbox"/> SERVICE MANAGER	<input checked="" type="checkbox"/> WARRANTY PROCESSOR	<input checked="" type="checkbox"/> SALES MANAGER

2018 MIRAGE G4

ENGINE		ES / SE		TRANSMISSION RATIOS			
Type	1.2L DOHC, 12-valve Inline 3 cyl.			MT			
Engine Code	3A92			CVT			
Engine Block/Cylinder Head	Aluminum / Aluminum			Gear		4.007 ~ 0.550	
Displacement (cu. in. / cc)	72.8 / 1193			1 st	3.545	N/A	
Bore x Stroke (in. / mm)	2.95 x 3.54 / (75.0 x 90.0)			2 nd	1.913	N/A	
Compression Ratio	10.5:1			3 rd	1.310	N/A	
Valve Train	DOHC Mitsubishi Innovative Valve-timing Electronic Control			4 th	0.973	N/A	
Horsepower @ RPM (BHP)	78 @ 6,000			5 th	0.804	N/A	
Torque @ RPM (lb-ft)	74 @ 4,000			Reverse	3.214	3.771	
Redline	6,500 RPM			Final Drive	4.055	3.757	
Fuel System	Electronically Controlled Multi-point Fuel Injection			RACK & PINION POWER ASSIST STEERING			
Engine Oil Capacity (w/o filter)	2.96 Qts / 2.8 L			Electric Power Steering			
Engine Oil Type	0W-20 (API Service Standard SN / ILSAC certification oil)			Turning Cir Wall - Wall	33.5 ft / 10.2 m		
SUSPENSION				Turning Cir Curb - Curb	31.5 ft / 9.6 m		
Front	Independent MacPherson strut suspension with coil springs and stabilizer bar			ELECTRICAL SYSTEM			
Rear	Torsion beam suspension with coil springs, shock absorbers			Battery	Group 55D23L / 356 (CCA)		
BRAKES (in. / mm)				Alternator	85 A		
Front Disc Diameter (Vented)	9.9 / 251			WEIGHTS (5MT / CVT)			
Rear Drum Inside Diameter	8.0 / 203			GVWR - 3053 / 3108 lbs			
Anti-Lock Brake System	4-wheel, 4-channel ASC with EBD			(1385 / 1410 kg)			
EXTERIOR DIMENSIONS (in. / mm)				CURB WEIGHT (lbs / kg)			
Wheelbase	100.4 / 2550			ES			
Length	169.5 / 4305			SE			
Width	65.7 / 1670			5M/T	2106 / 955	N/A	
Height	59.2 / 1505			CVT	2172 / 985	2194 / 995	
Front Tread Width	56.9 / 1445			WHEELS & TIRES			
Rear Tread Width	56.3 / 1430			Type	Steel	Alloy	
Min. Ground Clearance	6.3 / 160			Size	14 in.	15 in.	
INTERIOR DIMENSIONS (cu. ft)				Tires	165/65R14	175/55R15	
SAE Interior Volume	101.8			Spare	T115/70D14 88M		
Passenger Volume	89.5			FUEL TANK CAPACITY (gal / L)			
Cargo Area	12.3			9.2 / 35			
PASSENGER SPACE (in. / mm)				EPA FUEL ECONOMY (MPG)			
		Front	Rear				
Passenger Seating Capacity	5						
Head Room	39.1 / 994	36.9 / 936					
Shoulder Room	51.7 / 1314	51.2 / 1300					
Hip Room	48.8 / 1240	48.2 / 1225					
Leg Room	41.7 / 1058	37.2 / 944					
* WARRANTIES							
Basic	Powertrain	Anti-corrosion	Emissions	Roadside			
Years	5	10	7	See Warranty Statement			
Miles	60,000	100,000	100,000	5			
				Unlimited			
* U.S. coverage shown. Coverage may vary according to terms in effect at the time of purchase.							
				City			
				Hwy			
				Comb.			
				CVT	35	42	37
				5 M/T	33	40	35

Copyright 2017, Mitsubishi Motors North America, Inc.

The information contained in this bulletin is subject to change. For the latest version of this document, go to the Mitsubishi Dealer Link, MEDIC, or the Mitsubishi Service Information website (www.mitsubishitechinfo.com) (4581)