

Technical Service Bulletin

SUBJECT:			No:	TSB-17-00-009	
TECHNI	DATE: August 2017				
2017 OUTL	MODEL: 2017 Outlander Sport				
CIRCULATE TO:	[] GENERAL MANAGER	[X] PARTS MANAGER		[X] TECHNICIAN	
[X] SERVICE ADVISOR	[X] SERVICE MANAGER	[] WARRANTY PROCESS	OR	[X] SALES MANAGER	

This bulletin supercedes TSB-16-00-013*, issued September 2016, to add completed "EPA FUEL ECONOMY" data and include LE model information. Revisions are italicized and indicated by* **4***.*

2017 OUTLANDER SPORT

ENGINE		ES / LE SE / SEL / GT		TRANSMISSION RATIOS					
Туре		2.0L MIVEC	inline-4	2.4L MIVEC inline-4		M/T	CVT (2.0)	CVT (2.4)	
Engine Code		4B11		4B12	CVT Mode	N/A	2.631-0.378	2.349-0.394	
Engine Block/0	Cylinder Head		Aluminum/Alun	hinum	1 st	3.833	2.631	2.349	
Displacement	(cu. in./cc)	122 / 1998		144 / 2360	2 nd	1.913	1.440	1.517	
Bore x Stroke		3.4 x 3.4 / 86.0 x 86.0		3.5 x 3.8 / 88 x 97	3 rd	1.333	1.165	1.105	
Compression F		10:1		10.5:1	4 th	1.028	0.906	0.857	
Horsepower @		148 bhp @		168 bhp @ 6000	5 th	0.820	0.680	0.621	
Torque @ RPM	netadi sed	145 lb/ft @		167 lb/ft @ 4100	6 th	N/A	0.499	0.446	
Valve Train		DOHC 16		-054000	Rev	3.583	1.960	1.750	
Redline		6500 RPM			Final Drive	4.235	6.026	6.466	
Fuel System		Electronically Controlled Multi-Point Fuel Injection			RACK &	PINION P	OWER ASSIST	STEERING	
	ity (w/o filter)	CVT: 4.5 qt. / 4.2 L			Type: Electric power assisted rack & pinion				
Engine Oil Capacity (w/o filter)	ity (w/o inter)	5MT: 4.2 gt		4.5 qt. / 4.3 L	Ratio				
Engine Oil Type		0W-20 Minimum: API Service Standard SN (ILSAC certification)			Turns Lock		3.3		
SUSPENSION		000-20 1011111111			Collection (34.8 / 10.6			
Front		Independent Mer	Turn. Cir C-C (ft/m) 34.8 / 10.6 ELECTRICAL SYSTEM						
Rear		Independent Mac							
BRAKES		Multi-link, coil springs, stabilizer bar			Battery		75D23L		
	Dias Diamatas	11.6" / 294 mm			Alterreter		520 CCA		
Frt. Ventilated	1940.000 JUL		Alternator 130 amp						
Rear Solid Dis			WEIGHTS (lbs / kg) GVWR (All) 4343 / 1970						
Total swept an			424			11)	transerites T		
Anti-Lock Brake System 4-sensor, 4-channel with EBD					Curb wt.		2WD	AWC	
EXTERIOR DIMENSIONS (in. / mm)					ES (CVT)		09 / 1410	3252 / 147	
Wheelbase		105.1 / 2670			ES (M/T)		32 / 1375	N/A	
Length		171.5 / 4356			LE/SE		09 / 1410	3252 / 147	
Width		71.3 / 1811			SEL	31	42 / 1425	3265 / 148	
Height		64.8 / 1646			GT		N/A 3285 / 149		
Front Tread W	Service 1		60.6 / 1		Weight Distribution				
Rear Tread Wi			60.6 / 1	539	CVT (M/T		60/40 (59/41) 59/41 (N/A)		
Min. Ground C			8.5 / 216			WHEELS & TIRES			
INTERIOR DIMENSIONS (cu. ft.)				Wheels	18 >	18 x 7 J Aluminum Alloy			
Interior Volume	Э		119.2 (117.3 w/panoramic roof)		Tires	P22	P225/55R 18 97H - NE>		
Passenger		97.5 (95.6 w/panoramic roof)		Spare Tire		T155/90D16			
Cargo capacity be	ehind frt. seat		49.5 (48.8 w/pan	oramic roof)	FUEL TANK CAPACITY (gal)		gal / L)		
Cargo capacity be	ehind rear seat	21.7 (20.1 w/subwoofer)		16.6 / 62	.8 (2WD)	(2WD) 15.8 / 59.8 (AWC)			
PASSENGER S	SPACE (in./mm)	Fro	ont	Rear	EPA FUEL ECONOMY (mpg)		mpg)		
Headroom (w/	panoramic roof)	39.4 / 1000	(38.9 / 988)	37.9 / 962.7 (36.8 / 934.7)		Ci	ty Hwy	Comb	
Shoulder Roor	n	56.2 /	1428	55.5 / 1410	ES 2WD (M/	T) 24 (23) 30 (29) 27 (25	
Hip Room		52.1 / 1323		51.6 / 1310	ES AWC	2	3 29	26	
Leg Room (MAX) 41.6 / 1056		36.3 / 921	LE 2WD	2	4 30	27			
Max. Passenger Capacity 5 passer		ngers	LE AWC	2	23 29				
WARRANTIES	- U.S. shown - 0	Coverage may var	according to terr	ns in effect at time of first sale.	SE 2WD	2	3 28	25	
	Basic	Powertrain	Anti-corrosio		SE AWC	2.	2 27	24	
Yrs	5	10	7	See individual statement	SEL 2WD	2	3 28	25	
Miles	60,000	100,000	100,000	for CA & Fed. coverage	SEL AWC	2	2 27	24	
				fect at the time of purchase	GTAWC	2	2 27	24	

Copyright 2017 Mitsubishi Motors North America, Inc.

The information contained in this bulletin is subject to change. For the latest version of this document, go to the Mitsubishi Dealer Link, MEDIC, or the Mitsubishi Service Information website (www.mitsubishitechinfo.com). (4600)