



Job Aid

September 2017

07076 Version 2

Indirect TPMS Calibration

AFFECTED VEHICLES

As a convenience, this job aid lets you selectively view the applicable calibration method(s) for any affected vehicle. To do this, select the vehicle from this drop-down menu.

Select Vehicle: YEAR | MODEL | TRIM

Click [HERE](#) to see a chart of all affected vehicles.

INTRODUCTION

Indirect TPMS, first introduced in the 2013 Accord, provides the same function as direct TPMS but does it differently. And because of that, it remains a source of confusion for both service techs and customers alike.

This job aid offers important guidance, along with some valuable tips, to help you better understand indirect TPMS.

Here is what it covers:

- A Few Basics
- Calibration
- Low Tire Pressure/TPMS Indicator Functions
- Troubleshooting Tips
- Calibration Comparison Logic and Special Calibration
- To Learn More
- Affected Vehicle Application Chart for Indirect TPMS

A FEW BASICS

Unlike a direct TPMS, an indirect TPMS **does not** use tire pressure sensors mounted in the tires. Instead, the system is integrated into the VSA modulator-control unit and uses the following inputs to monitor and compare tire characteristics while driving and determine when one or more tires are significantly underinflated.

- VSA/ABS wheel speed sensors
- Yaw and G sensor
- Brake pressure
- Steering angle
- Outside temperature (measured from the front bumper)

From these inputs, the system calculates tire pressures. To determine tire pressure loss, the system uses these two methods:

- **Wheel Speed Differential** - This method is used to detect if one, two, or three tires have lost pressure. It compares the **two** left tires to the two **right** tires, the two **front** tires to the two **rear** tires, and the **left front** and **right rear** tires to the **left rear** and **right front** tires.
- **Peak Tire Resonance** - This method is used to detect if all four tires have lost pressure. A good example: if the tire pressures have not been checked for over 9 months.

An easy way to tell which type of TPMS a vehicle has is by looking at the valve stems. Vehicles with **indirect** TPMS have **black rubber** valve stems. Vehicles with **direct** TPMS have **gray alloy** valve stems.

CALIBRATION

In order to calculate tire pressures, the system must first be calibrated. The system relies on the tire pressures being set to the cold inflation values listed on the driver's doorjamb label and the calibration process started. This process must be done at PDI, and also at scheduled maintenance and anytime you do the following:

- Adjust pressure in one or more tires
- Rotate tires
- Replace one or more tires

Keep in mind if the Low Tire Pressure/TPMS indicator is **not** on, you just need to **start** the process; the system will finish it on its own as the customer drives the vehicle.

If the tire pressures are not properly set and/or the calibration process is not started at the right time, the tire pressure calculations are tricked, causing the Low Tire Pressure/TPMS indicator to possibly come on, resulting in a possible customer comeback and wasted troubleshooting time.

Starting calibration is very easy. Here is how it is done. You will also find these procedures in the PDI bulletins, owner's guides, owner's manuals, and service information.

Before You Start

1. Make sure the vehicle is completely stopped with the transmission in Neutral (M/T) or Park (A/T or CVT).
2. Make sure all of the tires are the same type and size. The system will not work right otherwise.
3. Set the tire pressures to the cold inflation values listed on the driver's doorjamb label.
4. Turn the ignition to ON.

NOTE: The following steps vary, depending on the vehicle and how it is equipped.

TPMS Button Method

Starting Calibration

Procedure: Press and hold the TPMS button underneath the left side of the dashboard until the Low Tire Pressure/TPMS indicator blinks **twice**.



TPMS Button Special Method

Starting Special Calibration

Procedure: Press and hold the TPMS button until the Low Tire Pressure/TPMS indicator blinks **twice**. Wait **5 seconds**, then press and hold the button until the indicator blinks twice. Wait **5 more seconds**, then press and hold the button until the indicator blinks twice. Within **10 seconds**, the indicator blinks once, letting you know that special calibration has started.

Display Audio Method

Starting Calibration

Procedure: Select **HOME**, **Settings**, **Vehicle**, **TPMS Calibration**, then **Calibrate**.

Display Audio Special Method

Starting Special Calibration

Procedure: Select **HOME**, **Settings**, **Vehicle**, **TPMS Calibration**, then **Calibrate**. Wait **5 seconds**, then select **TPMS Calibration** and **Calibrate**. Wait **5 more seconds**, then select **TPMS Calibration** and **Calibrate**. Within **10 seconds**, the indicator blinks **once**, letting you know that special calibration has started..

MID/i-MID/Driver Information Interface Method

Starting Calibration

Procedure: Using the steering wheel buttons, select **Settings** or **Menu**, **TPMS Calibration**, then **Calibrate** or **Initialize**.

Calibration Status.

During calibration, if you cycle the ignition, and the vehicle is not moved within **45 seconds**, the Low Tire Pressure/TPMS indicator will come on for **2 seconds**. This is normal and simply means that calibration has not yet completed.

MID/i-MID/Driver Information Interface Special Method

Starting Calibration

Procedure: Using the steering wheel buttons, select **Settings** or **Menu**, **TPMS Calibration**, then **Calibrate** or **Initialize**. Wait **5 more seconds**, then select **TPMS Calibration** and **Calibrate** or **Initialize**. Wait **5 more seconds**, then select **TPMS Calibration** and **Calibrate** or **Initialize**. Within **10 seconds**, the indicator blinks once, letting you know that special calibration has started.

CALIBRATION COMPARISON LOGIC AND SPECIAL CALIBRATION

Whenever calibration is started, the TPMS control unit learns the tire characteristics during the calibration drive. Should those characteristics change for any reason from what it has learned (for

example, there is a sudden drop in tire pressure), the Low Tire Pressure/TPMS indicator comes on as a reminder to check the tire pressures.

If the tire pressures are properly set and calibration is started, the indicator goes off, the control unit learns the proper tire characteristics during the calibration drive, and all is well. But what if **nothing** is done about the tire pressures, but calibration is started? The indicator will still go off, but now something called **calibration comparison logic** steps in.

The control unit then compares the tire characteristics that caused the indicator to come on to the tire characteristics during the calibration drive. If the control unit sees that there has been **no change** in tire characteristics, the indicator comes on again **within 20 minutes** as a reminder to check the tire pressures.

It is not uncommon for customers to experience this situation and, when they do, they are often confused and think there is something wrong with the TPMS and end up back at their dealership. Here are two ways this can happen:

Scenario 1

*At PDI, the tire pressures are not checked and they remain at their high-pressure values for shipping. The vehicle is delivered to the customer, and the control unit learns the tire characteristics at high pressure. Sometime later, the pressures are lowered to the recommended values but for some reason, calibration is **not** started. The control unit sees there is a **change** in tire characteristics and the Low Tire Pressure/TPMS indicator comes on. The customer, knowing the tire pressures were **already** set to the recommended values, just starts calibration. The control unit's calibration comparison logic sees there is **no change** in tire characteristics since the last calibration, and the indicator comes on **again** within 20 minutes.*

Scenario 2

*The Low Tire Pressure/TPMS indicator comes on while driving. The customer, not wanting to stop and check tire pressures, starts calibration knowing it will turn off the indicator. The control unit's calibration comparison logic sees there is **no change** in tire characteristics since the last calibration and the indicator comes on **again** within 20 minutes.*

The truth is both of these scenarios can easily be avoided: the first one by just remembering to set the tire pressures and start calibration at PDI, the second one by simply heeding the indicator and taking proper action (setting the tire pressures and starting calibration).

*To clear all learned tire pressures and avoid calibration comparison logic activity, there is a **special calibration**, which has you start the normal calibration three times in a row, waiting **5 seconds** between each start. After the third start, the Low Tire Pressure/TPMS indicator blinks **once**, letting you know the special calibration has started. There is no need for a calibration drive after each start.*

LOW TIRE PRESSURE/TPMS INDICATOR FUNCTIONS

The Low Tire Pressure/TPMS indicator does a variety of things, depending on conditions and circumstances.



Normal Conditions

- The indicator comes on for a few seconds when you turn the ignition to ON. This is just part of the system check.
- The indicator comes on for **2 seconds**, then goes off, if the vehicle is not moved within **45 seconds** after turning the ignition to ON. This just means the system is still calibrating.

Abnormal Conditions

- The indicator comes on and stays on if one or more tire pressures are very low or the system has not been calibrated. If this happens, the vehicle should be stopped in a safe place, the tire pressures checked and adjusted as needed, and the calibration process started.
- The indicator blinks for about **1 minute**, then stays on if the compact spare tire is mounted or there is a problem with the TPMS.
If the spare is mounted, the regular tire should be repaired or replaced and mounted as soon as possible, and the calibration process started. If the spare is not mounted, the calibration process should be started and the system checked.

TROUBLESHOOTING TIPS

If the Low Tire Pressure/TPMS indicator is on steady, here are a few tips to help you troubleshoot.

- Check cold tire pressures. A cold tire means the vehicle has been parked for at least **3 hours** or driven less than **1 mile**. Be sure to use an accurate tire pressure gauge (P/N 07AAJ-000-A100)
- If you find a low tire, repair or replace it, then set the tire pressure to the recommended cold inflation value and start the calibration process. You **do not** need to finish calibration.

- If the tire pressures are OK, check that the wheels and tires are the OEM size, make, and model and that they are not damaged in any way. Then, check if the vehicle was recently serviced within or outside a Honda dealer. If a tire was recently replaced, and its tread depth is different from the other tires, the Low Tire Pressure/TPMS indicator could be triggered.
- If all of the vehicle's tires are worn, it is best to replace them together. If that is not possible, then replace the front pair or the rear pair.
- If you suspect that calibration was not done at a recent service, you can find out for sure by connecting the i-HDS and checking the **INITIALIZED ODOMETER** signal in the **VSA Data List**. In the case below, calibration was not started at PDI.

CRUISE CANCEL CLUTCH SWITCH STATUS	OFF	
NEUTRAL SWITCH STATUS	N/A	
OUTSIDE TEMPERATURE	100.4	°F
INITIALIZED ODOMETER	0	mile

TO LEARN MORE

To learn more about the material covered in this job aid, check out these resources:

- Online University Self-Study Module SSC16, *Indirect Tire Pressure Monitoring System*
- Tech2Tech® Video [“TPMS Identification and Calibration”](#)

We have also produced and posted these five videos demonstrating the calibration process on the Honda YouTube Channel:

- [“Calibrating an Indirect Tire Pressure Monitoring System: Vehicles with TPMS Button”](#)
- [“Calibrating an Indirect Tire Pressure Monitoring System: Vehicles with MID”](#)
- [“Calibrating an Indirect Tire Pressure Monitoring System: Vehicles with i-MID”](#)
- [“Calibrating an Indirect Tire Pressure Monitoring System: Using Driver Information Interface”](#)
- [“Calibrating an Indirect Tire Pressure Monitoring System: Using Display Audio”](#)

AFFECTED VEHICLE APPLICATION CHART FOR INDIRECT TPMS

Year	Model	Trim	Calibration Method
2013–17	Accord	All Except Touring	TPMS Button

2013–17	Accord	Touring	MID/i-MID/Driver Information Interface Method
2014	Accord	Plug-in	MID/i-MID/Driver Information Interface Method
2014–15	Accord	Hybrid	MID/i-MID/Driver Information Interface Method
2017	Accord	Hybrid	MID/i-MID/Driver Information Interface Method
2014–15	Civic	All	MID/i-MID/Driver Information Interface Method
2016–17	Civic	LX w/o Honda Sensing	TPMS Button
2016–17	Civic	LX w/Honda Sensing	MID/i-MID/Driver Information Interface Method
2016–17	Civic	EX / Touring	Display Audio
2017	Civic	Sport	TPMS Button
2017	Civic	Sport Touring / Type R	Display Audio
2017	Clarity	All	Display Audio
2014–16	CR-V	All Except Touring	TPMS Button
2015–16	CR-V	Touring	MID/i-MID/Driver Information Interface Method
2017	CR-V	LX	TPMS Button
2017	CR-V	Except LX	Display Audio
2016	CR-Z	All	MID/i-MID/Driver Information Interface Method
2015–17	Fit	All	TPMS Button
2018	Fit	w/o Honda Sensing	TPMS Button
2018	Fit	w/Honda Sensing	MID/i-MID/Driver Information Interface Method

2016–17	HR-V	All	TPMS Button
---------	------	-----	-------------

