



2017 Passat



Engine	Part	Part Number	Quantity
1.8L Turbo: CPRA	Oil Filter	06K 115 562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30	N/A	5.5L (5.7qt)
	Drain Plug W/Gasket	N 911 679 01	1
	Air Filter	5C0 129 620	1

Engine	Part	Part Number	Quantity
2.0L Turbo: DDSA, DDSB	Oil Filter	06K 115 562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30	N/A	5.7L (6.0qt)
	Drain Plug W/Gasket	06L 103 801	1
	Air Filter	5C0 129 620 B	1

Engine	Part	Part Number	Quantity
3.6L VR6: CDVB	Oil Filter	03H 115 562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30	N/A	5.5L (5.8qt)
	Drain Plug W/Gasket	N 908 132 02	1
	Air Filter	1K0 129 620 B	1

Miscellaneous	Part	Part Number	Quantity
Miscellaneous	Pollen Filter (PR-KH6)	1K0 819 644 B	1
	Pollen Filter (PR-9AK)	1K1 819 653 B	1
	Wiper Blade – Left	561 955 425	1
	Wiper Blade – Right	561 955 426	1
	Battery (Amp. Req. Vary)	000 915 105 *	1

*VIN Required

2017 Passat Service Reminder Reset



Resetting the oil change service reminder

If the oil change service was not performed by a Volkswagen workshop, it can be reset as follows:

Vehicles with text messages:

1. Switch off the ignition.
 2. Press and hold down the **0.0/SET** button in the instrument cluster.
 3. Restart the ignition.
 4. Release the **0.0/SET** button.
 5. Confirm the query in the instrument cluster with the **OK** button on the multi-function steering wheel.
-

Vehicles without text messages:

1. Switch off the ignition.
 2. Press and hold down the **0.0/SET** button in the instrument cluster.
 3. Restart the ignition.
 4. Release the **0.0/SET** button and press the   button within approximately 20 seconds.
-

Do **not** reset the service reminder between service intervals; otherwise incorrect information will be displayed.

If you manually reset the service interval display while flexible oil change service is valid, the “fixed oil change service” will be activated. The service interval will no longer be calculated on an individual basis
⇒ Booklet *Service Schedule*.

Resetting inspection

If the inspection was not performed by a Volkswagen workshop, it can be reset as follows:

Vehicles with text messages:


1. Switch off the ignition.
 2. Switch on the hazard warning lights.
-


Vehicles with text messages:

3. Press and hold down the **0.0/SET** button in the instrument cluster.
 4. Restart the ignition.
 5. Release the **0.0/SET** button.
 6. Confirm the query in the instrument cluster with the **OK** button on the multi-function steering wheel.
 7. Switch off the hazard warning lights.
-

Vehicles without text messages:

1. Switch off the ignition.
 2. Switch on the hazard warning lights.
 3. Press and hold down the **0.0/SET** button in the instrument cluster.
 4. Restart the ignition.
 5. Release the **0.0/SET** button and press the **⏏/⌚** button within approximately 20 seconds.
 6. Switch off the hazard warning lights.
-

 The service message will go out after a few seconds when the engine is running or by pressing the **OK** button on the multi-function steering wheel.

 If the vehicle battery was disconnected for long periods in vehicles with flexible service, the system cannot calculate the time at which the next service is due. The service displays could then display incorrect information. If this is the case, please heed the maximum permissible service intervals listed in the ⇒ *Booklet Service Schedule*.

For current fluid capacity charts, please refer to the Maintenance section in Elsa.