



SERIES 5050 NO WELD SQUARE CORNER CAMPER DOOR

Frame Assembly

- Mechanically fastened outer frame creates a strong, sturdy assembly
- Extruded hinges, with stainless steel bushings and full-length pin, provide longer service life and sturdy core to frame connection
- Hinge system complies with DOT FMVSS 206 and CMVSS 206
- Built-in drip cap requires less labor at installation and sloped threshold provides better drainage
- Available in black, mill, silver or white finish

Core Assembly

- Smooth and embossed exterior skins available in a variety of popular colors
- Damage resistant fiberglass exterior and interior surfaces. Optional aluminum skin available
- Strong extruded aluminum core surround protects the core edge from damage
- Precambered lock side stile and adjustable strike plate ensure a positive seal
- Optional flush and safety locks are available

Screen Door Assembly

- Extruded aluminum screen door frame
- Screen door lever latch secures firmly to the primary door and frame

Sizes

- Call Widths: 22"-36" with screen door, 20"-48" without screen door
- Call Heights: 54"-80"
- Frame Depth: 2.098"
- Core Thickness: 1³/₈"
- Rough Opening Dimensions:
Call Width = Rough Opening Dimension
Call Height = Rough Opening Dimension
(Example: 28" x 76" Call Size - 28" x 76" Rough Opening)



Available Window Styles



1.) Radius Corner
Blank Door



2.) Radius Corner
12" x 21" Window

SERIES 5050 NO WELD SQUARE CORNER CAMPER DOOR



1. Door is precambered at manufacture for consistency.
2. Door does not require adjustment of camber at installation, saving time and money.
3. Door will "spring" to fit flat or convex walls.
4. Camber enhances weather tight seal.

Options

- Multiple window options are available upon request
- Smooth and embossed exterior skins available in a variety of popular colors
- Locks: Chrome or painted flush lock w/integral deadbolt
- Chrome or painted safety lock
- Cross bars on screen door
- Kick panel on screen door

Note: Some options and colors subject to availability and/or minimum order quantities

Continuous Hinge Pin
Adds strength to prevent door from sagging

Rubber Seal
Weather resistant compression seal reduces leakage and draft

Galvaneal Stile
Creates a tight seal for strength and durability

Hot Melt adhesive
Superior process maintains door integrity



ADVANCED DOOR SOLUTIONS FOR OVER 40 YEARS