



Technical Service Bulletin

DATE: 12/29/2017
NUMBER: 5JW-F596D-12
MODEL(S): EXA SPEEDLOADER

Subject: EXA Breakaway Ground

Description: EXA Aluminum Speed Loader® Tilt trailers could possibly need to be repaired to ensure the breakaway system is properly grounded at all times. You will be reimbursed \$45.00 per trailer for the repair. Warranty claim forms have been included for submission of completed repairs.

Reason for Bulletin: This bulletin is to provide you the necessary information to determine if the specified trailer(s) sold to your dealership will need the repair.

[insert trailer weld(s) per dealer]

Required Tools: (1) 5/16" Nut Driver (not supplied)

Supplied Repair Kit Parts: (1) 5/16" Self-tapping, Hex Screw, (1) Ground Wire wrapped in Loom



Details: Repair Instructions

1. Place the 5/16" Hex Screw (provided in kit) in the 5/16" Nut Driver.
2. Insert screw through one end of the ground wire and fasten to the bottom of the pump box.
3. Remove the 1/2" nut from the negative post of the battery.
4. Place the opposite end of the ground wire to the negative post.
5. Fasten the 1/2" nut back to the negative post of the battery.



No Ground Wire



Completed Repair -
With Ground Wire