



Service Bulletin

File in Section: -

Bulletin No.: 16-NA-206

Date: September, 2017

INFORMATION

Subject: A New Way to Look at NOx Sensor Readings and Exhaust Temperature During a DPF Regeneration or a Reductant System Malfunction Warning Service Bay Test

Brand:	Model:	Model Year:		VIN:		Engine:	Transmission:
		from	to	from	to		
Chevrolet	Colorado	2016	2018			2.8L Diesel (LWN)	
GMC	Canyon	2016	2018				

Involved Region or Country	North America
----------------------------	---------------

Introduction

The following procedure is to aid in graphing NOx sensor readings and temperature sensor readings using the GDS2.

Information for the temperatures and NOx sensors can be pulled from the DPF Service Regeneration and the Reductant System Malfunction Warning Service Bay Test from session files or stored data in GDS2.

Suggested Procedure for Graphing the DPF Service Regeneration Temperatures

Locate the DPF Service Regeneration in the Stored Data:

1. Select the Review Tab.

Stored Data Review

Graphical Data Display **Diagnostic Data Display** Line Graph Bookmarks System Information


Data List: Exhaust Aftertreatment Data **Select**

Parameter Name
Exhaust Gas Temperature Sensor 1
Exhaust Gas Temperature Sensor 2
Exhaust Gas Temperature Sensor 3

2. Select the Diagnostic Data Display tab.

3. Select the Exhaust Gas Temperature Sensor 1.

4526869



4526889

Note: The LOCK PARAMETER BUTTONS must be selected after each parameter has been selected to be graphed.

4. Select the Lock Parameter button located at the upper right side of display.
5. Repeat the steps above to add the Exhaust Gas Temperature Sensor 2, 3, 4 and 5.

Stored Data Review


Graphical Data Display | Diagnostic Data Display | **Line Graph** | Bookmarks | System Information

Data List: Exhaust Aftertreatment Data

Parameter Name
Exhaust Gas Temperature Sensor 1
Exhaust Gas Temperature Sensor 2
Exhaust Gas Temperature Sensor 3
Exhaust Gas Temperature Sensor 4
Exhaust Gas Temperature Sensor 5


4532796

6. Select the Line Graph tab.



4526913

7. On the right side of the display, select the Show/Hide Control arrow button.



4526924

8. Select the Change Scale button.

Parameters Minimum and Maximum Values

Parameter Name	Min	Max
Exhaust Gas Temperature Sensor 4	400	1200
Exhaust Gas Temperature Sensor 5	400	1200
Exhaust Gas Temperature Sensor 2	400	1200
Exhaust Gas Temperature Sensor 1	400	1200
Exhaust Gas Temperature Sensor 3	400	1200


Select

OK Cancel Reset

Note: When selecting the temperature values, the parameters should be all on the same scale.

- 4531058
9. Under the Parameters Values, select the MIN and MAX parameters for graphing out the readings.
 10. Select OK.

Graph Results



4530964


Graphed results of the exhaust temperatures during the DPF Service Regeneration.

Recommended parameter values;

- Enter 400 under MIN.
- Enter 1200 under MAX.

Stored Data Review

Graphical Data Display | Diagnostic Data Display | **Line Graph** | Bookmarks | System Information | Selected Vehicle Configuration | RPO



Legend	Parameter Name	Control Module	Value 1	Value 2	Delta	Unit
■	NOx Concentration (NOx Sensor 2)	Engine Control Module	25			ppm
■	NOx Concentration (NOx Sensor 1)	Engine Control Module	99.4			ppm


4533023

Note: NOx Sensor 2 may have higher readings than the NOx sensor 1 during a regeneration.

Graphed results of the NOx sensors during the DPF Service Regeneration.

Recommended parameter values;

- Enter 0 under MIN.
- Enter 200 under MAX.




4532848

Graphed results of the exhaust temperature readings during the Reductant System Malfunction Warning Service Bay test.

Recommended parameter values;

- Enter 400 under MIN.
- Enter 620 under MAX.



4532836

Graphed results of the NOx sensor readings during the a Reductant System Malfunction Warning Service Bay test.

Recommended parameter values;

- Enter 0 under MIN.
- Enter 360 under MAX.

Version	2
Modified	September 05, 2017 — Updated Model Years.

Additional Keywords 2.8, soot, fuel, NOx, Nitrogen Oxide, O2, Regen, Regeneration, Fuel, SCR, LWN, EGT, DOC, DPF, Exhaust, Particulate, Fluid, Quality, Message, P2463, P20EE, P219D, P249E, P2BAA, P2459, P144E, P144F

GM bulletins are intended for use by professional technicians, NOT a "do-it-yourselfer". They are written to inform these technicians of conditions that may occur on some vehicles, or to provide information that could assist in the proper service of a vehicle. Properly trained technicians have the equipment, tools, safety instructions, and know-how to do a job properly and safely. If a condition is described, DO NOT assume that the bulletin applies to your vehicle, or that your vehicle will have that condition. See your GM dealer for information on whether your vehicle may benefit from the information.



WE SUPPORT VOLUNTARY
TECHNICIAN
CERTIFICATION