

**Approved Wheels and Tires (04/18)**

Revision: This bulletin replaces bulletin Group 4, #3/17, dated April 12, 2017.

Model Year: **As of 2017**

Vehicle Type: **718 Boxster, 718 Cayman (982)**

Concern: Approval status: January 2018

Sizes: **Permissible tire and wheel sizes**  
**(RO = rim offset in mm, FA = front axle, RA = rear axle)**

Tires	Tire sizes	Wheel sizes	Snow chains
<b>718 Boxster, 718 Boxster S, 718 Cayman, 718 Cayman S</b>			
Summer	FA: 235/45 ZR18 94Y RA: 265/45 ZR18 101Y	FA: 8.0J x 18, RO 57 RA: 9.5J x 18, RO 49	No
	FA: 235/40 ZR19 (92Y) RA: 265/40 ZR19 (98Y)	FA: 8.0J x 19, RO 57 RA: 10J x 19, RO 45	No
	FA: 235/35 ZR20 (88Y) RA: 265/35 ZR20 (95Y) FA: 235/35 ZR20 (92Y) RA: 265/35 ZR20 (99Y)	FA: 8J x 20, RO 57 RA: 10J x 20, RO 45	No
	FA: 235/35 ZR20 (88Y) RA: 265/35 ZR20 (95Y) FA: 235/35 ZR20 (92Y) RA: 265/35 ZR20 (99Y)	FA: 8.5J x 20, RO 57 RA: 10.5J x 20, RO 47	No
Winter	FA: 235/45 R18 94V M+S RA: 265/45 R18 101V M+S	FA: 8.0J x 18, RO 57 RA: 9.5J x 18, RO 49	RA only
	FA: 235/40 R19 92V M+S RA: 265/40 R19 98V M+S	FA: 8.0J x 19, RO 57 RA: 10J x 19, RO 45	No

Wheels: **Overview of Porsche wheels for summer and winter tires**  
 Identification on inside of wheel:  
 Wheel size, rim offset (RO) in mm, part number (without color code FFF) and Porsche logo

**18-inch "Boxster 4" wheel**

FA: 8J x 18, RO 57

Part No. 982.601.025.M\_FFF

RA: 9.5J x 18, RO 49

Part No. 982.601.025.N\_FFF

*18-inch Boxster 4***18-inch "Cayman 3" wheel**

FA: 8J x 18, RO 57

Part No. 982.601.025.P\_FFF

RA: 9,5J x 18, RO 49

Part No. 982.601.025.Q\_FFF

*18-inch Cayman 3*

**19-inch "Boxster S 4" wheel**

FA: 8J x 19, RO 57  
Part No. 982.601.025\_FFF

RA: 10J x 19, RO 45  
Part No. 982.601.025.A\_FFF



*19-inch Boxster S 4*

**19-inch "Cayman S 4" wheel**

FA: 8J x 19, RO 57  
Part No. 982.601.025.B\_FFF

RA: 10J x 19, RO 45  
Part No. 982.601.025.C\_FFF



*19-inch Cayman S 4*

**20-inch "Carrera S 4" wheel**

FA: 8J x 20, RO 57  
Part No. 982.601.025.H\_FFF/  
982.601.026.A\_FFF

RA: 10J x 20 H2, RO 45  
Part No. 982.601.025.J\_FFF/  
982.601.026.B\_FFF



*20-inch Carrera S 4*

**20-inch "Carrera Classic 2" wheel**

FA: 8J x 20, RO 57

Part No. 981.362.160.14\_FFF

RA: 10J x 20, RO 45

Part No. 982.601.025.S\_FFF

*20-inch Carrera Classic 2*

**20-inch "Carrera Sport" wheel**

FA: 8.5J x 20, RO 57  
Part No. 982.601.025.K\_FFF/  
982.601.026.C\_FFF

RA: 10.5J x 20, RO 47  
Part No. 982.601.025.L\_FFF/  
982.601.026.D\_FFF



*20-inch Carrera Sport*

**20-inch "911 Turbo 4" wheel**

FA: 8,5J x 20, RO 57  
Part No. 982.601.025.F\_FFF

RA: 10,5J x 20, RO 47  
Part No. 982.601.025.G\_FFF



*20-inch 911 Turbo 4*



**Information**

Improper handling can damage the wheel surface.  
Carry out tire removal and mounting using a bead holding-down device only.  
Use a leather pad on the rim flange to support the valve insertion tool.  
Only use the Porsche centering clamping set for balancing.  
Do not use brushes to clean the wheels because brushes can cause deep scratches that cannot be removed by polishing.  
Never use solvents or other chemical substances on tires.



**Information**

Only fit wheels with identical part numbers on one axle.

Wheel **Tightening torque 160 Nm (118 ftlb.)**  
 Mounting:

**WARNING****Driving with different tires (mixed tires)**

- **Uncontrollable vehicle handling**
- ⇒ **Only use tires of the same make and type, with the same speed index and the same specification code (NO, N1, N2, ...) on a vehicle.**

Summer Tires:

Model	Tire size	Tire make and type
<b>718 Boxster, 718 Boxster S, 718 Cayman, 718 Cayman S</b>	FA: 235/45 ZR18 94Y RA: 265/45 ZR18 101Y	Pirelli PZero N1 (Inside/Outside)
		Goodyear Eagle F1 Asymmetric 2 NO (Inside/Outside)
	FA: 235/40 ZR19 (92Y) RA: 265/40 ZR19 (98Y)	Pirelli PZero N1 (Inside/Outside)
		Yokohama Advan Sport V105 NO (Inside/Outside)
	FA: 235/35 ZR20 (88Y) RA: 265/35 ZR20 (95Y)	Pirelli PZero N1 (Inside/Outside)
		Goodyear Eagle F1 Asymmetric 2 NO (Inside/Outside)
FA: 235/35 ZR20 (92Y) RA: 265/35 ZR20 (99Y)	Michelin XL Pilot Sport 4S NO (Inside/Outside)	

Winter Tires:

Model	Tire size	Tire make and type
<b>718 Boxster, 718 Boxster S, 718 Cayman, 718 Cayman S</b>	FA: 235/45 R18 94V M+S RA: 265/45 R18 101V M+S	Pirelli Winter 240 Sottozero Series II NO (Inside/Outside)
		Continental ContiWinterContact TS830P NO (Inside/Outside)
	FA: 235/40 R19 92V M+S RA: 265/40 R19 98V M+S	Michelin Pilot Alpin PA4 NO (Rotation)

- Arrow with inscription "Rotation" = directional mounting
- "Inside/Outside" inscription or "Left" or "Right" = mounting on specified side only
- Arrow with both inscriptions "Rotation" and "Inside/Outside" = directional mounting on specified side only.
- Arrow with both inscriptions "Rotation" and "Left" or "Right" = directional mounting on specified side only.



**Information**

N... = Specification code of the tire, e.g. "N0", "N1", "N2" ... The complete "N ..." code of the tires in question must be shown on the tire sidewall near the tire type designation.

Instructions for correct mounting of the tires are also given on the tire sidewall. If there are no mounting instructions on the tire sidewall, the tire must be mounted so that the DOT marking is visible from the outside.



**Information**

If a tire is damaged and it is not possible to determine with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally and/or mechanically overloaded due to a loss of pressure or other prior damage, replace the tire in question for safety reasons.

Repairs to "V", "W", "Y" and "ZR" tires are not permissible, as well as the use of inner tubes in tubeless tires. Please inform your customers accordingly. It is advisable to mount winter tires at temperatures below **45° F/7°C**, because the driving characteristics of summer tires are reduced at low temperatures. Extremely low temperatures can cause permanent damage to summer tires.

Tire Pressure:



**Incorrect tire pressure**

- **Uncontrollable vehicle handling**
- ⇒ **Adjust the tire pressure according to specifications. Never allow the pressure to fall below the minimum pressure.**
- ⇒ **Check age of tires. Replace tires that are more than 6 years old.**
- ⇒ **Perform visual inspections.**
- ⇒ **Use only tires recommended by Porsche.**



**Information**

The tire pressure applies only to the tire makes and types approved by Porsche, and is specified for cold tires (approx. **68° F/20°C**). The tire pressures must never be lower than the specified values.

**Standard tire pressure for summer tires**

Wheel size	718 Boxster, 718 Boxster S, 718 Cayman, 718 Cayman S	
	FA	RA
18-inch wheels	2.0 bar 200 kPa 29 psi	
19-inch wheels	2.0 bar 200 kPa 29 psi	2.1 bar 210 kPa 30 psi
20-inch wheels	2.3 bar 230 kPa 33 psi	

**Standard tire pressure for winter tires**

Wheel size	718 Boxster, 718 Boxster S, 718 Cayman, 718 Cayman S	
	FA	RA
18-inch wheels	2.2 bar 220 kPa 31 psi	
19-inch wheels	2.2 bar 220 kPa 31 psi	

**Comfort tire pressure for summer tires up to 165 mph (270 km/h) – only for vehicles with Tire Pressure Monitoring (TPM) and "Comfort pressure" menu in the multi-function display (depending on the country)**

**WARNING****Driving at high speed with low tire pressure**

- Irreparable damage to tires
- ⇒ Set Comfort air pressure for tires only on vehicles with Tire Pressure Monitoring (TPM) and "Comfort" selected in the "Tire pressure" main menu in the multi-function display.

Wheel size	718 Boxster, 718 Boxster S, 718 Cayman, 718 Cayman S	
	FA	RA
20-inch wheels	2.1 bar 210 kPa 30 psi	



Snow Chains:



**Incorrectly installed snow chains**

- **Uncontrollable vehicle handling**
- ⇒ **Do not exceed the maximum speed of Speed 30mph km/h (50) .**
- ⇒ **Observe installation instructions from the chain manufacturer.**

Porsche offers the following snow chains as accessories:

Tire size	Porsche Part No.	Type of snow chain
265/45 R 18 M+S	982.044.600.00	Link-type chain, quick fit

**Wheel Storage:** Tires must be stored in a cool, dry and dark room with adequate ventilation. Tires must never come into contact with fuel, oil, grease or chemicals.

Complete wheels can be stacked for storage; it is advisable to increase the tire pressure by 6 psi (0.4 bar).

If the tires are not mounted on wheels, it is best to store them in a vertical position. We recommend that you turn tires stored in this position every two weeks in order to prevent flat spots. Tires that are stacked in a horizontal position will become severely deformed and cannot be seated properly in the rim flange when they are mounted.

**General**

**Information:**

Always use new valves when changing tires.

Always observe any possible instructions concerning the rolling direction and/or specifying which side the tires must be mounted on. Refer to notes on page 1 (if applicable).

Coat the tire beads and humps with mounting lubricant before mounting the tire. This ensures that the tire beads will slide over the humps easily. In order to prevent the tire from turning on the wheel, avoid extreme driving maneuvers (acceleration and braking) during the first 100 to 200 miles with new or recently mounted tires.

In order to optimize smoothness of rolling, it is appropriate - and necessary in individual cases - to mount the tire in a certain (favorable) position with respect to the wheel (matching).

Matching (uncontrolled and controlled) is explained below:

**Uncontrolled matching:** Turning the tire on the wheel by 90° or 120° if necessary in order to achieve an acceptable value with regard to rolling smoothness (true running, imbalance and weight distribution of balance weights).

**Controlled matching:** With a balancing machine with matching program. In most cases, this produces an even better result with regard to the rolling smoothness (true running, imbalance and weight distribution of the balance weights) than can be achieved with uncontrolled matching. Maximum permissible radial runout and lateral runout of the wheels < 0.7 mm. Maximum permissible radial runout and lateral runout of the wheels with tires < 1.25 mm. Values < 1.50 mm - ideally approx. 0.5 mm - are desirable.

The mounting pressure (seating pressure) of 58 psi/4.0 bar overpressure must not be exceeded before both tire beads are evenly seated on the rim flange.

If new tires are to be mounted or the tires of one axle are to be replaced, tires of the same make, the same type and with the same specification code must always be used on each of the two axles. If tires are replaced on one axle only, the different tread depth from that on the other axle can cause a noticeable change in the familiar handling. This is especially the case if new tires are mounted on the rear axle. This effect decreases with increasing tire mileage.

When replacing a tire on an axle, make sure that the tread depth of the new tire does not differ from that of the other tire by more than 30 %.

If a tire is damaged and it cannot be determined with absolute certainty that there is no ply damage - with all of its consequences - or if the tire was thermally or mechanically overloaded due to a loss of pressure or other prior damage, we recommend replacement of the tire in question for safety reasons.

Repairs on "ZR" tires are not permissible, as is the use of inner tubes in tubeless tires. Tires age due to chemical and physical processes, which can impair their function. Tires that are stored unused for an extended period harden and become brittle faster than tires that are in continual use. Hairline aging cracks can occur on older tires. On tires in continual use, the kneading action activates the plasticizer in the rubber and thereby prevents hardening and cracking.

Therefore, attention should be paid not only to the tread depth but also to the age of the tire. Tires should not be older than 6 years. The age of the tire can be determined via the DOT code on the sidewall, which indicates the production date of the tire: e.g. DOT 2201 = 22nd week of 2001.

**Important Notice:** Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2018 Porsche Cars North America, Inc.