



SI B34 05 08
Brakes

April 2018
Technical Service

BRAKE ROTOR MINIMUM THICKNESS

New information provided by this revision is preceded by this symbol .

This Service Information bulletin replaces SI B34 05 08 **dated August 2008**

What's New:

- Model Information

MODEL



All

INFORMATION

BMW brake discs/rotors are stamped with a Minimum Thickness. The stamped minimum thickness is used to determine whether the brake discs/rotors require replacement during a brake service, such as pad replacement. However, some motor vehicle inspection procedures require the measurement of brake discs/rotors. An additional minimum thickness specification for the purpose of motor vehicle inspection is provided in the Technical Data section of the Repair Manual. Examples of the two specifications are described in this bulletin.

The **Stamped Minimum Thickness (MIN TH)** is utilized as described below:

New brake pads may only be installed if the brake disc thickness is greater than or equal to the minimum brake disc thickness (MIN TH) [not including M vehicles].

In the case of M vehicles and perforated (cross-drilled) brake discs, new brake pads may only be installed if the brake disc thickness is greater than the minimum brake disc thickness (MIN TH).

The **Minimum Thickness for general inspection (Motor Vehicle Inspection)** is defined as follows:

Nominal size thickness minus 2.4 mm (not applicable to perforated brake discs and M vehicles)

M vehicles and perforated (cross-drilled) brake discs: Nominal size thickness minus 1.6 mm

Note: The nominal size thickness refers to the width of a new rotor.

Always refer to the Repair Manual for model-specific information.

Posted: Friday, April 27, 2018

[Copyright ©2018 BMW of North America, Inc.]