

GROUP	NUMBER
BODY ELECTRICAL	19-BE-003H
DATE	MODEL(S)
FEBRUARY, 2019	ALL VEHICLES EQUIPPED WITH WIRELESS CHARGER

SUBJECT: WIRELESS CHARGING SYSTEM DIAGNOSIS INFORMATION

Description: Some vehicles equipped with the wireless charging pad may experience a no charging condition. This bulletin provides information of how to diagnose the no charging condition.



Applicable Vehicles: All Vehicles Equipped With Wireless Charger

Warranty Information:

Normal Warranty Applies

Parts Information:

Parts information.									
PART NAME	PART PREFIX	PART IMAGE							
Unit Assy-Wireless Charging	95560	(W/WIRELESS CHARGING (FR)) 95570 95560A J 9 k							

Diagnosis for No Charge Condition

	Condition		Checkpoint		Action	
1.	Condition of Phone / Charger	→	 Confirm if phone is equipped with wireless charging feature. Check thickness of case. Check for foreign objects. * If there is a metal foreign object between the charging pad and phone, the charging LED will start blinking. 	-	 If phone is not equipped with wireless charging, then explain to the customer. Check charging status after removing the case and/or foreign matter. 	
2.	Feature is not turned ON	→	Confirm if the feature is turned ON in the instrument cluster settings or in the radio settings.	→	Check charging status after confirming the charging setting is turned ON.	
3.	Ignition Position and/or Condition of Door (Open/Close)	→	 Confirm if ignition is in ACC or IGN position. No Charging when door is opened. 	→	 Confirm all doors are closed then check charging status. Turn ignition to ACC or IGN position then check charging status. 	
4.	Key FOB	→	Charging is stopped when vehicle is searching for the key FOB.	→	Confirm the key FOB is inside the vehicle then check charging status.	
5.	Connection	→	Check the harness connection to the charging pad.	→	If harness is not fully connected, reconnect then check charging status.	
6.	Faulty Code	→	Use the GDS to scan for DTCs.	→	If DTC B1621 (ECU Defect/Error) code is found, replace the wireless charger pad.	
7.	Temperature	→	 The maximum operating temperative of the charging mat is approximately 40 degree celsius. If the temperature is above 40 degree celsius, the charging system will shut down. 	→	 Confirm if the charging mat or phone temperative is below 40 degree celsius. If temperarture is above specification, allow both the mat and phone to cool down then check charging status. 	

TSB #: 19-BE-003H Page 2 of 2