

SSM 47948 - 2010-2019 Various Vehicles - Turbocharged Engines - Oil Supply Filter Replacement When Replacing The Turbocharger Or The Turbocharger Oil Supply Tube

For 2010-2019 vehicles equipped with turbocharged engines, when diagnosing and/or replacing turbo related concerns, all steps within the Workshop Manual (WSM) procedure must be followed including replacement of all mandatory discarded parts. When specified in the WSM, the turbocharger oil supply filter must be replaced whenever the turbocharger or the turbocharger oil supply tube are replaced. Turbocharger bearing failure may occur if oil starvation occurs due to a restricted filter.

APPLICABLE VEHICLES

2017 - 2019 CAR: CONTINENTAL
2015 - 2019 CAR: EDGE
2017 - 2019 TRUCK: ESCAPE
2011 - 2015 TRUCK: EXPLORER
2013 - 2018 CAR: FOCUS
2013 - 2019 CAR: FUSION
2015 - 2019 TRUCK: MKC
2016 - 2019 CAR: MKX
2013 - 2019 CAR: MKZ
2011 - 2019 TRUCK: EXPLORER
2010 - 2019 CAR: TAURUS
2015 - 2018 CAR: FOCUS
2015 - 2019 TRUCK: MKC
2015 - 2019 CAR: MUSTANG
2017 - 2019 CAR: CONTINENTAL
2015 - 2019 TRUCK: F-150
2017 - 2019 CAR: FUSION
2015 - 2019 TRUCK: EXPEDITION
2013 - 2019 TRUCK: EXPLORER
2010 - 2019 TRUCK: FLEX
2010 - 2016 CAR: MKS
2010 - 2019 TRUCK: MKT
2015 - 2019 TRUCK: NAVIGATOR
2015 - 2019 TRUCK: TRANSIT
2016 - 2019 TRUCK: MEDIUM TRUCK
2011 - 2019 TRUCK: SUPER DUTY