



**Countries:** AUSTRALIA, BAHAMAS, BOLIVIA, BRAZIL, BELIZE, CANADA, CHILE, TAIWAN, COLOMBIA, COSTA RICA, DOMINICAN REPUBLIC, ECUADOR, EL SALVADOR, TRINIDAD AND TOBAGO, UNITED STATES, URUGUAY, VENEZUELA, MEXICO, ARUBA, NICARAGUA, PERU, PUERTO RICO, Curaçao, GUAM, GUATEMALA, GUYANA, HAITI, HONDURAS, JAMAICA, KOREA, SOUTH KOREA, PANAMA, SOUTH AFRICA

**Document ID:** IK0200013

**Availability:** ISIS, Bus ISIS, FleetISIS, IsSIR **Revision:** 13

**Major System:** FRONT AXLE **Created:** 9/12/2011

**Current Language:** English **Last Modified:** 5/30/2019

**Other Languages:** [Français](#), [Español](#), **Author:** William Knoth

**Viewed:** 4964

[Less Info](#)

Hide Details

Coding Information

<b>Copy Link</b> 	<b>Copy Relative Link</b> 	<b>Bookmark</b>  <a href="#">View My Bookmarks</a>	<b>Add to Favorites</b> 	<b>Print</b> 	<b>Provide Feedback</b> 	<b>Helpful</b>  251	<b>Not Helpful</b>  162
----------------------	-------------------------------	--	-----------------------------	------------------	-----------------------------	---------------------------	-------------------------------

**Title:** Suggested alignment target values when performing a vehicle axle alignment

**Applies To:** All models

## CHANGE LOG

Please refer to the change log text box below for recent changes to this article:

05/20/2019 - Updated formatting, added part numbers, links to manuals and added note about radar alignments and SAS cal  
 08/02/2018 - Corrected typo  
 05/11/2018 - Updated field alignment values  
 04/04/2018 - Updated for Author Feedback

## DESCRIPTION

A proper vehicle alignment will maximize tire life and driving comfort. However, the alignment should not drift overtime under normal operating conditions. If there is a repair performed on the suspension or an accident the alignment should be checked and adjusted as needed.

## SYMPTOMS

Some indications of the need for an alignment may include a drift or pull while driving or abnormal tire wear.

Ensure the ride height is set correctly on air suspensions before checking or adjusting any alignment measurements. Please refer to the appropriate service manual for setting the ride height

## **SERVICE PARTS INFORMATION**

Description	Part Number	Required	Size
0.5 Degree Caster Shim	89500HA	As needed	2.75 x 5.75
1.0 Degree Caster Shim	520339C2	As needed	2.75 x 5.75
2.0 Degree Caster Shim	92825HA	As needed	2.75 x 5.75
3.0 Degree Caster Shim	63656R2	As needed	2.75 x 5.75
0.5 Degree Caster Shim	471170C1	As needed	3.75 x 6.8
1.0 Degree Caster Shim	692453R1	As needed	3.75 x 6.8
1.3 Degree Caster Shim	692454R1	As needed	3.75 x 6.8
2.0 Degree Caster Shim	692455R1	As needed	3.75 x 6.8
2.75 Degree Caster Shim	1654036C1	As needed	3.75 x 6.9
3.0 Degree Caster Shim	2015313C1	As needed	3.75 x 6.8
3.5 Degree Caster Shim	2020883C1	As needed	3.75 x 6.8
4.0 Degree Caster Shim	2015314C1	As needed	3.75 x 6.8
0.010 Inch Rear Axle Shim	1516023C1	As needed	
0.033 Inch Rear Axle Shim	488917C1	As needed	
0.056 Inch Rear Axle Shim	488916C1	As needed	
0.119 Inch Rear Axle Shim	590752C1	As needed	

## **RESOLUTION**



Park vehicle on a hard, flat surface, turn the engine off, set the parking brake, and block the wheels to prevent the vehicle from moving in either direction. Failure to do so may result in property damage, personal injury, and / or death.



If the vehicle must be raised, do not work under the vehicle supported only by jacks. Jacks can slip or fall over, potentially resulting in property damage, personal injury, and / or death.



**Always wear safe eye protection when performing vehicle maintenance. Failure to do so may result in personal injury and / or death.**

Refer to [IK0200023 - Navistar Wheel Alignment Policy](#) before performing any alignments to vehicles under warranty.

For front axle alignments please refer to [S02001K Steering General Service Information and Front Wheel Alignment](#) manual.

For rear axle alignments please refer to [S03003 Suspension Alignment](#) manual.

**In Service Specifications:**

**Steering Axle**

	Minimum	Maximum	Unit
<b>Toe in</b>	.00	.18	Degrees
	.00"	.125"	Inches
	0	1/8"	Fractions
	.00	3.19	Millimeter
	.00	3.14	mm/M

**Rear Axles**

	Minimum	Maximum	Unit
<b>Thrust</b>	-.18	.18	Degrees
	-.250"	.250"	Inches
	-6.4	6.4	Millimeter
	-3.1	3.1	mm/M
<b>Tram/Scrub</b>	-.08	.08	Degrees
	-.125	.125	Inches
	-3.2	3.2	Millimeter
	-1.4	1.4	mm/M

**NOTES:**  
 Due to variation in equipment and measuring techniques do NOT make any adjustments if the initial readings are inside the "In Service Specifications".

**NOTES:**  
 Negative degree tolerance denotes left tire behind right (Josam alignment equipment inverse).

**NOTES:**

For caster and camber specifications refer to [S02001K](#)

If out of "In Service Specifications" re-adjust to below target values:

**Steering Axle**

	Minimum	Maximum	Unit
<b>Toe in</b>	0.03	0.09	Degrees
	0.021"	0.063"	Inches
	1/32	1/16	Fractions
	0.54	1.60	Millimeter
	0.54	1.62	mm/M

**Rear Axles**

	Minimum	Maximum	Unit
<b>Thrust</b>	-0.05	0.05	Degrees
	-0.084"	0.084"	Inches
	-2.13	2.13	Millimeter
	-0.9	0.9	mm/M
<b>Tram/Scrub</b>	-.08	0.00	Degrees
	-.125	0.000	Inches
	-3.2	0.0	Millimeter
	-1.4	0.0	mm/M

**NOTES:**  
 Negative degree tolerance denotes left tire behind right (Josam alignment equipment inverse).

**NOTES:**  
 On vehicles equipped with forward radar. The radar alignment procedure should be followed anytime the rear axles are adjusted. (Refer to the radar manufacturer for this procedure.)

**NOTES:**  
 On vehicles equipped with ESC. The steering wheel angle sensor calibration should be performed anytime the toe is adjusted. (Refer to the ABS manufacturer for this procedure.)

**NOTES:**  
 For caster and camber specifications refer to [S02001K](#)

## **WARRANTY INFORMATION**

### **Warranty Claim Coding:**

Refer to the [Warranty Coding Manual](#) for Group and Noun Codes.

### **Standard Repair Time(s):**

Refer to the [SRT Manual](#) for Repair Times

---

## **OTHER RESOURCES**

MaxxPower Front Air Suspension: [S03015 Service Manual](#) ([PDF Version](#))

 Hide Details

#### **Feedback Information**

Viewed: 4963  
Helpful: 251  
Not Helpful: 162

No Feedback Found

---

Copyright © 2019 Navistar, Inc.