

NUMBER: 09-002-19 REV. A

GROUP: 09 - Engine

DATE: May 18, 2019

This bulletin is supplied as technical information only and is not an authorization for repair. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without written permission of FCA US LLC.

This bulletin supersedes Service Bulletin 09-002-19, dated May 01, 2019, which should be removed from your files. All revisions are highlighted with **asterisks** and include adding 2018 model year and build date.

This Service Bulletin is also being released as Rapid Response Transmittal (RRT) 19-035, dated May 01, 2019. All applicable Un-Sold RRT VINs have been loaded. To verify this RRT service action is applicable to the Un-Sold vehicle, use VIP or perform a VIN search in DealerCONNECT/Service Library.

SUBJECT:

Diesel Low Pressure Exhaust Gas Recirculation (EGR) Valve Cleaning

OVERVIEW:

This bulletin involves cleaning the diesel low pressure EGR valve.

MODELS:

2018 - 2019 (JL)

Jeep Wrangler

NOTE: This bulletin applies to vehicles within the following markets/countries: EMEA.

NOTE: This bulletin applies to vehicles built on or after **April 01, 2018 (MDH 0401XX)** on or before January 31, 2019 (MDH 0131XX) equipped with a 2.2L N-S I4 Turbo Diesel W/ESS (Sales Code EBH).

SYMPTOM/CONDITION:

Vehicles may display a Malfunction Indicator Lamp (MIL) illumination. Upon further investigation the technician may find that the following Diagnostic Trouble Code (DTC) has been set:

• P045E - EGR -B- Control Stuck Open.

DIAGNOSIS:

If the VIN is listed in VIP or your RRT VIN list, perform the repair. This RRT only applies to vehicles on the RRT VIN list.

REPAIR PROCEDURE:

- 1. Verify the ambient temperature is above 0° C (32° F).
- 2. Using wiTECH, record all DTCs and clear them.
- 3. Start the engine and allow it to run until the coolant temperature reaches a minimum of 50° C (122° F). Monitor the coolant temperature using wiTECH.

NOTE: Do not leave the ignition off for more than 30 seconds to avoid the engine cooling down.

- 4. Turn the ignition **off** for 10 to 30 seconds.
- 5. Turn the ignition **on** for 10 to 20 seconds to allow the low pressure EGR to perform several opening and closing cycles.
- 6. Turn the ignition off for 10 to 30 seconds.
- 7. Repeat steps 4 through 6 for a total of **nine times**.
- 8. Did the MIL illuminate and DTC P045E set, after the above cleaning procedure was performed?
 - YES>>> Follow normal diagnostic procedures for the DTC and repair as necessary per current warranty guidelines.
 - NO>>> This bulletin has been completed.

POLICY:

Reimbursable within the provisions of the warranty.

TIME ALLOWANCE:

Labor Operation No:	Description	Skill Category	Amount
25-01-45-9C	Clean EGR Valve - 2.2 Liter Diesel Engine Only (2 - Skilled)	10 - Diesel	0.5 Hrs.

FAILURE CODE:

ZZ Service Action	
-------------------	--