



SAFETY RECALL V71 OCCUPANT RESTRAINT CONTROLLER

ABS INITIALIZATION

There has been an increase in warranty claim submissions for performing the ABS Initialization on vehicles after they have had Safety Recall V71 completed. Please note that this is included as part of Dealer Instructions as indicated in step 18 on page 5. Moving forward any claim that is paid due to not adhering to this step will be subject to chargeback.

Safety Recall V71 -- Occupant Restraint Controller

Page 5

Service Procedure [Continued]

16. From the **“Topology”** screen, click on the **“ABS”** icon.
17. From the **“ABS”** screen, select the **“Misc Functions”** tab.
18. Perform the **“ABS Initialization”** routine and follow the screen prompts.
19. Select **“Clear All DTCs”** and then select **“Close”**.
20. Remove the battery charger from the vehicle and then close the hood.
21. Place the vehicle ignition in the **“OFF”** position, unplug the wiTECH MicroPod II and open and close the driver’s door. Let all modules go to sleep (This should take approximately one minute).
22. Reconnect wiTECH 2.0 and clear any DTCs which may have been set.
23. Place the vehicle ignition in the **“OFF”** position and unplug the wiTECH MicroPod II.
24. Return the vehicle to the customer or to vehicle inventory.

FCA Appreciates Your Support!