



Volkswagen

2017 Beetle/Beetle Convertible

Engine	Part	Part Number	Quantity
1.8L Turbo: CPKA, CPRA	Oil Filter	06K 115 562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30	N/A	5.5L (5.7qt)
	Drain Plug Gasket	N 911 679 01	1
	Air Filter	5C0 129 620	1

Engine	Part	Part Number	Quantity
2.0L Turbo: CPLA, CPPA	Oil Filter	06K 115 562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30	N/A	5.5L (5.8qt)
	Drain Plug Gasket	N 911 679 01	1
	Air Filter	5C0 129 620	1

Engine	Part	Part Number	Quantity
2.0L Turbo: DDSA, DDSB	Oil Filter	06K 115 562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30	N/A	5.7L (6.0qt)
	Drain Plug Gasket	06L 103 801	1
	Air Filter	5C0 129 620 B	1

2017	Engine Code		Torque Spec
Oil drain plug Torque	1.8L	CPKA, CPRA	30 Nm
	2.0L	CPLA, CPPA	
	2.0L	DDSA, DDSB	
Wheel hub bolt Torque	1.8L	CPKA, CPRA	140 Nm
	2.0L	CPLA, CPPA	
	2.0L	DDSA, DDSB	

<i>Miscellaneous</i>	Part	Part Number	Quantity
<i>Miscellaneous</i>	Pollen Filter	1K0 819 644 B	1
	Wiper Blades (Left or Right)	5C1 955 425	2
	Battery (Amp. Req. Vary)	5K0 915 105*	1
	Battery (Amp. Req. Vary)	5GM 915 105*	1
	Battery (Amp. Req. Vary)	000 915 105*	1

*VIN Required

Revised 10/28/2019

2017 Beetle Service Reminder Reset

Resetting oil change service

If the oil change service was not performed by a Volkswagen workshop, it can be reset as follows:

Vehicles with text messages:

1. Switch off the ignition.
2. Press and hold down the **0.0/SET** button in the instrument cluster.
3. Restart the ignition.
4. Release the button **0.0/SET**.
5. Confirm the selection on the instrument cluster by pressing the **OK/RESET** button on the windshield wiper lever or the **OK** button on the multi-function steering wheel.

Vehicles without text messages:

1. Switch off the ignition.
2. Press and hold down the **0.0/SET** button in the instrument cluster.
3. Restart the ignition.
4. Release the **0.0/SET** button and press the **🔧/🕒** button within approximately 20 seconds.

Do **not** reset the service interval display between service intervals, otherwise incorrect data may be shown.

If you manually reset the service interval display while flexible oil change service is valid, “fixed oil change service” will be activated. The service interval will no longer be calculated on an individual basis.

Resetting inspection

If the inspection was not performed by an authorized Volkswagen workshop, it can be reset as follows:

Vehicles with text message:

1. Switch off the ignition.
2. Switch on the hazard warning lights.
3. Press and hold down the **0.0/SET** button in the instrument cluster.
4. Restart the ignition.
5. Release the button **0.0/SET**.
6. Confirm the selection on the instrument cluster by pressing the **OK/RESET** button on the windshield wiper lever or the **OK** button on the multi-function steering wheel.
7. Switch off the hazard warning lights.

Vehicles without text messages:

1. Switch off the ignition.
2. Switch on the hazard warning lights.
3. Press and hold down the **0.0/SET** button in the instrument cluster.
4. Restart the ignition.
5. Release the **0.0/SET** button and press the **⏏/⌚** button within approximately 20 seconds.
6. Switch off the hazard warning lights.



The service message will disappear after a few seconds, when the engine is running, or when the **OK/RESET** button on the windshield wiper lever or the **OK** button on the multifunction steering wheel is pressed.



If the 12-volt vehicle battery is disconnected for an extended period in a vehicle with flexible oil change service, the system will not be able to calculate the time when the next oil change service is due. The service displays could then display incorrect information. If this is the case, then please observe the maximum service intervals shown in the Service Schedule.

For current fluid capacity charts, please refer to the Maintenance section in Elsa.