



## 2017 CC



Volkswagen

Engine	Part	Part Number	Quantity
<b>2.0L Turbo: CBFA, CCTA</b>	Oil Filter	06J 115 403 Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30	N/A	4.7L (5.0qt)
	Drain Plug Gasket	N 911 679 01	1
	Air Filter	1K0 129 620 D	1

2017	Engine Code		Torque Spec	
<i>Oil drain plug Torque</i>	2.0L	CBFA, CCTA	M14 plug	30 Nm
			M24 plug	50 Nm
<i>Wheel hub bolt Torque</i>	2.0L	CBFA, CCTA	120 Nm	

Engine	Part	Part Number	Quantity
<b>Miscellaneous</b>	Pollen Filter (Odor and Harmful Substance)	1K1 819 653 B	1
	Pollen Filter (Odor and Allergen)	1K1 819 669	1
	Pollen Filter (Dust and Pollen)	1K1 819 644 B	1
	Wiper Blade Set	3CB 998 002	1
	Battery (Amp. Req. Vary)	000 915 105 *	1
	Battery (Amp. Req. Vary)	JZW 915 105 *	1

\*VIN Required

Revised 10/28/2019

## 2017 CC Service Reminder Reset

### Resetting the oil change service reminder

If the service was not performed by an authorized Volkswagen dealer or an authorized Volkswagen Service Facility, the oil change service reminder can be reset as follows:

1. Switch off the ignition.
2. Press and hold the **0.0/SET** button in the instrument cluster.
3. Switch on the ignition.
4. Release the **0.0/SET** button.
5. A confirmation message appears in the display. Confirm request with **OK** button on the multi-function steering wheel.

### Resetting the inspection service reminder

If the service was not performed by an authorized Volkswagen dealer or an authorized Volkswagen Service Facility, the inspection service reminder can be reset as follows:

1. Switch off the ignition.
2. Switch on the emergency flashers.
3. Press and hold the **0.0/SET** button in the instrument cluster.
4. Switch on the ignition.
5. Release the **0.0/SET** button.
6. A confirmation message appears in the display. Confirm request with the **OK** button on the multi-function steering wheel.
7. Switch off the emergency flashers.



Do **not** reset the service reminder between service intervals; otherwise incorrect information will be displayed.



The service reminder disappears after a few seconds or after the **OK** button on the multi-function steering wheel has been pushed.

**For current fluid capacity charts, please refer to the Maintenance section in Elsa.**