



Volkswagen



## 2009 – 2010 Routan

Engine	Part	Part Number	Quantity
<b>3.8L V6: CGUA</b>	Oil Filter	7B0-115-561	1
	SAE 5W-20 (API Certified) Engine oil is recommended for all operating temperatures	N/A	4.7L (5.0qt)
	Drain Plug With Gasket	7B0-103-624	1
<b>Miscellaneous</b>	Air Filter	7B0-129-620	1
	Driver's Wiper Blade	7B0955425A	1
	Passenger's Wiper Blade	7B0-955-426	1
	Rear Wiper Blade – Plastic	7B0-955-427-A	X
	Rear Wiper Blade – Metal	7B0-955-427-B	X

Engine	Part	Part Number	Quantity
<b>4.0L V6: CVGA</b>	Oil Filter	7B0-115-561-C	1
	SAE 10W-30 (API Certified) Engine oil is recommended for all operating temperatures	N/A	5.2L (5.5qt)
	Drain Plug With Gasket	7B0-103-193	1
	Pollen Filter (12K Only)	7B0-819-644	1
<b>Miscellaneous</b>	Air Filter	7B0-129-620	1
	Driver's Wiper Blade	7B0955425A	1
	Passenger's Wiper Blade	7B0-955-426	1
	Rear Wiper Blade – Plastic	7B0-955-427-A	X
	Rear Wiper Blade – Metal	7B0-955-427-B	X

2009-2010	Engine Code		Torque Spec
<b>Oil drain plug Torque</b>	3.8L	CGUA	27 Nm
	4.0L	CVGA	
<b>Wheel Mounting Nuts Torque</b>	3.8L	CGUA	135 Nm
	4.0L	CVGA	

Revised 11/11/2019

## **CHAngE OIL**

Your vehicle is equipped with an engine oil change indicator system. The **CHAngE OIL** message will flash in the instrument cluster odometer for approximately 12 seconds after a single chime has sounded to indicate the next scheduled oil change interval. The engine oil change indicator system is duty cycle-based, which means the engine oil change interval may fluctuate dependent upon your personal driving style.

Unless reset, this message will continue to display each time you turn the ignition switch to the ON/RUN position. To turn off the message temporarily, press and release the Trip / Odometer Display reset button on the instrument cluster.

### **To reset the oil change indicator system** (after performing the scheduled maintenance)

Refer to the following procedure.

1. Turn the ignition switch to the ON position (Do not start the engine).
2. Fully depress the accelerator pedal slowly three times within 10 seconds.
3. Turn the ignition switch to the OFF position.

**NOTE:** If the indicator message illuminates when you start the vehicle, the oil change indicator system did not reset. If necessary repeat this procedure.