

**** SOLUTION ****

Title **To Be Published** Description and Function - Premium Tech Tool (PTT) Operation [2589-08-03-18 Exhaust Aftertreatment System Analysis](#)

Mack Models

Mack Model LR , TE - TerraPro , AN - Anthem , GR - Granite , PI - Pinnacle

Volvo Models

Volvo Model VN , VNL , VNR , VNX , VAH , VHD

Emission Standard

Emission Standard US17+OBD18

Engine family

Engine family 11L Engine , 13L Engine , MP7 , MP8

**** SOLUTION ****

Cause **Purpose:** To have a series of routines in Premium Tech Tool (PTT) to effectively evaluate and diagnose the NOx sensors, Urea (DEF) dosing system, and SCR efficiency. The routine is also captured in a .csv file and can be downloaded from Product History Viewer for later review if necessary. This document includes the list of Diagnostic Trouble Codes (DTC) that, when following Guided Diagnostics (GD), will list this operation as a step. This document will outline key details that the technician should be aware of when performing the operation. Currently this operation is only available for 11 and 13 liter engines with:

- US17+OBD18 Emissions
- A Variable Geometry Turbo (VGT)
- Engine Control Module (EMS) Main Software (MSW) Part Number 23766686 and newer.

For these vehicle configurations, the NOx Conversion Test (operation 2549-08-03-03) is replaced by this operation (2589-08-03-18 EATS Analysis). The NOx Conversion Test will remain available for all other variants except US17 emissions turbo compound engine configurations.

Solution Current operations in Premium Tech Tool typically allow for activation of actuators with the engine off/key on or without control over other variables, and trying to record on-the-road data typically introduces too many variables to make an effective diagnosis. The Exhaust Aftertreatment System Analysis attempts to resolve many of these issues by testing engine and emissions components as a system with the engine running under more controlled operating conditions and without the requirement of removing engine components. The current operation consists of 4 subtests:

1. Aftertreatment Hydrocarbon Injection (AHI) System

- Verifies that the AHI system is properly working to warm the exhaust system at various levels of fuel dosing. Aids in clearing the SCR buffer.

2. NOx Sensors

- Checks NOx sensor readings during varying engine operating conditions.

3. Diesel Exhaust Fluid (DEF) Dosing System

- Verifies proper DEF flow, dosing valve operation, and pump function.

4. SCR efficiency

- Provides an objective evaluation of SCR efficiency under controlled, repeatable conditions.

Prior to these tests, there is a warm-up step to ensure proper exhaust/ aftertreatment temperatures and that the NOx sensors are warmed up/enabled:

These routines can be run separately or in combination. By default, all of the subtests are enabled. Typical time to run all 4 subtests is 25-45 minutes. The test time is dependent on many factors: engine/coolant temperature and ambient temperature, for example.

Operations screens for PTT

Tech Tool

Tech Tool Links Help

Product Product History Diagnose Test Calibrate Program Impact

2589-08-03-18 Exhaust Aftertreatment System Analysis

Information >> Conditions >> Execution >> Result

Purpose

Comprehensive check of Exhaust Aftertreatment System (EATS)

Note: This operation should only be used in the following circumstances

- Reference to: 1 diagnostic service information or Technical support
- Relevant DTCs: P103C, P20EE, P225E, P225C, P229F, P2201, P0422

Description


- The ECM routine will perform a self-evaluating system test on the Exhaust Aftertreatment System (EATS)
- All test can be performed in sequential order or specific sub-test that can be individually selected

Available sub-test that can be performed individually

- 1 Aftertreatment hydrocarbon injection (AHI) system
- 2 NOx sensors
- 3 DEF dosing system
- 4 SCR efficiency

Operation may take approximately 15 - 45 minute(s) to complete

Continue > Cancel





Diagnostic Trouble Codes

The Guided Diagnostic (GD) trees for the DTCs below will be updated to reflect this operation.

Diagnostic Trouble Code	Description	Behavior
P20EE-00	SCR NOx Catalyst Efficiency Below Threshold Bank 1	All subtests should be performed
P103C-00	SCR NOx Catalyst Efficiency Inducement	All subtests should be performed
P0422-00	Catalyst 2 Efficiency Below Threshold Bank 1 (DPF NMHC conversion efficiency)	All subtests should be performed (only when DTC is confirmed)

P225E-00	NOx Sensor Performance Signal Stuck High Bank 1 Sensor 2 (NOx outlet)	All subtests should be performed (only when DTC is confirmed)
P2201-64	NOx Sensor Circuit Range/Performance Bank 1 Sensor 1 / Signal Plausibility Failure (NOx inlet)	Only the NOx sensors subtest should be performed
P225C-00	NOx Sensor Performance Signal Stuck High Bank 1 Sensor 1 (NOx inlet)	Only the NOx sensors subtest should be performed
P229F-64	NOx Sensor Circuit Range/Performance Bank 1 Sensor 2 / Signal Plausibility Failure (NOx outlet)	Only the NOx sensors subtest should be performed

General Testing Conditions

The primary thresholds / enable and exit conditions are listed below:

Parameter	Value	Behavior
Ambient Air Temperature	Between 11 °F and 104 °F (12 °C and 40 °C)	
DPF Soot Level	Less than 69%	
DEF Tank Level	Greater than 10%	
Coolant Temperature	Greater than 140 °F (60 °C)	Vehicle will run in Heating EATS phase until minimum temperature is reached.
Diesel Oxidation Catalyst (DOC) Outlet Temperature (T2)	Greater than 734 °F (390 °C)	
SCR Average Temperature (Calculated Value)	Greater than 680 °F (360 °C) for at least 2 minutes.	Minimum temp must be maintained for minimum time period for test to begin.

- When coolant and SCR average temp requirements are satisfied, and if NOx sensors have not come online, the routine allows 4 minutes for NOx Inlet and 5 minutes for NOx outlet to come online before it will abort test for NOx sensor quality (bad).
- Additionally, if the NOx sensors are the last to come online, there is a 60 second delay before it will enter the NOx sensor evaluation.
- If the conditions are not met within 1800 seconds (30 minutes) the test will abort.
- EGR position is commanded to zero (full closed) for warmup and currently every phase of the operation.

NOTE: Test abort due to NOx Inlet or Outlet sensor quality bad is an unlikely scenario, however if this exception occurs, it is advisable to re-run test 1 more time.

Tests and Operations

Heating EATS Phase (Warmup)

Heating EATS Phase Operation Details

The purpose of the warmup phase is to stabilize engine and exhaust temperatures, bring the NOx sensors online, and clear the SCR buffer. During the Heating EATS phase (sometimes referred to as “warmup”) the engine enters a state similar to regeneration and will vary engine speed between 1200 and 1250 rpm and control the VGT position to reach the target range for engine exhaust temperature (measured by the T1 temperature sensor). This phase will occur during all of the selected sub tests. AHI dosing will occur whether or not the AHI subtest is selected in order to meet target DOC outlet temperature (measured by the T2 temperature sensor) and SCR average temperatures and bring the NOx sensors online faster.

The screenshot displays the Tech Tool software interface during a test. The main window is titled "Tech Tool" and has a menu bar with "Tech Tool", "Links", and "Help". Below the menu bar are tabs for "Product", "Product History", "Diagnose", "Test", "Calibrate", "Program", and "Impact". The "Test" tab is active.

On the left side, there is a "Start" button and a "DEF System Status" indicator showing "Running". Below this is a "Percentage completed (0 - 100%)" progress bar at 38%. A "Primary Parameters" section contains a graph titled "AHI" with a y-axis from 0 to 125 and an x-axis from 10.0 to 10.83. The graph shows a black line representing AHI dosing, which starts at approximately 75, drops to about 40, and then rises back to 75. A vertical dashed green line is positioned at approximately 10.5 on the x-axis.


On the right side, there is an "Action" section and a "Current test status" section. The "Current test status" section contains a yellow box with the text: "Test phases are based on which subtests have been selected; test phases 1 - 7 are used if all subtests have been selected". Below this, there are several test phases listed: "Alertreatment hydrocarbon injection (AHI) system (Phase: 1)", "NOx sensors (Phases: 1, 2 & 3)", "DEF dosing system (Phases: 1 & 4)", and "SCR efficiency (Phases: 1, 5, 6 & 7)". A blue circle icon indicates which test phase is currently active. Below the list, there are three numbered items: "1) Heating EATS - During this phase of the test sequence, the Exhaust Alertreatment System (EATS) will be heated. This is done so that it is possible to start the NOx sensors safely without exposing them to harmful moisture, and to ensure that the selective catalytic reduction catalyst is completely emptied. The heating phase will finish when the temperature has been reached and the NOx sensors are started and free from internal electrical faults.", "2) NOx sensor high level evaluation - The engine will be set in a mode where high NOx is produced, average readings from the inlet and outlet sensor will be recorded and evaluated after the low NOx sensor evaluation. If the difference between the average sensor readings exceeds pre-determined limits, the responses and recommended actions will be displayed in the Results step.", and "3) NOx sensor low level evaluation - The engine will be set in a mode where very low NOx is".

At the bottom of the window, there is a "Continue >" button. The status bar at the very bottom shows "Chassis ID: N 976465 VIN: 4V4N99EHXHN976465 Work Order: 94eats" and "Product Online" with green checkmarks.

Operation failure during Heating EATS phase:

The screenshot below shows the current recommended actions for the scenario when criteria are met for the Heating EATS phase, except NOx outlet sensor came online just after the timeout period.

The first recommended action in this scenario, specifically if the unit did not have NOx sensor DTCs, is to rerun the test.



AHI Subtest

The AHI subtest has the advantage of adding more heat to the system and aids in clearing the SCR buffer faster. When the AHI system subtest is selected, AHI dosing is added at 3 fixed dosing rates for 2 minutes at each step. When the AHI subtest is selected and the Engine exhaust temperature (T1) reaches 527 °F (275 °C), AHI dosing will begin.

Subtest conditions:

Condition	Value
Engine Exhaust Temperature (T1)	Minimum of 527 °F (275 °C)

AHI Subtest Failure

The following conditions will allow the AHI subtest to complete, but will show a “test failed” status for the results:

DOC Outlet Temperature (T2) Threshold	Time Limit
T2 fails to reach 464 °F (240 °C)	First 2 minutes of dosing
T2 fails to reach 626 °F (330 °C)	Second 2 minutes of dosing
T2 fails to reach 734 °F (390 °C)	Third 2 minutes of dosing

The conditions below will cause the AHI Subtest to abort or fail:


Parameter	Condition	Effect
Engine, DOC, or DPF Outlet Temperature (T1, T2, OR T3)	Temperature exceeds 914 °F (490 °C)	Test aborts due to over-temperature
Engine Exhaust Temperature (T1)	Temperature falls below 527 °F (275 °C) after AHI dosing begins	Test result will show failed


If the AHI subtest fails as shown in the screenshot below, the first recommended action is to uncheck the AHI system test and restart the test. This failure can result if the DOC Outlet Temperature (T2) does not reach the specified minimum temperature for each of the subtest's 3 steps.


Tech Tool Links Help


Product Product History Diagnose **Test** Calibrate Program Impact


Test result

AHI Response




NOx inlet response


NOx outlet response


DEF dosing system


SCR efficiency


Reference

Icon	Description
	OK
	Test failed


2589-08-03-18 Exhaust Aftertreatment System Analysis

Information >> Conditions >> Execution >> **Result**

Result

Recommended actions

AHI Response

 The main purpose of the AHI subtest is to heat the exhaust aftertreatment system in a controlled manner. It also helps to clear the SCR buffer for further tests. Due to the way the AHI subtest is run, there may be instances of subtest failure if system enters cool-down mode or other circumstances. Before diagnosing AHI system, run the operation again without the AHI system subtest enabled. If the routine completes and there are no faults related to the AHI system, no further action should be necessary.

- Carry out the following operation: 2545-08-03-02 Exhaust Aftertreatment Diagnostics (Active Diagnostics Test/Aftertreatment hydrocarbon doser air flow test)
- Check for exhaust temperature sensor plausibly faults
- Visual inspection of the DOC

NOx inlet response


- No action needed

NOx outlet response

- No action needed

Continue >

The “Not tested” response shown under the AHI Response section in the screenshot below is the result of unchecking the AHI subtest.



NOx Sensor Subtest

The primary purpose for the NOx high and low phase evaluation is to verify the plausibility of the sensors at two points in the measurement range where the readings should be within the manufacturers specified accuracy with the SCR buffer cleared, the readings should be within the “allowable difference” tolerance and the NOx level is not expected to exceed the Max/Min limits.

After conditions are satisfied for the warmup state, the routine enters the NOx sensor high and low evaluation phases. This phase replaces the current NOx Conversion test.

IMPORTANT NOTE: In the rare case that there are enough crystals in the urea (DEF) injection pipe to sublime during the warmup, the Outlet NOx Value will read significantly lower than the Inlet NOx Value during the last part of the Heating EATS phase, typically when the DPF outlet temperature (T3) is above approximately 626 °F (330 °C). as T3 drops—which should occur during NOx sensor high and low evaluations—NOx outlet may rise as less sublimation occurs. This could cause the routine to abort immediately after the Heating EATS phase, or cause the NOx sensor evaluation to fail if this is suspected, a crystal sublimation should remedy the problem.

Subtest conditions:

High Evaluation

Condition	Value	
	11 Liter Engine	13 Liter Engine
Engine Speed	1050 RPM	1100 RPM
VGT (Turbo) Position	10%	7%
Injection Timing	5° BTDC	5° BTDC
Fan Speed	Max	Max

The routine will stabilize for 40 seconds and then average the NOx sensor readings for 20 seconds before entering NOx low evaluation.

NOx sensor low evaluation:

Condition	Value	
	11 Liter Engine	13 Liter Engine
Engine Speed	1050 RPM	1100 RPM
VGT (Turbo) Position	25%	25%
Injection Timing	0° (TDC)	0° (TDC)
Fan Speed	Max	Max

The routine will stabilize for 40 seconds and then average the NOx sensor reading for 20 seconds.

Limits (For test to complete successfully)

Phase	Maximum Difference between Inlet and Outlet NOx Values
High	100 ppm
Low	50 ppm

Operations Screens - NOx Sensor High Level Evaluation



Start




DEF System Status:

Running

Percentage completed (0 - 100%)



Primary Parameters



NOx sensors (Phases: 1, 2 & 3)

DEF dosing system (Phases: 1 & 4)

SCR efficiency (Phases: 1, 5, 6 & 7)

Indicates which test phase is currently active

1) Heating EATS - During this phase of the test sequence, the Exhaust Aftertreatment System (EATS) will be heated. This is done so that it is possible to start the NOx sensors safely without exposing them to harmful moisture, and to ensure that the selective catalytic reduction catalyst is completely emptied. The heating phase will finish when the temperature has been reached and the NOx sensors are started and free from internal electrical faults.


2) NOx sensor high level evaluation - The engine will be set in a mode where high NOx is produced, average readings from the inlet and outlet sensor will be recorded and evaluated after the low NOx sensor evaluation. If the difference between the average sensor readings exceeds pre-determined limits, the responses and recommended actions will be displayed in the Results step.

3) NOx sensor low level evaluation - The engine will be set in a mode where very low NOx is produced, average readings from the inlet and outlet sensor will be recorded. At the last test phase, average values from the high NOx and low NOx will be compared and evaluated. If the difference between the average sensor readings exceeds pre-determined limits, the responses and recommended actions will be displayed in the Results step.

4) DEF dosing system evaluation - Average pump duty cycles will be recorded during no dosing and dosing conditions. After this phase, the difference in duty cycle will be calculated and compared to an expected value. If the difference in pump duty cycle is below expected limits, the responses and recommended actions will be displayed in the Results step.

5) Cool down mode - The purpose of this phase is to lower the temperature of the EATS prior to the

Continue >



Urea (DEF) Dosing System Subtest

The primary purpose for the urea dosing system check is to verify urea flow prior to evaluation of the SCR efficiency. While this test can be performed separately, and has the advantage over the flow test in that there is no dis assembly for some cases it may be good practice to also perform the standard dosing valve test, especially in any case when SCR replacement is considered. This would allow for visual inspection of the urea injection pipe for excessive crystal buildup. In any cases where excessive crystal buildup is observed , it may be advisable to perform a sulfur regeneration or crystal sublimation and then re run the operation.

After conditions are satisfied for the NOx Sensor Subtest, the routine enters the DEF dosing system check.

Subtest Conditions

Condition	Value (11L & 13L Engines)
Engine Speed	1000 RPM
VGT (Turbo) Position	~10%

Injection Timing	20° BTDC
------------------	----------

The DEF Dosing Routine lasts approximately 30 seconds. The DEF pump duty cycle is first evaluated during a “no dosing” state at 131 psi (900 kPa) pressure. The ACM will then command .8 g/sec (0.028 oz/sec) urea flow. The urea dosing valve duty cycle will last approximately 10 seconds, and the change in pump duty cycle to maintain pressure is evaluated.

Limits (For test to complete successfully)

Parameter	Allowable change (.8 g/s flow, 10 second average)
DEF Pump Duty Cycle	Between 8% and 12%

This range allowance, while appearing narrow is actually quite wide. Based on test data, typical pump duty cycle change is about 9-10%

Cooldown Mode (Intermediate Phase)

The primary purpose for the cooling phase is to bring exhaust and SCR temperatures lower in order to expedite the stabilization step prior to efficiency evaluations. The target SCR temperature for the stabilization and SCR efficiency low evaluation steps is relatively low at 518.9 °F (270.5 °C) when compared to the temperature targets reached during the warmup phase. The SCR temperature reacts significantly slower than the other exhaust temperatures, and is usually elevated well above the target for SCR evaluation from the previous steps.

Both the NOx flow and Exhaust Mass Flow are recorded in the data (csv) file and displayed in the results of the test. These are not displayed during the test for initial releases of the EATS Health Check due to current Tech Tool limitations.

After conditions are satisfied for the Urea Dosing System check, the routine enters the Cooling step.

Phase Conditions

Condition	Value (11L & 13L Engines)
Engine Speed	1600 RPM
VGT (Turbo) Position	Variable
Injection Timing	Variable

This step will last approximately 30 seconds.

Limits (For phase to complete successfully)

Parameter	Condition
SCR Outlet Temperature	Temperature decreasing toward 518.9 °F (270.5 °C)

Stabilize Low SCR Temperature (Intermediate Phase)

The purpose of the stabilization step is to stabilize the SCR temperature, exhaust mass flow and NOx flow to begin the SCR efficiency evaluation.

After the cooling step, the routine enters the Stabilize low SCR temp step.

Phase Conditions

Condition	Value (11L & 13L Engines)
Engine Speed	1550 RPM
VGT (Turbo) Position	18% (At start of phase)
Injection Timing	20° BTDC (At start, then retarding)
Intake Throttle Valve (ITV) Position	Closes from 87% to 20%

After approximately 5 seconds, injection timing will retard from 20 BTDC to control NOx flow at 0.40 ± 0.01 g/s (.052 to .054 lb/min)

After approximately 1 minute, the routine will evaluate the exhaust temperature and exhaust mass flow routine will adjust the VGT to raise or lower the exhaust temperature between 518 and 536 °F (270 and 280 °C) and engine speed may be increased or decreased in 30 RPM increments as required to maintain exhaust mass flow between 0.21 and 0.26 kg/s (27.783 to 34.398 lb/min)

After the target exhaust mass flow and engine temperatures are reached, the routine will wait until the SCR average temperature falls within the range of 509-527 °F (265-275 °C) for 30 seconds to begin the SCR efficiency low step.

Additional condition for exiting stabilize low is the difference between NOx inlet and outlet doesn't exceed 150 ppm (this is to ensure any SCR buffer accumulated during the UDS check is clear)


Limits (For phase to complete successfully)

Parameter	Condition
Engine Speed Variation	Maximum of 150 RPM for the duration of the phase
VGT (Turbo) Position Change	Maximum of 10% from the start position
Target Temperature Range	509-527 °F (265-275 °C) for minimum of 30 seconds
NOx Values	Maximum difference of 150 ppm between inlet and outlet sensors

Operation failure during Stabilize Low SCR Temperature phase:

The routine will timeout if target temperatures and exhaust flow are not met within 1800 seconds.

Operations Screens - Stabilize Low SCR Temperature Phase



NOx Conversion Efficiency Low Temperature Evaluation Subtest

The purpose for SCR efficiency evaluation is to evaluate SCR performance, and in most cases, assist in determination of whether the SCR is failed or still serviceable. The temperature and mass flow set points allow for evaluation under “less than ideal” conditions for the SCR (relatively low temperature and typical mass flow). There are cases in which the duty cycle of the vehicle allows for very optimum conditions during the On board diagnostic, (heavy loads and high average exhaust temperatures) and there may be only minimum instances of related fault codes, since this test evaluates at “less optimum” conditions the results of the test may indicate failure without setting related DTCs.

After the stabilize low SCR temperature conditions are satisfied, the routine enters the NOx conversion efficiency low temperature evaluation :

Conditions

Condition	Value
SCR Temperature Range	509-527 °F (265-275 °C)
Exhaust Mass Flow Range	27.8-34.4 lb/min (12.6-15.6 kg/min)
NOx Flow Range	0.052-0.054 lb/min (0.0236-0.0245 kg/min)

When conditions are met, urea (DEF) dosing will begin at a rate of 0.8 g/sec (0.028 oz/sec)

Limits (For phase to complete successfully)

SCR Efficiency Value	Time Limit	Behavior
Greater than or equal to 85%	Within first 5 minutes	Subtest will pass
Between 65% and 85%	Within first 5 minutes	DEF dosing continues for 5 more minutes
Does not reach 77%	After 10 minutes	Subtest will fail (See note below)

NOx Conversion Efficiency Low Temperature Evaluation Subtest Failure

In some cases where the efficiency is borderline (within 3-4% of the limit) consider the items below:

- There is possibility of aged SCRs that will finish the evaluation step a few percent below the failure limit after 10 minutes of evaluation. These instances should be handled on a case-by-case basis. For this reason, the test will be uploaded as a .csv file in case additional review is needed. It may be possible that SCR evaluation is borderline or slightly below the limit, but replacement may not be necessary. These cases will most often include vehicles that do not show frequent SCR related faults, and may operate in extreme enough conditions to allow average exhaust temperatures greater than 660 °F (350 °C).

- **In all cases where the SCR shows efficiency at or below the passing limit**, the following checks should always be done prior to SCR replacement:

- Check the DEF quality with refractometer and test strips, and perform visual inspection of the tank for any contaminants
- Inspect SCR inlet for excessive crystal buildup, also inspect the SCR inlet for any indications of contaminants e.g. oil in exhaust from component failure upstream

Post Test Results - Screenshots And Recommendations

NOx sensor evaluation results


The screen shows both High and Low phases with the difference and average value.


Tech Tool


Tech Tool Links Help


Product Product History Diagnose **Test** Calibrate Program Impact


Test result

AHJ Response 






NOx inlet response 

NOx outlet response 

DEF dosing system 

SCR efficiency 

Reference

Icon	Description
	OK
	Test failed
	Test did not complete
	Not tested
	Contact Technical Support

NOx outlet response

- No action needed

DEF dosing system

- No action needed

SCR efficiency

- The SCR is suspected to be faulty

Before replacing the SCR the following actions must be completed

- NOx sensor and Dosing test completed successively
- DEF concentration within specifications
- DEF free from contamination
- SCR inlet free from fuel/oil contamination or excessive crystal buildup

Detailed information

▲ AHJ system values

Not tested

▲ NOx sensor values

NOx	High level	Low level
Average inlet	1101 ppm	349 ppm
Average outlet	1187 ppm	377 ppm
Average difference	86 ppm	27 ppm
MIN threshold	500 ppm	50 ppm
MAX threshold	1500 ppm	500 ppm
MAX difference	100 ppm	50 ppm

Continue >

Chassis ID: M243 1981 VIN: 1M2LR02C7H0001981 Work Order: 104

Product Online

DEF Dosing system and SCR Evaluation Phases

In the screenshot below, step 2 conversion efficiency is not shown because the “fast pass” limit is 85% (shown at 93% in step 1).

Tech Tool

Tech Tool Links Help

Product Product History Diagnose **Test** Calibrate Program Impact

Test result

AHI Response

NOx inlet response

NOx outlet response

DEF dosing system

SCR efficiency

Reference

Icon	Description
	OK
	Test failed

NOx inlet sensor values

NOx outlet sensor values

DEF Dosing system values

Pump duty cycle	No Dosing	Dosing
Average	13 %	13 %
Actual increase	Not used	10 %
MIN expected increase	Not used	8 %
MAX expected increase	Not used	12 %

SCR efficiency values

	Step 1	Step 2
Conversion Efficiency	93 %	0 %
Conversion efficiency time	300 s	600 s
MIN Conversion efficiency threshold	65 %	77 %
Conversion efficiency fast pass minimum limit	85 %	Not used
Exhaust mass flow	28.307 lb/min	0 lb/min
NOx Flow	0.053 lb/min	0 lb/min
T3 - Post DPF Temperature	532 °F	32 °F

Continue >

Chassis ID: N 976465 VIN: 4V4N99EH10H976465 Work Order: 94eats2

Product Online

Step 2 conversion efficiency failed to reach the expected efficiency limits in both steps of the SCR evaluation in the screenshot below. The next test update will allow for a “fast fail” if SCR efficiency does not reach 65% in the first 5 minutes of evaluation.

Tech Tool

Tech Tool Links Help

Product Product History Diagnose **Test** Calibrate Program Impact

Test result

- AHI Response
- NOx inlet response
- NOx outlet response
- DEF dosing system
- SCR efficiency

Reference

Icon	Description
	OK
	Test failed
	Test did not complete
	Not tested
	Contact Technical Support

SCR efficiency

- The SCR is suspected to be faulty

Before replacing the SCR the following actions must be completed

- NOx sensor and Dosing test completed successfully
- DEF concentration within specifications
- DEF free from contamination
- SCR inlet free from fuel/oil contamination or excessive crystal buildup

Detailed information

+

-

▲ AHI system values

▼ NOx sensor values

▲ DEF dosing system values

	No Dosing	Dosing
Average	15 %	24 %
Actual increase	Not used	10 %
MIN expected increase	Not used	8 %
MAX expected increase	Not used	12 %

▲ SCR efficiency values

	Step 1	Step 2
Conversion Efficiency	40 %	53 %
MIN Conversion efficiency threshold	65 %	77 %
Conversion efficiency fast pass minimum limit	65 %	Not used
Conversion efficiency time	300 s	600 s
Exhaust mass flow	28.233 lb/min	28.101 lb/min
NOx flow	0.054 lb/min	0.053 lb/min
T3 - Post DPF Temperature	520 °F	520 °F

[Continue >](#)

Chassis ID: M248 1981 VIN: 1M2LR02C7HM001981 Work Order: 104

Product Online

The screen below shows the rare scenario when one or both sensors fail to reach a minimum value and also exceeds the allowable difference between the sensors.

Test result

AHI Response



NOx inlet response



NOx outlet response



DEF dosing system



SCR efficiency



Reference

Icon	Description
	OK
	Test failed
	Test did not complete
	Not tested
	Contact Technical Support

2589-08-03-18 Exhaust Aftertreatment System Analysis

Information >> Conditions >> Execution >> Result

Result

Recommended actions

AHI Response

- No action needed

NOx inlet response

- Restart the operation and run the NOx sensor subtest
- Refer to the detailed information and check if the NOx inlet or NOx outlet is closest to the fault limit, the sensor with values closest to the fault limit is suspected to be faulty
- Exit and fault trace relevant DTCs

NOx outlet response

- Restart the operation and run the NOx sensor subtest
- Refer to the detailed information and check if the NOx inlet or NOx outlet is closest to the fault limit, the sensor with values closest to the fault limit is suspected to be faulty
- Exit and fault trace relevant DTCs

DEF dosing system

- No action needed

SCR efficiency

- Not tested

Detailed information



AHI system values

NOx inlet sensor values

Internal comments (BO)

The attached pdf document is intended to assist the technician that is unfamiliar with this operation or has questions that may not be answered while performing the operation

Solution visibility

[Dealer distribution](#)

Function(s)/component(s) affected

Function affected

SCR , DEF Dosing , DOC , DPF , Fuel Dosing

Function Group

Function Group

254 catalytic converter; exhaust emission control equipment , 258 emissions after-treatment

Customer effect

Main customer effect

diagnostics/methodology , fault code/display

Fault Codes And Error Codes

OBDII Diagnostic Trouble Codes (P, U, B Format)

P0422 , P0422-00 , P103C , P103C-00 , P20EE , P20EE-00 , P2201 , P2201-64 , P225C , P225C-00 , P225E , P225E-00 , P229F , P229F-64

Administration

Author UT9246H

Dealer ID UT9246H

Last modified by A241298

Creation date 06-01-2020 15:01



Date of last update 11-03-2020 14:03

Status To be published

UNCONTROLLED COPY. Printed document is for temporary use only and should not be retained.



Aftertreatment selective catalytic reduction (SCR) system




2549-08-03-03 NOx Conversion

Simulation

Information >> Conditions >> Execution

Purpose

Caution



Test not supported

The NOx Conversion operation is not supported with this ECM software, it has been replaced with a new Test operation

Please refer to: 2589-08-03-18 Exhaust Aftertreatment System Analysis

Select the Cancel button to exit the operation

Close

Verification - To compare system behaviour before and after repair

Note: Operation may take approximately 20 - 30 minute(s) to complete

Information

Continue > Cancel

