

LED Matrix Headlights, Black including PDLs Plus

Revision: This bulletin replaces bulletin Group 9, 26/19, dated November 18, 2019

Model Year: **As of 2019**

Concern: **Retrofitting**

Information: **Matrix Beam 8IU already installed**



Figure 1

Parts Info: **992.044.902**

Matrix Beam headlights, set, right-hand traffic, darkened **USA**

Installing headlights

- 1 Replace headlights at the left and right. ⇒ *Workshop Manual 'Replacing headlights'*

NOTICE

Voltage drop

- Risk of irreparable damage to control unit
- Risk of damage to control unit
- Fault entries in the control unit
- Coding in the control unit is aborted

- Malfunctions in control unit, even during programming
- ⇒ Prior to disconnecting the control unit, switch off the ignition and remove the ignition key.
- ⇒ Ensure that the power supply is not interrupted during programming.
- ⇒ Connect battery charger/power supply suitable for AGM Type batteries, recommended current rating of 90A fixed voltage 13.5V to 14.5V, tool number VAS 5908.



Information

The **9900 - PIWIS Tester III** instructions take precedence since the description may be different with later Tester releases.

The procedure described here has been structured in general terms; different text or additions may appear on the **9900 - PIWIS Tester III**.

2 Code headlights.

2.1 **9900 - PIWIS Tester 3** must be connected before switching on the ignition.

2.2 Select vehicle type. PIWIS Tester III Diagnostics starts.

2.3 Update vehicle data.

2.3.1 **Additional menu** must now be selected by pressing •F7“ . Press •F11“ to confirm the question “Create vehicle analysis log (VAL)?”.

2.3.2 Select the **Maintenance of vehicle data** function. Press •F12“ until **PR numbers** appears in the Value group column.

2.3.3 Select **Headlights** in the Family column.

- **Select the value: 8JU**

2.3.4 The selected value appears. Press •F8“ to write the value. Wait until the message **Generation of vehicle data is complete. to continue.** appears.

3 **Adjust and calibrate Matrix LED headlights;** ⇒ *Workshop Manual 'Adjusting headlights'*

94 15 23 40:	Retrofitting black Matrix headlights. Includes: Removing and installing wheel housing liners and headlights. Removing and installing light bulb control unit and seal. Removing and installing LED module control unit and LED fan. Without: Adjusting headlights.	Labor time: 148 TU
95 15 16 01:	Adjusting headlights	Labor time: 53 TU

Important Notice: Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2020 Porsche Cars North America, Inc.