

Manufacturer's Certificate

Cayenne (9PA)

44/20 ENU 4400

4

**Wheels with 19-inch Brakes (44/20)**

Revision: This bulletin replaces bulletin Group 4, 9/04, dated August 10, 2004.

Model Year: **As of 2003**

Models: **Cayenne Turbo with power kit (9PA)**

Information: More space required for 19-inch brakes

Subject: Wheels 9 J x 20 H2, Part Nos. 955.362.140.80 9A1 and 955.362.140.90 9A1 for all vehicles in the Cayenne Turbo model range, from model year 2005, and for all older Cayenne Turbo vehicles retrofitted with 19-inch brakes.

Note: The size and design of the specified wheels are almost identical to the wheels used up to and including model year 2004, Part Nos. 955.362.140.50 9A1 and 955.362.140.60 9A1. Given that the 19-inch brake system used as standard in conjunction with an engine power of 368 kW requires more space, the new wheels have been designed with spokes that are approx. 8 mm thinner.

**NOTICE**

**Wheels can contact brake calipers**

- **Risk of damage to wheels**
- ⇒ **More space is required in the wheel disc area to accommodate 19-inch brakes.**
- ⇒ **Never install 20-inch wheels - up to and including the model year 2004 version - on vehicles with a 19-inch brake rotor system.**

The wheels, Part Nos. 955.362.140.50 9A1 and 955.362.140.60 9A1, may only be installed on vehicles **without** a 19-inch brake system.

Wheels Identification on the inside/outside of the wheel disc:  
Wheel size, rim offset (RO) in mm, Part No. and Porsche logo

---

**4**Cayenne (9PA)  
4400 ENU 44/20

---

**Manufacturer's Certificate****Wheels for 18-inch brakes:****Designation****Size****Part No.**

9 J x 20 H2, RO 60

955.362.140.50 9A1

*20-inch Sport Design wheel*

9 J x 20 H2, RO 60

955.362.140.60 9A1

Only permitted on vehicles  
with 18-inch brake system*20-inch Sport Techno wheel*

**Wheels for 19-inch brakes:**

Designation	Size	Part No.
 <i>20-inch Sport Design wheel</i>	9 J x 20 H2, RO 60	955.362.140.80 9A1
 <i>20-inch Sport Techno wheel</i>	9 J x 20 H2, RO 60	955.362.140.91 9A1 (or: 955.362.140.90 9A1, but not for USA)  Permitted on vehicles with 18-inch and 19-inch brake system; optional installing per axle permitted

- References:
- ⇒ *Workshop Manual '44 Wheels and tyres'*
  - ⇒ *Workshop Manual '440519 Removing and installing wheel'*
  - ⇒ *Workshop Manual '44 Tyres'*
  - ⇒ *Workshop Manual '44 Checking disc wheels'*
  - ⇒ *Owner's Manual 'Tyres and wheels'*

**Important Notice:** Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know-how to do the job properly and safely. Part numbers listed in these bulletins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2020 Porsche Cars North America, Inc.